

# *How to Design Programs Languages*

Version 5.0.2

November 6, 2010

The languages documented in this manual are provided by DrRacket to be used with the *How to Design Programs* book.

When programs in these languages are run in DrRacket, any part of the program that was not run is highlighted in orange and black. These colors are intended to give the programmer feedback about the parts of the program that have not been tested. To avoid seeing these colors, use `check-expect` to test your program. Of course, just because you see no colors, does not mean that your program has been fully tested; it simply means that each part of the program has been run (at least once).

# Contents

<b>1</b>	<b>Beginning Student</b>	<b>7</b>
1.1	define . . . . .	13
1.2	define-struct . . . . .	14
1.3	Function Calls . . . . .	14
1.4	Primitive Calls . . . . .	14
1.5	cond . . . . .	15
1.6	if . . . . .	15
1.7	and . . . . .	16
1.8	or . . . . .	16
1.9	Test Cases . . . . .	16
1.10	empty . . . . .	17
1.11	Identifiers . . . . .	17
1.12	Symbols . . . . .	17
1.13	true and false . . . . .	18
1.14	require . . . . .	18
1.15	Primitive Operations . . . . .	19
1.15.1	Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts . . . . .	19
1.15.2	Booleans . . . . .	25
1.15.3	Symbols . . . . .	26
1.15.4	Lists . . . . .	26
1.15.5	Posns . . . . .	31
1.15.6	Characters . . . . .	32
1.15.7	Strings . . . . .	34
1.15.8	Images . . . . .	38

1.15.9 Misc . . . . .	38
<b>2 Beginning Student with List Abbreviations</b>	<b>40</b>
2.1 Quote . . . . .	46
2.2 Quasiquote . . . . .	47
2.3 Primitive Operations . . . . .	47
2.3.1 Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts . . .	47
2.3.2 Booleans . . . . .	54
2.3.3 Symbols . . . . .	55
2.3.4 Lists . . . . .	55
2.3.5 Posns . . . . .	60
2.3.6 Characters . . . . .	61
2.3.7 Strings . . . . .	63
2.3.8 Images . . . . .	66
2.3.9 Misc . . . . .	67
2.4 Unchanged Forms . . . . .	68
<b>3 Intermediate Student</b>	<b>70</b>
3.1 define . . . . .	77
3.2 define-struct . . . . .	77
3.3 local . . . . .	78
3.4 letrec, let, and let* . . . . .	78
3.5 Function Calls . . . . .	78
3.6 time . . . . .	79
3.7 Identifiers . . . . .	79
3.8 Primitive Operations . . . . .	79

3.8.1	Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts . . .	79
3.8.2	Booleans . . . . .	86
3.8.3	Symbols . . . . .	86
3.8.4	Lists . . . . .	87
3.8.5	Posns . . . . .	92
3.8.6	Characters . . . . .	92
3.8.7	Strings . . . . .	94
3.8.8	Images . . . . .	98
3.8.9	Misc . . . . .	98
3.8.10	Numbers (relaxed conditions) . . . . .	99
3.8.11	Higher-Order Functions . . . . .	100
3.9	Unchanged Forms . . . . .	102
<b>4</b>	<b>Intermediate Student with Lambda</b>	<b>104</b>
4.1	define . . . . .	111
4.2	lambda . . . . .	111
4.3	Function Calls . . . . .	112
4.4	Primitive Operation Names . . . . .	112
4.4.1	Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts . . .	112
4.4.2	Booleans . . . . .	118
4.4.3	Symbols . . . . .	119
4.4.4	Lists . . . . .	119
4.4.5	Posns . . . . .	124
4.4.6	Characters . . . . .	125
4.4.7	Strings . . . . .	127
4.4.8	Images . . . . .	130

4.4.9	Misc . . . . .	131
4.4.10	Numbers (relaxed conditions) . . . . .	132
4.4.11	Higher-Order Functions . . . . .	133
4.5	Unchanged Forms . . . . .	135
<b>5</b>	<b>Advanced Student</b>	<b>137</b>
5.1	define . . . . .	147
5.2	define-struct . . . . .	147
5.3	define-datatype . . . . .	147
5.4	lambda . . . . .	148
5.5	Function Calls . . . . .	148
5.6	begin . . . . .	148
5.7	begin0 . . . . .	148
5.8	set! . . . . .	149
5.9	delay . . . . .	149
5.10	shared . . . . .	149
5.11	let . . . . .	149
5.12	recur . . . . .	150
5.13	case . . . . .	150
5.14	match . . . . .	151
5.15	when and unless . . . . .	151
5.16	Primitive Operations . . . . .	151
5.16.1	Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts . . . . .	151
5.16.2	Booleans . . . . .	158
5.16.3	Symbols . . . . .	158
5.16.4	Lists . . . . .	159

5.16.5 Posns . . . . .	164
5.16.6 Characters . . . . .	165
5.16.7 Strings . . . . .	167
5.16.8 Images . . . . .	170
5.16.9 Misc . . . . .	170
5.16.10 Numbers (relaxed conditions) . . . . .	173
5.16.11 Higher-Order Functions . . . . .	173
5.16.12 Reading and Printing . . . . .	175
5.16.13 Vectors . . . . .	176
5.16.14 Boxes . . . . .	177
5.16.15 Hash Tables . . . . .	178
5.17 Unchanged Forms . . . . .	181

<b>Index</b>	<b>183</b>
--------------	------------

# 1 Beginning Student

```
program = def-or-expr ...

def-or-expr = definition
             | expr
             | test-case
             | library-require

definition = (define (id id id ...) expr)
             | (define id expr)
             | (define id (lambda (id id ...) expr))
             | (define-struct id (id ...))

expr = (id expr expr ...) ; function call
       | (prim-op expr ...) ; primitive operation call
       | (cond [expr expr] ... [expr expr])
       | (cond [expr expr] ... [else expr])
       | (if expr expr expr)
       | (and expr expr expr ...)
       | (or expr expr expr ...)
       | empty
       | id
       | id ; identifier
       | 'id ; symbol
       | number
       | true
       | false
       | string
       | character

test-case = (check-expect expr expr)
           | (check-within expr expr expr)
           | (check-member-of expr expr ...)
           | (check-range expr expr expr)
           | (check-error expr expr)
           | (check-error expr)

library-require = (require string)
                 | (require (lib string string ...))
                 | (require (planet string package))

package = (string string number number)
```

An *id* is a sequence of characters not including a space or one of the following:

" , ' ( ) [ ] { } | ; #

A *number* is a number such as 123, 3/2, or 5.5.

A *string* is enclosed by a pair of ". Unlike symbols, strings may be split into characters and manipulated by a variety of primitive functions. For example, "abcdef", "This is a string", and "This is a string with \" inside" are all strings.

A *character* begins with #\ and has the name of the character. For example, #\a, #\b, and #\space are characters.

A *prim-op* is one of:

**Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts**

```
* : (number number number ... -> number)
+ : (number number number ... -> number)
- : (number number ... -> number)
/ : (number number number ... -> number)
< : (real real real ... -> boolean)
<= : (real real real ... -> boolean)
= : (number number number ... -> boolean)
> : (real real real ... -> boolean)
>= : (real real ... -> boolean)
abs : (real -> real)
acos : (number -> number)
add1 : (number -> number)
angle : (number -> real)
asin : (number -> number)
atan : (number -> number)
ceiling : (real -> integer)
complex? : (any -> boolean)
conjugate : (number -> number)
cos : (number -> number)
cosh : (number -> number)
current-seconds : (-> integer)
denominator : (rat -> integer)
e : real
even? : (integer -> boolean)
exact->inexact : (number -> number)
exact? : (number -> boolean)
exp : (number -> number)
expt : (number number -> number)
floor : (real -> integer)
gcd : (integer integer ... -> integer)
imag-part : (number -> real)
inexact->exact : (number -> number)
inexact? : (number -> boolean)
```



```
integer->char : (integer -> char)
integer-sqrt : (number -> integer)
integer? : (any -> boolean)
lcm : (integer integer ... -> integer)
log : (number -> number)
magnitude : (number -> real)
make-polar : (real real -> number)
make-rectangular : (real real -> number)
max : (real real ... -> real)
min : (real real ... -> real)
modulo : (integer integer -> integer)
negative? : (number -> boolean)
number->string : (number -> string)
number? : (any -> boolean)
numerator : (rat -> integer)
odd? : (integer -> boolean)
pi : real
positive? : (number -> boolean)
quotient : (integer integer -> integer)
random : (integer -> integer)
rational? : (any -> boolean)
real-part : (number -> real)
real? : (any -> boolean)
remainder : (integer integer -> integer)
round : (real -> integer)
sgn : (real -> (union 1 1.0 0 0.0 -1 -1.0))
sin : (number -> number)
sinh : (number -> number)
sqr : (number -> number)
sqrt : (number -> number)
sub1 : (number -> number)
tan : (number -> number)
zero? : (number -> boolean)
```

#### **Booleans**

```
boolean=? : (boolean boolean -> boolean)
boolean? : (any -> boolean)
false? : (any -> boolean)
not : (boolean -> boolean)
```

#### **Symbols**

```
symbol->string : (symbol -> string)
symbol=? : (symbol symbol -> boolean)
symbol? : (any -> boolean)
```

#### **Lists**

```

append : ((listof any)
          (listof any)
          (listof any)
          ...
          ->
          (listof any))
assq : (X
        (listof (cons X Y))
        ->
        (union false (cons X Y)))
caaar : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
         ->
         W)
caadr : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
         ->
         (listof Z))
caar : ((cons (cons Z (listof Y)) (listof X)) -> Z)
cadar : ((cons (cons W (cons Z (listof Y))) (listof X))
         ->
         Z)
caddr : ((listof Y) -> Y)
caddr : ((cons W (cons Z (cons Y (listof X)))) -> Y)
cadr : ((cons Z (cons Y (listof X))) -> Y)
car : ((cons Y (listof X)) -> Y)
cdaar : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
         ->
         (listof Z))
cdadr : ((cons W (cons (cons Z (listof Y)) (listof X)))
         ->
         (listof Y))
cdar : ((cons (cons Z (listof Y)) (listof X))
         ->
         (listof Y))
cddar : ((cons (cons W (cons Z (listof Y))) (listof X))
         ->
         (listof Y))
cddr : ((cons W (cons Z (cons Y (listof X))))
         ->
         (listof X))
caddr : ((cons Z (cons Y (listof X))) -> (listof X))

```

```

cdr : ((cons Y (listof X)) -> (listof X))
cons : (X (listof X) -> (listof X))
cons? : (any -> boolean)
eighth : ((listof Y) -> Y)
empty? : (any -> boolean)
fifth : ((listof Y) -> Y)
first : ((cons Y (listof X)) -> Y)
fourth : ((listof Y) -> Y)
length : ((listof any) -> number)
list : (any ... -> (listof any))
list* : (any ... (listof any) -> (listof any))
list-ref : ((listof X) natural-number -> X)
make-list : (natural-number any -> (listof any))
member : (any (listof any) -> boolean)
member? : (any (listof any) -> boolean)
memq : (any (listof any) -> (union false list))
memv : (any (listof any) -> (union false list))
null : empty
null? : (any -> boolean)
pair? : (any -> boolean)
remove : (any (listof any) -> (listof any))
rest : ((cons Y (listof X)) -> (listof X))
reverse : ((listof any) -> list)
second : ((cons Z (cons Y (listof X))) -> Y)
seventh : ((listof Y) -> Y)
sixth : ((listof Y) -> Y)
third : ((cons W (cons Z (cons Y (listof X)))) -> Y)

```

### Posns

```

make-posn : (number number -> posn)
posn : signature
posn-x : (posn -> number)
posn-y : (posn -> number)
posn? : (anything -> boolean)

```

### Characters

```

char->integer : (char -> integer)
char-alphabetic? : (char -> boolean)
char-ci=? : (char char char ... -> boolean)
char-ci<? : (char char char ... -> boolean)
char-ci=? : (char char char ... -> boolean)
char-ci>=? : (char char char ... -> boolean)
char-ci>? : (char char char ... -> boolean)
char-downcase : (char -> char)
char-lower-case? : (char -> boolean)
char-numeric? : (char -> boolean)
char-upcase : (char -> char)
char-upper-case? : (char -> boolean)

```

```

char-whitespace? : (char -> boolean)
char<=? : (char char char ... -> boolean)
char<? : (char char char ... -> boolean)
char=? : (char char char ... -> boolean)
char>=? : (char char char ... -> boolean)
char>? : (char char char ... -> boolean)
char? : (any -> boolean)

```

### Strings

```

explode : (string -> (listof string))
format : (string any ... -> string)
implode : ((listof string) -> string)
int->string : (integer -> string)
list->string : ((listof char) -> string)
make-string : (nat char -> string)
replicate : (nat string -> string)
string : (char ... -> string)
string->int : (string -> integer)
string->list : (string -> (listof char))
string->number : (string -> (union number false))
string->symbol : (string -> symbol)
string-alphabetic? : (string -> boolean)
string-append : (string ... -> string)
string-ci<=? : (string string string ... -> boolean)
string-ci<? : (string string string ... -> boolean)
string-ci=? : (string string string ... -> boolean)
string-ci>=? : (string string string ... -> boolean)
string-ci>? : (string string string ... -> boolean)
string-copy : (string -> string)
string-ith : (string nat -> string)
string-length : (string -> nat)
string-lower-case? : (string -> boolean)
string-numeric? : (string -> boolean)
string-ref : (string nat -> char)
string-upper-case? : (string -> boolean)
string-whitespace? : (string -> boolean)
string<=? : (string string string ... -> boolean)
string<? : (string string string ... -> boolean)
string=? : (string string string ... -> boolean)
string>=? : (string string string ... -> boolean)
string>? : (string string string ... -> boolean)
string? : (any -> boolean)
substng : (string nat nat -> string)

```

### Images

```

image=? : (image image -> boolean)
image? : (any -> boolean)

```

### Misc

```
=~ : (real real non-negative-real -> boolean)
eof : eof
eof-object? : (any -> boolean)
eq? : (any any -> boolean)
equal? : (any any -> boolean)
equal~? : (any any non-negative-real -> boolean)
eqv? : (any any -> boolean)
error : (any ... -> void)
exit : (-> void)
identity : (any -> any)
struct? : (any -> boolean)
```

## 1.1 define

---

```
(define (id id id ...) expr)
```

Defines a function. The first *id* inside the parentheses is the name of the function. All remaining *ids* are the names of the function's arguments. The *expr* is the body of the function, evaluated whenever the function is called. The name of the function cannot be that of a primitive or another definition.

---

```
(define id expr)
```

Defines a constant *id* as a synonym for the value produced by *expr*. The defined name cannot be that of a primitive or another definition, and *id* itself must not appear in *expr*.

---

```
(define id (lambda (id id ...) expr))
```

An alternate form for defining functions. The first *id* is the name of the function. The *ids* in parentheses are the names of the function's arguments, and the *expr* is the body of the function, which evaluated whenever the function is called. The name of the function cannot be that of a primitive or another definition.

---

lambda

The lambda keyword can only be used with define in the alternative function-definition syntax.

## 1.2 define-struct

---

```
(define-struct structid (fieldid ...))
```

Define a new type of structure. The structure's fields are named by the *fieldids* in parentheses. After evaluation of a define-struct form, a set of new primitives is available for creation, extraction, and type-like queries:

- *make-structid* : takes a number of arguments equal to the number of fields in the structure type, and creates a new instance of the structure type.
- *structid-fieldid* : takes an instance of the structure and returns the field named by *structid*.
- *structid?* : takes any value, and returns `true` if the value is an instance of the structure type.
- *structid* : an identifier representing the structure type, but never used directly.

The created names must not be the same as a primitive or another defined name.

## 1.3 Function Calls

---

```
(id expr expr ...)
```

Calls a function. The *id* must refer to a defined function, and the *exprs* are evaluated from left to right to produce the values that are passed as arguments to the function. The result of the function call is the result of evaluating the function's body with every instance of an argument name replaced by the value passed for that argument. The number of argument *exprs* must be the same as the number of arguments expected by the function.

---

```
(#%app id expr expr ...)
```

A function call can be written with `%app`, though it's practically never written that way.

## 1.4 Primitive Calls

---

```
(prim-op expr ...)
```

Like a function call, but for a primitive operation. The *expr*s are evaluated from left to right, and passed as arguments to the primitive operation named by *prim-op*. A *define-struct* form creates new primitives.

## 1.5 cond

---

```
(cond [expr expr] ... [expr expr])
```

A *cond* form contains one or more “lines” that are surrounded by parentheses or square brackets. Each line contains two *expr*s: a question *expr* and an answer *expr*.

The lines are considered in order. To evaluate a line, first evaluate the question *expr*. If the result is *true*, then the result of the whole *cond* expression is the result of evaluating the answer *expr* of the same line. If the result of evaluating the question *expr* is *false*, the line is discarded and evaluation proceeds with the next line.

If the result of a question *expr* is neither *true* nor *false*, it is an error. If none of the question *expr*s evaluates to *true*, it is also an error.

---

```
(cond [expr expr] ... [else expr])
```

This form of *cond* is similar to the prior one, except that the final *else* clause is always taken if no prior line’s test expression evaluates to *true*. In other words, *else* acts like *true*, so there is no possibility to “fall off the end” of the *cond* form.

---

*else*

The *else* keyword can be used only with *cond*.

## 1.6 if

---

```
(if expr expr expr)
```

The first *expr* (known as the “test” *expr*) is evaluated. If it evaluates to *true*, the result of the *if* expression is the result of evaluating the second *expr* (often called the “then” *expr*). If the text *expr* evaluates to *false*, the result of the *if* expression is the result of evaluating the third *expr* (known as the “else” *expr*). If the result of evaluating the test *expr* is neither *true* nor *false*, it is an error.

## 1.7 and

---

`(and expr expr expr ...)`

The *exprs* are evaluated from left to right. If the first *expr* evaluates to `false`, the `and` expression immediately evaluates to `false`. If the first *expr* evaluates to `true`, the next expression is considered. If all *exprs* evaluate to `true`, the `and` expression evaluates to `true`. If any of the expressions evaluate to a value other than `true` or `false`, it is an error.

## 1.8 or

---

`(or expr expr expr ...)`

The *exprs* are evaluated from left to right. If the first *expr* evaluates to `true`, the `or` expression immediately evaluates to `true`. If the first *expr* evaluates to `false`, the next expression is considered. If all *exprs* evaluate to `false`, the `or` expression evaluates to `false`. If any of the expressions evaluate to a value other than `true` or `false`, it is an error.

## 1.9 Test Cases

---

`(check-expect expr expr)`

A test case to check that the first *expr* produces the same value as the second *expr*, where the latter is normally an immediate value.

---

`(check-within expr expr expr)`

Like `check-expect`, but with an extra expression that produces a number *delta*. The test case checks that each number in the result of the first *expr* is within *delta* of each corresponding number from the second *expr*.

---

`(check-error expr expr)`  
`(check-error expr)`

A test case to check that the first *expr* signals an error, where the error messages matches the string produced by the second *expr*, if it is present.

---

`(check-member-of expr expr expr ...)`



A test case to check that the first *expr* produces an element that is equivalent to one of the following *exprs*.

---

```
(check-range expr expr expr)
```

A test case to check that the first *expr* produces a number inbetween the numbers produced by the second and third *exprs*, inclusive.

## 1.10 empty

---

```
empty : empty?
```

The empty list.

## 1.11 Identifiers

---

*id*

An *id* refers to a defined constant or argument within a function body. If no definition or argument matches the *id* name, an error is reported. Similarly, if *id* matches the name of a defined function or primitive operation, an error is reported.

## 1.12 Symbols

---

```
'id  
(quote id)
```

A quoted *id* is a symbol. A symbol is a constant, like 0 and `empty`.

Normally, a symbol is written with a `'`, like `'apple`, but it can also be written with `quote`, like `(quote apple)`.

The *id* for a symbol is a sequence of characters not including a space or one of the following:

```
" , ' ' ( ) [ ] { } | | ; #
```

### 1.13 true and false

---

`true` : `boolean?`

The true value.

---

`false` : `boolean?`

The false value.

### 1.14 require

---

`(require string)`

Makes the definitions of the module specified by `string` available in the current module (i.e., current file), where `string` refers to a file relative to the enclosing file.

The `string` is constrained in several ways to avoid problems with different path conventions on different platforms: a `/` is a directory separator, `.` always means the current directory, `..` always means the parent directory, path elements can use only `a` through `z` (uppercase or lowercase), `0` through `9`, `=`, `_`, and `.`, and the string cannot be empty or contain a leading or trailing `/`.

---

`(require module-id)`

Accesses a file in an installed library. The library name is an identifier with the same constraints as for a relative-path string, with the additional constraint that it must not contain a `..`.

---

`(require (lib string string ...))`

Accesses a file in an installed library, making its definitions available in the current module (i.e., current file). The first `string` names the library file, and the remaining `strings` name the collection (and sub-collection, and so on) where the file is installed. Each string is constrained in the same way as for the `(require string)` form.

---

`(require (planet string (string string number number)))`

Accesses a library that is distributed on the internet via the PLaneT server, making its definitions available in the current module (i.e., current file).

## 1.15 Primitive Operations

### 1.15.1 Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts

---

`*` : (number number number ... -> number)

Purpose: to compute the product of all of the input numbers

---

`+` : (number number number ... -> number)

Purpose: to compute the sum of the input numbers

---

`-` : (number number ... -> number)

Purpose: to subtract the second (and following) number(s) from the first; negate the number if there is only one argument

---

`/` : (number number number ... -> number)

Purpose: to divide the first by the second (and all following) number(s); try (/ 3 4) and (/ 3 2 2) only the first number can be zero.

---

`<` : (real real real ... -> boolean)

Purpose: to compare real numbers for less-than

---

`<=` : (real real real ... -> boolean)

Purpose: to compare real numbers for less-than or equality

---

`=` : (number number number ... -> boolean)

Purpose: to compare numbers for equality

---

`>` : (real real real ... -> boolean)

Purpose: to compare real numbers for greater-than

---

`>=` : (real real ... -> boolean)

Purpose: to compare real numbers for greater-than or equality

---

`abs : (real -> real)`

Purpose: to compute the absolute value of a real number

---

`acos : (number -> number)`

Purpose: to compute the arccosine (inverse of cos) of a number

---

`add1 : (number -> number)`

Purpose: to compute a number one larger than a given number

---

`angle : (number -> real)`

Purpose: to extract the angle from a complex number

---

`asin : (number -> number)`

Purpose: to compute the arcsine (inverse of sin) of a number

---

`atan : (number -> number)`

Purpose: to compute the arctan (inverse of tan) of a number

---

`ceiling : (real -> integer)`

Purpose: to determine the closest integer (exact or inexact) above a real number

---

`complex? : (any -> boolean)`

Purpose: to determine whether some value is complex

---

`conjugate : (number -> number)`

Purpose: to compute the conjugate of a complex number

---

`cos : (number -> number)`

Purpose: to compute the cosine of a number (radians)

---

`cosh` : (number -> number)

Purpose: to compute the hyperbolic cosine of a number

---

`current-seconds` : (-> integer)

Purpose: to compute the current time in seconds elapsed (since a platform-specific starting date)

---

`denominator` : (rat -> integer)

Purpose: to compute the denominator of a rational

---

`e` : real

Purpose: Euler's number

---

`even?` : (integer -> boolean)

Purpose: to determine if some integer (exact or inexact) is even or not

---

`exact->inexact` : (number -> number)

Purpose: to convert an exact number to an inexact one

---

`exact?` : (number -> boolean)

Purpose: to determine whether some number is exact

---

`exp` : (number -> number)

Purpose: to compute e raised to a number

---

`expt` : (number number -> number)

Purpose: to compute the power of the first to the second number

---

`floor` : (real -> integer)

Purpose: to determine the closest integer (exact or inexact) below a real number

---

```
gcd : (integer integer ... -> integer)
```

Purpose: to compute the greatest common divisor of two integers (exact or inexact)

---

```
imag-part : (number -> real)
```

Purpose: to extract the imaginary part from a complex number

---

```
inexact->exact : (number -> number)
```

Purpose: to approximate an inexact number by an exact one

---

```
inexact? : (number -> boolean)
```

Purpose: to determine whether some number is inexact

---

```
integer->char : (integer -> char)
```

Purpose: to lookup the character that corresponds to the given integer (exact only!) in the ASCII table (if any)

---

```
integer-sqrt : (number -> integer)
```

Purpose: to compute the integer (exact or inexact) square root of a number

---

```
integer? : (any -> boolean)
```

Purpose: to determine whether some value is an integer (exact or inexact)

---

```
lcm : (integer integer ... -> integer)
```

Purpose: to compute the least common multiple of two integers (exact or inexact)

---

```
log : (number -> number)
```

Purpose: to compute the base-e logarithm of a number

---

```
magnitude : (number -> real)
```

Purpose: to determine the magnitude of a complex number

---

```
make-polar : (real real -> number)
```

Purpose: to create a complex from a magnitude and angle

---

```
make-rectangular : (real real -> number)
```

Purpose: to create a complex from a real and an imaginary part

---

```
max : (real real ... -> real)
```

Purpose: to determine the largest number

---

```
min : (real real ... -> real)
```

Purpose: to determine the smallest number

---

```
modulo : (integer integer -> integer)
```

Purpose: to find the remainder of the division of the first number by the second; try (modulo 4 3) (modulo 4 -3)

---

```
negative? : (number -> boolean)
```

Purpose: to determine if some value is strictly smaller than zero

---

```
number->string : (number -> string)
```

Purpose: to convert a number to a string

---

```
number? : (any -> boolean)
```

Purpose: to determine whether some value is a number

---

```
numerator : (rat -> integer)
```

Purpose: to compute the numerator of a rational

---

```
odd? : (integer -> boolean)
```

Purpose: to determine if some integer (exact or inexact) is odd or not

---

`pi` : real

Purpose: the ratio of a circle's circumference to its diameter

---

`positive?` : (number -> boolean)

Purpose: to determine if some value is strictly larger than zero

---

`quotient` : (integer integer -> integer)

Purpose: to divide the first integer (exact or inexact) into the second; try (quotient 3 4) and (quotient 4 3)

---

`random` : (integer -> integer)

Purpose: to generate a random natural number less than some given integer (exact only!)

---

`rational?` : (any -> boolean)

Purpose: to determine whether some value is a rational number

---

`real-part` : (number -> real)

Purpose: to extract the real part from a complex number

---

`real?` : (any -> boolean)

Purpose: to determine whether some value is a real number

---

`remainder` : (integer integer -> integer)

Purpose: to determine the remainder of dividing the first by the second integer (exact or inexact)

---

`round` : (real -> integer)

Purpose: to round a real number to an integer (rounds to even to break ties)



---

`sgn` : (real -> (union 1 1.0 0 0.0 -1 -1.0))

Purpose: to compute the sign of a real number

---

`sin` : (number -> number)

Purpose: to compute the sine of a number (radians)

---

`sinh` : (number -> number)

Purpose: to compute the hyperbolic sine of a number

---

`sqr` : (number -> number)

Purpose: to compute the square of a number

---

`sqrt` : (number -> number)

Purpose: to compute the square root of a number

---

`sub1` : (number -> number)

Purpose: to compute a number one smaller than a given number

---

`tan` : (number -> number)

Purpose: to compute the tangent of a number (radians)

---

`zero?` : (number -> boolean)

Purpose: to determine if some value is zero or not

---

### 1.15.2 Booleans

---

`boolean=?` : (boolean boolean -> boolean)

Purpose: to determine whether two booleans are equal

---

`boolean?` : (any -> boolean)

Purpose: to determine whether some value is a boolean

---

`false?` : (any -> boolean)

Purpose: to determine whether a value is false

---

`not` : (boolean -> boolean)

Purpose: to compute the negation of a boolean value

---

### 1.15.3 Symbols

---

`symbol->string` : (symbol -> string)

Purpose: to convert a symbol to a string

---

`symbol=?` : (symbol symbol -> boolean)

Purpose: to determine whether two symbols are equal

---

`symbol?` : (any -> boolean)

Purpose: to determine whether some value is a symbol

---

### 1.15.4 Lists

---

`append` : ((listof any)  
          (listof any)  
          (listof any)  
          ...  
          ->  
          (listof any))

Purpose: to create a single list from several, by juxtaposition of the items

---

```
assq : (X
      (listof (cons X Y))
      ->
      (union false (cons X Y)))
```

Purpose: to determine whether some item is the first item of a pair in a list of pairs

---

```
caaar : ((cons
         (cons (cons W (listof Z)) (listof Y))
         (listof X))
        ->
        W)
```

Purpose: to select the first item of the first list in the first list of a list

---

```
caadr : ((cons
         (cons (cons W (listof Z)) (listof Y))
         (listof X))
        ->
        (listof Z))
```

Purpose: to select the rest of the first list in the first list of a list

---

```
caar : ((cons (cons Z (listof Y)) (listof X)) -> Z)
```

Purpose: to select the first item of the first list in a list

---

```
cadar : ((cons (cons W (cons Z (listof Y))) (listof X))
        ->
        Z)
```

Purpose: to select the second item of the first list of a list

---

```
caddr : ((listof Y) -> Y)
```

Purpose: to select the fourth item of a non-empty list

---

```
caddr : ((cons W (cons Z (cons Y (listof X)))) -> Y)
```

Purpose: to select the third item of a non-empty list

---

```
cadr : ((cons Z (cons Y (listof X))) -> Y)
```

Purpose: to select the second item of a non-empty list

---

```
car : ((cons Y (listof X)) -> Y)
```

Purpose: to select the first item of a non-empty list

---

```
cdaar : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
         ->
         (listof Z))
```

Purpose: to select the rest of the first list in the first list of a list

---

```
cdadr : ((cons W (cons (cons Z (listof Y)) (listof X)))
         ->
         (listof Y))
```

Purpose: to select the rest of the first list in the rest of a list

---

```
cdar : ((cons (cons Z (listof Y)) (listof X))
        ->
        (listof Y))
```

Purpose: to select the rest of a non-empty list in a list

---

```
cddar : ((cons (cons W (cons Z (listof Y))) (listof X))
         ->
         (listof Y))
```

Purpose: to select the rest of the rest of the first list of a list

---

```
cddr : ((cons W (cons Z (cons Y (listof X))))
        ->
        (listof X))
```

Purpose: to select the rest of the rest of the rest of a list

---

```
cddr : ((cons Z (cons Y (listof X))) -> (listof X))
```

Purpose: to select the rest of the rest of a list

---

```
cdr : ((cons Y (listof X)) -> (listof X))
```

Purpose: to select the rest of a non-empty list

---

```
cons : (X (listof X) -> (listof X))
```

Purpose: to construct a list

---

```
cons? : (any -> boolean)
```

Purpose: to determine whether some value is a constructed list

---

```
eighth : ((listof Y) -> Y)
```

Purpose: to select the eighth item of a non-empty list

---

```
empty? : (any -> boolean)
```

Purpose: to determine whether some value is the empty list

---

```
fifth : ((listof Y) -> Y)
```

Purpose: to select the fifth item of a non-empty list

---

```
first : ((cons Y (listof X)) -> Y)
```

Purpose: to select the first item of a non-empty list

---

```
fourth : ((listof Y) -> Y)
```

Purpose: to select the fourth item of a non-empty list

---

```
length : ((listof any) -> number)
```

Purpose: to compute the number of items on a list

---

```
list : (any ... -> (listof any))
```

Purpose: to construct a list of its arguments

---

```
list* : (any ... (listof any) -> (listof any))
```

Purpose: to construct a list by adding multiple items to a list

---

```
list-ref : ((listof X) natural-number -> X)
```

Purpose: to extract the indexed item from the list

---

```
make-list : (natural-number any -> (listof any))
```

Purpose: (make-list k x) constructs a list of k copies of x

---

```
member : (any (listof any) -> boolean)
```

Purpose: to determine whether some value is on the list (comparing values with equal?)

---

```
member? : (any (listof any) -> boolean)
```

Purpose: to determine whether some value is on the list (comparing values with equal?)

---

```
memq : (any (listof any) -> (union false list))
```

Purpose: to determine whether some value is on some list if so, it produces the suffix of the list that starts with x if not, it produces false. (It compares values with the eq? predicate.)

---

```
memv : (any (listof any) -> (union false list))
```

Purpose: to determine whether some value is on the list if so, it produces the suffix of the list that starts with x if not, it produces false. (it compares values with the eqv? predicate.)

---

```
null : empty
```

Purpose: the empty list

---

```
null? : (any -> boolean)
```

Purpose: to determine whether some value is the empty list

---

`pair?` : (any -> boolean)

Purpose: to determine whether some value is a constructed list

---

`remove` : (any (listof any) -> (listof any))

Purpose: to construct a list like the given one with the first occurrence of the given item removed (comparing values with equal?)

---

`rest` : ((cons Y (listof X)) -> (listof X))

Purpose: to select the rest of a non-empty list

---

`reverse` : ((listof any) -> list)

Purpose: to create a reversed version of a list

---

`second` : ((cons Z (cons Y (listof X))) -> Y)

Purpose: to select the second item of a non-empty list

---

`seventh` : ((listof Y) -> Y)

Purpose: to select the seventh item of a non-empty list

---

`sixth` : ((listof Y) -> Y)

Purpose: to select the sixth item of a non-empty list

---

`third` : ((cons W (cons Z (cons Y (listof X)))) -> Y)

Purpose: to select the third item of a non-empty list

---

### 1.15.5 Posns

---

`make-posn` : (number number -> posn)

Purpose: to construct a posn

---

`posn` : signature

Purpose: signature for posns

---

`posn-x` : (`posn` -> number)

Purpose: to extract the x component of a posn

---

`posn-y` : (`posn` -> number)

Purpose: to extract the y component of a posn

---

`posn?` : (`anything` -> boolean)

Purpose: to determine if its input is a posn

---

### 1.15.6 Characters

---

`char->integer` : (`char` -> integer)

Purpose: to lookup the number that corresponds to the given character in the ASCII table (if any)

---

`char-alphabetic?` : (`char` -> boolean)

Purpose: to determine whether a character represents an alphabetic character

---

`char-ci<=?` : (`char char char ...` -> boolean)

Purpose: to determine whether a character precedes another (or is equal to it) in a case-insensitive manner

---

`char-ci<?` : (`char char char ...` -> boolean)

Purpose: to determine whether a character precedes another in a case-insensitive manner

---

`char-ci=?` : (`char char char ...` -> boolean)

Purpose: to determine whether two characters are equal in a case-insensitive manner

---



---

`char-ci>=?` : (char char char ... -> boolean)

Purpose: to determine whether a character succeeds another (or is equal to it) in a case-insensitive manner

---

`char-ci>?` : (char char char ... -> boolean)

Purpose: to determine whether a character succeeds another in a case-insensitive manner

---

`char-downcase` : (char -> char)

Purpose: to determine the equivalent lower-case character

---

`char-lower-case?` : (char -> boolean)

Purpose: to determine whether a character is a lower-case character

---

`char-numeric?` : (char -> boolean)

Purpose: to determine whether a character represents a digit

---

`char-upcase` : (char -> char)

Purpose: to determine the equivalent upper-case character

---

`char-upper-case?` : (char -> boolean)

Purpose: to determine whether a character is an upper-case character

---

`char-whitespace?` : (char -> boolean)

Purpose: to determine whether a character represents space

---

`char<=?` : (char char char ... -> boolean)

Purpose: to determine whether a character precedes another (or is equal to it)

---

`char<?` : (char char char ... -> boolean)

Purpose: to determine whether a character precedes another

---

`char=?` : (char char char ... -> boolean)

Purpose: to determine whether two characters are equal

---

`char>=?` : (char char char ... -> boolean)

Purpose: to determine whether a character succeeds another (or is equal to it)

---

`char>?` : (char char char ... -> boolean)

Purpose: to determine whether a character succeeds another

---

`char?` : (any -> boolean)

Purpose: to determine whether a value is a character

### 1.15.7 Strings

---

`explode` : (string -> (listof string))

Purpose: to translate a string into a list of 1-letter strings

---

`format` : (string any ... -> string)

Purpose: to format a string, possibly embedding values

---

`implode` : ((listof string) -> string)

Purpose: to concatenate the list of 1-letter strings into one string

---

`int->string` : (integer -> string)

Purpose: to convert an integer in [0,55295] or [57344 1114111] to a 1-letter string

---

`list->string` : ((listof char) -> string)

Purpose: to convert a s list of characters into a string

---

`make-string` : (nat char -> string)

Purpose: to produce a string of given length from a single given character

---

`replicate` : (nat string -> string)

Purpose: to replicate the given string

---

`string` : (char ... -> string)

Purpose: (string c1 c2 ...) builds a string

---

`string->int` : (string -> integer)

Purpose: to convert a 1-letter string to an integer in [0,55295] or [57344, 1114111]

---

`string->list` : (string -> (listof char))

Purpose: to convert a string into a list of characters

---

`string->number` : (string -> (union number false))

Purpose: to convert a string into a number, produce false if impossible

---

`string->symbol` : (string -> symbol)

Purpose: to convert a string into a symbol

---

`string-alphabetic?` : (string -> boolean)

Purpose: to determine whether all 'letters' in the string are alphabetic

---

`string-append` : (string ... -> string)

Purpose: to juxtapose the characters of several strings

---

`string-ci<=?` : (string string string ... -> boolean)

Purpose: to determine whether one string alphabetically precedes another (or is equal to it) in a case-insensitive manner

---

`string-ci<? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically precedes another in a case-insensitive manner

---

`string-ci=? : (string string string ... -> boolean)`

Purpose: to compare two strings character-wise in a case-insensitive manner

---

`string-ci>=? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically succeeds another (or is equal to it) in a case-insensitive manner

---

`string-ci>? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically succeeds another in a case-insensitive manner

---

`string-copy : (string -> string)`

Purpose: to copy a string

---

`string-ith : (string nat -> string)`

Purpose: to extract the *i*th 1-letter substring from the given one

---

`string-length : (string -> nat)`

Purpose: to determine the length of a string

---

`string-lower-case? : (string -> boolean)`

Purpose: to determine whether all 'letters' in the string are lower case

---

`string-numeric? : (string -> boolean)`

Purpose: to determine whether all 'letters' in the string are numeric

---

`string-ref : (string nat -> char)`

Purpose: to extract the i-th character from a string

---

`string-upper-case? : (string -> boolean)`

Purpose: to determine whether all 'letters' in the string are upper case

---

`string-whitespace? : (string -> boolean)`

Purpose: to determine whether all 'letters' in the string are white space

---

`string<=? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically precedes another (or is equal to it)

---

`string<? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically precedes another

---

`string=? : (string string string ... -> boolean)`

Purpose: to compare two strings character-wise

---

`string>=? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically succeeds another (or is equal to it)

---

`string>? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically succeeds another

---

`string? : (any -> boolean)`

Purpose: to determine whether a value is a string

---

`substring : (string nat nat -> string)`

Purpose: to extract the substring starting at a 0-based index up to the second 0-based index (exclusive)

### 1.15.8 Images

---

`image=?` : (image image -> boolean)

Purpose: to determine whether two images are equal

---

`image?` : (any -> boolean)

Purpose: to determine whether a value is an image

### 1.15.9 Misc

---

`=~` : (real real non-negative-real -> boolean)

Purpose: to check whether two real numbers are within some amount (the third argument) of either other

---

`eof` : eof

Purpose: the end-of-file value

---

`eof-object?` : (any -> boolean)

Purpose: to determine whether some value is the end-of-file value

---

`eq?` : (any any -> boolean)

Purpose: to determine whether two values are equivalent from the computer's perspective (intensional)

---

`equal?` : (any any -> boolean)

Purpose: to determine whether two values are structurally equal where basic values are compared with the `eqv?` predicate

---

`equal~?` : (any any non-negative-real -> boolean)

Purpose: to compare like `equal?` on the first two arguments, except using `=~` in the case of real numbers

---

`eqv?` : (any any -> boolean)

Purpose: to determine whether two values are equivalent from the perspective of all functions that can be applied to it (extensional)

---

`error` : (any ... -> void)

Purpose: to signal an error, combining the given values into an error message.

If any of the values' printed representations is too long, it is truncated and “...” is put into the string. If the first value is a symbol, it is treated specially; it is suffixed with a colon and a space (the intention is that the symbol is the name of the function signalling the error).

---

`exit` : (-> void)

Purpose: to exit the running program

---

`identity` : (any -> any)

Purpose: to return the argument unchanged

---

`struct?` : (any -> boolean)

Purpose: to determine whether some value is a structure

## 2 Beginning Student with List Abbreviations

```
program = def-or-expr ...

def-or-expr = definition
             | expr
             | test-case
             | library-require

definition = (define (id id id ...) expr)
             | (define id expr)
             | (define id (lambda (id id ...) expr))
             | (define-struct id (id ...))

expr = (id expr expr ...) ; function call
       | (prim-op expr ...) ; primitive operation call
       | (cond [expr expr] ... [expr expr])
       | (cond [expr expr] ... [else expr])
       | (if expr expr expr)
       | (and expr expr expr ...)
       | (or expr expr expr ...)
       | empty
       | id
       | 'quoted ; quoted value
       | 'quasiquoted ; quasiquote
       | number
       | true
       | false
       | string
       | character

quoted = id
        | number
        | string
        | character
        | (quoted ...)
        | 'quoted
        | 'quoted
        | ,quoted
        | ,@quoted

quasiquoted = id
             | number
             | string
             | character
```



```

| (quasiquoted ...)
| 'quasiquoted
| `quasiquoted
| ,expr
| ,@expr

test-case = (check-expect expr expr)
| (check-within expr expr expr)
| (check-member-of expr expr ...)
| (check-range expr expr expr)
| (check-error expr expr)
| (check-error expr)

library-require = (require string)
| (require (lib string string ...))
| (require (planet string package))

package = (string string number number)

```

An *id* is a sequence of characters not including a space or one of the following:

```
" , ' ( ) [ ] { } | ; #
```

A *number* is a number such as 123, 3/2, or 5.5.

A *string* is enclosed by a pair of ". Unlike symbols, strings may be split into characters and manipulated by a variety of primitive functions. For example, "abcdef", "This is a string", and "This is a string with \" inside" are all strings.

A *character* begins with #\ and has the name of the character. For example, #\a, #\b, and #\space are characters.

A *prim-op* is one of:

**Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts**

```

* : (number number number ... -> number)
+ : (number number number ... -> number)
- : (number number ... -> number)
/ : (number number number ... -> number)
< : (real real real ... -> boolean)
<=: (real real real ... -> boolean)
=: (number number number ... -> boolean)
> : (real real real ... -> boolean)
>=: (real real ... -> boolean)
abs : (real -> real)
acos : (number -> number)
add1 : (number -> number)
angle : (number -> real)

```

```

asin : (number -> number)
atan : (number -> number)
ceiling : (real -> integer)
complex? : (any -> boolean)
conjugate : (number -> number)
cos : (number -> number)
cosh : (number -> number)
current-seconds : (-> integer)
denominator : (rat -> integer)
e : real
even? : (integer -> boolean)
exact->inexact : (number -> number)
exact? : (number -> boolean)
exp : (number -> number)
expt : (number number -> number)
floor : (real -> integer)
gcd : (integer integer ... -> integer)
imag-part : (number -> real)
inexact->exact : (number -> number)
inexact? : (number -> boolean)
integer->char : (integer -> char)
integer-sqrt : (number -> integer)
integer? : (any -> boolean)
lcm : (integer integer ... -> integer)
log : (number -> number)
magnitude : (number -> real)
make-polar : (real real -> number)
make-rectangular : (real real -> number)
max : (real real ... -> real)
min : (real real ... -> real)
modulo : (integer integer -> integer)
negative? : (number -> boolean)
number->string : (number -> string)
number? : (any -> boolean)
numerator : (rat -> integer)
odd? : (integer -> boolean)
pi : real
positive? : (number -> boolean)
quotient : (integer integer -> integer)
random : (integer -> integer)
rational? : (any -> boolean)
real-part : (number -> real)
real? : (any -> boolean)
remainder : (integer integer -> integer)
round : (real -> integer)
sgn : (real -> (union 1 1.0 0 0.0 -1 -1.0))

```

```

sin : (number -> number)
sinh : (number -> number)
sqr : (number -> number)
sqrt : (number -> number)
sub1 : (number -> number)
tan : (number -> number)
zero? : (number -> boolean)

```

### Booleans

```

boolean=? : (boolean boolean -> boolean)
boolean? : (any -> boolean)
false? : (any -> boolean)
not : (boolean -> boolean)

```

### Symbols

```

symbol->string : (symbol -> string)
symbol=? : (symbol symbol -> boolean)
symbol? : (any -> boolean)

```

### Lists

```

append : ((listof any)
          (listof any)
          (listof any)
          ...
          ->
          (listof any))

assq : (X
        (listof (cons X Y))
        ->
        (union false (cons X Y)))

caaar : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
        ->
        W)

caadr : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
        ->
        (listof Z))

caar : ((cons (cons Z (listof Y)) (listof X)) -> Z)
cadar : ((cons (cons W (cons Z (listof Y))) (listof X))
        ->
        Z)

caddr : ((listof Y) -> Y)
caddr : ((cons W (cons Z (cons Y (listof X)))) -> Y)
cadr : ((cons Z (cons Y (listof X))) -> Y)
car : ((cons Y (listof X)) -> Y)

```

```

cdaar : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
         ->
         (listof Z))
cdadr : ((cons W (cons (cons Z (listof Y)) (listof X)))
         ->
         (listof Y))
cdar : ((cons (cons Z (listof Y)) (listof X))
        ->
        (listof Y))
cddar : ((cons (cons W (cons Z (listof Y))) (listof X))
         ->
         (listof Y))
cddddr : ((cons W (cons Z (cons Y (listof X))))
          ->
          (listof X))
cddr : ((cons Z (cons Y (listof X))) -> (listof X))
cdr : ((cons Y (listof X)) -> (listof X))
cons : (X (listof X) -> (listof X))
cons? : (any -> boolean)
eighth : ((listof Y) -> Y)
empty? : (any -> boolean)
fifth : ((listof Y) -> Y)
first : ((cons Y (listof X)) -> Y)
fourth : ((listof Y) -> Y)
length : ((listof any) -> number)
list : (any ... -> (listof any))
list* : (any ... (listof any) -> (listof any))
list-ref : ((listof X) natural-number -> X)
make-list : (natural-number any -> (listof any))
member : (any (listof any) -> boolean)
member? : (any (listof any) -> boolean)
memq : (any (listof any) -> (union false list))
memv : (any (listof any) -> (union false list))
null : empty
null? : (any -> boolean)
pair? : (any -> boolean)
remove : (any (listof any) -> (listof any))
rest : ((cons Y (listof X)) -> (listof X))
reverse : ((listof any) -> list)
second : ((cons Z (cons Y (listof X))) -> Y)
seventh : ((listof Y) -> Y)
sixth : ((listof Y) -> Y)
third : ((cons W (cons Z (cons Y (listof X)))) -> Y)

```

## Posns

```
make-posn : (number number -> posn)
posn : signature
posn-x : (posn -> number)
posn-y : (posn -> number)
posn? : (anything -> boolean)
```

### Characters

```
char->integer : (char -> integer)
char-alphabetic? : (char -> boolean)
char-ci<=? : (char char char ... -> boolean)
char-ci<? : (char char char ... -> boolean)
char-ci=? : (char char char ... -> boolean)
char-ci>=? : (char char char ... -> boolean)
char-ci>? : (char char char ... -> boolean)
char-downcase : (char -> char)
char-lower-case? : (char -> boolean)
char-numeric? : (char -> boolean)
char-upcase : (char -> char)
char-upper-case? : (char -> boolean)
char-whitespace? : (char -> boolean)
char<=? : (char char char ... -> boolean)
char<? : (char char char ... -> boolean)
char=? : (char char char ... -> boolean)
char>=? : (char char char ... -> boolean)
char>? : (char char char ... -> boolean)
char? : (any -> boolean)
```

### Strings

```
explode : (string -> (listof string))
format : (string any ... -> string)
implode : ((listof string) -> string)
int->string : (integer -> string)
list->string : ((listof char) -> string)
make-string : (nat char -> string)
replicate : (nat string -> string)
string : (char ... -> string)
string->int : (string -> integer)
string->list : (string -> (listof char))
string->number : (string -> (union number false))
string->symbol : (string -> symbol)
string-alphabetic? : (string -> boolean)
string-append : (string ... -> string)
string-ci<=? : (string string string ... -> boolean)
string-ci<? : (string string string ... -> boolean)
string-ci=? : (string string string ... -> boolean)
string-ci>=? : (string string string ... -> boolean)
string-ci>? : (string string string ... -> boolean)
string-copy : (string -> string)
```

```

string-ith : (string nat -> string)
string-length : (string -> nat)
string-lower-case? : (string -> boolean)
string-numeric? : (string -> boolean)
string-ref : (string nat -> char)
string-upper-case? : (string -> boolean)
string-whitespace? : (string -> boolean)
string<=? : (string string string ... -> boolean)
string<? : (string string string ... -> boolean)
string=? : (string string string ... -> boolean)
string>=? : (string string string ... -> boolean)
string>? : (string string string ... -> boolean)
string? : (any -> boolean)
substring : (string nat nat -> string)

```

### Images

```

image=? : (image image -> boolean)
image? : (any -> boolean)

```

### Misc

```

=~ : (real real non-negative-real -> boolean)
eof : eof
eof-object? : (any -> boolean)
eq? : (any any -> boolean)
equal? : (any any -> boolean)
equal~? : (any any non-negative-real -> boolean)
eqv? : (any any -> boolean)
error : (any ... -> void)
exit : (-> void)
identity : (any -> any)
struct? : (any -> boolean)

```

## 2.1 Quote

---

```

'quoted


```

Creates symbols and abbreviates nested lists.

Normally, this form is written with a `'`, like `'(apple banana)`, but it can also be written with `quote`, like `(quote (apple banana))`.

## 2.2 Quasiquote

---

```
'quasiquoted  
(quasiquote quasiquoted)
```

Creates symbols and abbreviates nested lists, but also allows escaping to expression “unquotes.”

Normally, this form is written with a backquote, `'`, like `'(apple ,(+ 1 2))`, but it can also be written with `quasiquote`, like `(quasiquote (apple ,(+ 1 2)))`.

---

```
,quasiquoted  
(unquote expr)
```

Under a single quasiquote, `,expr` escapes from the quote to include an evaluated expression whose result is inserted into the abbreviated list.

Under multiple quasiquotes, `,expr` is really `,quasiquoted`, decrementing the quasiquote count by one for `quasiquoted`.

Normally, an unquote is written with `,`, but it can also be written with `unquote`.

---

```
,@quasiquoted  
(unquote-splicing expr)
```

Under a single quasiquote, `,@expr` escapes from the quote to include an evaluated expression whose result is a list to splice into the abbreviated list.

Under multiple quasiquotes, a splicing unquote is like an unquote; that is, it decrements the quasiquote count by one.

Normally, a splicing unquote is written with `,`, but it can also be written with `unquote-splicing`.

## 2.3 Primitive Operations

### 2.3.1 Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts

---

```
* : (number number number ... -> number)
```

Purpose: to compute the product of all of the input numbers

---

`+ : (number number number ... -> number)`

Purpose: to compute the sum of the input numbers

---

`- : (number number ... -> number)`

Purpose: to subtract the second (and following) number(s) from the first; negate the number if there is only one argument

---

`/ : (number number number ... -> number)`

Purpose: to divide the first by the second (and all following) number(s); try `(/ 3 4)` and `(/ 3 2 2)` only the first number can be zero.

---

`< : (real real real ... -> boolean)`

Purpose: to compare real numbers for less-than

---

`<= : (real real real ... -> boolean)`

Purpose: to compare real numbers for less-than or equality

---

`= : (number number number ... -> boolean)`

Purpose: to compare numbers for equality

---

`> : (real real real ... -> boolean)`

Purpose: to compare real numbers for greater-than

---

`>= : (real real ... -> boolean)`

Purpose: to compare real numbers for greater-than or equality

---

`abs : (real -> real)`

Purpose: to compute the absolute value of a real number

---

`acos : (number -> number)`



Purpose: to compute the arccosine (inverse of cos) of a number

---

`add1` : (number -> number)

Purpose: to compute a number one larger than a given number

---

`angle` : (number -> real)

Purpose: to extract the angle from a complex number

---

`asin` : (number -> number)

Purpose: to compute the arcsine (inverse of sin) of a number

---

`atan` : (number -> number)

Purpose: to compute the arctan (inverse of tan) of a number

---

`ceiling` : (real -> integer)

Purpose: to determine the closest integer (exact or inexact) above a real number

---

`complex?` : (any -> boolean)

Purpose: to determine whether some value is complex

---

`conjugate` : (number -> number)

Purpose: to compute the conjugate of a complex number

---

`cos` : (number -> number)

Purpose: to compute the cosine of a number (radians)

---

`cosh` : (number -> number)

Purpose: to compute the hyperbolic cosine of a number

---

`current-seconds` : (-> integer)

Purpose: to compute the current time in seconds elapsed (since a platform-specific starting date)

---

`denominator` : (rat -> integer)

Purpose: to compute the denominator of a rational

---

`e` : real

Purpose: Euler's number

---

`even?` : (integer -> boolean)

Purpose: to determine if some integer (exact or inexact) is even or not

---

`exact->inexact` : (number -> number)

Purpose: to convert an exact number to an inexact one

---

`exact?` : (number -> boolean)

Purpose: to determine whether some number is exact

---

`exp` : (number -> number)

Purpose: to compute e raised to a number

---

`expt` : (number number -> number)

Purpose: to compute the power of the first to the second number

---

`floor` : (real -> integer)

Purpose: to determine the closest integer (exact or inexact) below a real number

---

`gcd` : (integer integer ... -> integer)

Purpose: to compute the greatest common divisor of two integers (exact or inexact)

---

`imag-part` : (number -> real)

Purpose: to extract the imaginary part from a complex number

---

`inexact->exact` : (number -> number)

Purpose: to approximate an inexact number by an exact one

---

`inexact?` : (number -> boolean)

Purpose: to determine whether some number is inexact

---

`integer->char` : (integer -> char)

Purpose: to lookup the character that corresponds to the given integer (exact only!) in the ASCII table (if any)

---

`integer-sqrt` : (number -> integer)

Purpose: to compute the integer (exact or inexact) square root of a number

---

`integer?` : (any -> boolean)

Purpose: to determine whether some value is an integer (exact or inexact)

---

`lcm` : (integer integer ... -> integer)

Purpose: to compute the least common multiple of two integers (exact or inexact)

---

`log` : (number -> number)

Purpose: to compute the base-e logarithm of a number

---

`magnitude` : (number -> real)

Purpose: to determine the magnitude of a complex number

---

`make-polar` : (real real -> number)

Purpose: to create a complex from a magnitude and angle

---

`make-rectangular` : (real real -> number)

Purpose: to create a complex from a real and an imaginary part

---

```
max : (real real ... -> real)
```

Purpose: to determine the largest number

---

```
min : (real real ... -> real)
```

Purpose: to determine the smallest number

---

```
modulo : (integer integer -> integer)
```

Purpose: to find the remainder of the division of the first number by the second; try (modulo 4 3) (modulo 4 -3)

---

```
negative? : (number -> boolean)
```

Purpose: to determine if some value is strictly smaller than zero

---

```
number->string : (number -> string)
```

Purpose: to convert a number to a string

---

```
number? : (any -> boolean)
```

Purpose: to determine whether some value is a number

---

```
numerator : (rat -> integer)
```

Purpose: to compute the numerator of a rational

---

```
odd? : (integer -> boolean)
```

Purpose: to determine if some integer (exact or inexact) is odd or not

---

```
pi : real
```

Purpose: the ratio of a circle's circumference to its diameter

---

```
positive? : (number -> boolean)
```

Purpose: to determine if some value is strictly larger than zero

---

`quotient` : (integer integer -> integer)

Purpose: to divide the first integer (exact or inexact) into the second; try (quotient 3 4) and (quotient 4 3)

---

`random` : (integer -> integer)

Purpose: to generate a random natural number less than some given integer (exact only!)

---

`rational?` : (any -> boolean)

Purpose: to determine whether some value is a rational number

---

`real-part` : (number -> real)

Purpose: to extract the real part from a complex number

---

`real?` : (any -> boolean)

Purpose: to determine whether some value is a real number

---

`remainder` : (integer integer -> integer)

Purpose: to determine the remainder of dividing the first by the second integer (exact or inexact)

---

`round` : (real -> integer)

Purpose: to round a real number to an integer (rounds to even to break ties)

---

`sgn` : (real -> (union 1 1.0 0 0.0 -1 -1.0))

Purpose: to compute the sign of a real number

---

`sin` : (number -> number)

Purpose: to compute the sine of a number (radians)

---

```
sinh : (number -> number)
```

Purpose: to compute the hyperbolic sine of a number

---

```
sqr : (number -> number)
```

Purpose: to compute the square of a number

---

```
sqrt : (number -> number)
```

Purpose: to compute the square root of a number

---

```
sub1 : (number -> number)
```

Purpose: to compute a number one smaller than a given number

---

```
tan : (number -> number)
```

Purpose: to compute the tangent of a number (radians)

---

```
zero? : (number -> boolean)
```

Purpose: to determine if some value is zero or not

### 2.3.2 Booleans

---

```
boolean=? : (boolean boolean -> boolean)
```

Purpose: to determine whether two booleans are equal

---

```
boolean? : (any -> boolean)
```

Purpose: to determine whether some value is a boolean

---

```
false? : (any -> boolean)
```

Purpose: to determine whether a value is false

---

```
not : (boolean -> boolean)
```

Purpose: to compute the negation of a boolean value

### 2.3.3 Symbols

---

```
symbol->string : (symbol -> string)
```

Purpose: to convert a symbol to a string

---

```
symbol=? : (symbol symbol -> boolean)
```

Purpose: to determine whether two symbols are equal

---

```
symbol? : (any -> boolean)
```

Purpose: to determine whether some value is a symbol

### 2.3.4 Lists

---

```
append : ((listof any)
           (listof any)
           (listof any)
           ...
           ->
           (listof any))
```

Purpose: to create a single list from several, by juxtaposition of the items

---

```
assq : (X
        (listof (cons X Y))
        ->
        (union false (cons X Y)))
```

Purpose: to determine whether some item is the first item of a pair in a list of pairs

---

```
caaar : ((cons
         (cons (cons W (listof Z)) (listof Y))
         (listof X))
        ->
        W)
```

Purpose: to select the first item of the first list in the first list of a list

---

```
caadr : ((cons
         (cons (cons W (listof Z)) (listof Y))
         (listof X))
        ->
        (listof Z))
```

Purpose: to select the rest of the first list in the first list of a list

---

```
caar : ((cons (cons Z (listof Y)) (listof X)) -> Z)
```

Purpose: to select the first item of the first list in a list

---

```
cadar : ((cons (cons W (cons Z (listof Y))) (listof X))
        ->
        Z)
```

Purpose: to select the second item of the first list of a list

---

```
caddr : ((listof Y) -> Y)
```

Purpose: to select the fourth item of a non-empty list

---

```
caddr : ((cons W (cons Z (cons Y (listof X)))) -> Y)
```

Purpose: to select the third item of a non-empty list

---

```
cadr : ((cons Z (cons Y (listof X))) -> Y)
```

Purpose: to select the second item of a non-empty list

---

```
car : ((cons Y (listof X)) -> Y)
```

Purpose: to select the first item of a non-empty list



---

```
cdaar : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
        ->
        (listof Z))
```

Purpose: to select the rest of the first list in the first list of a list

---

```
cdadr : ((cons W (cons (cons Z (listof Y)) (listof X)))
        ->
        (listof Y))
```

Purpose: to select the rest of the first list in the rest of a list

---

```
cdar : ((cons (cons Z (listof Y)) (listof X))
        ->
        (listof Y))
```

Purpose: to select the rest of a non-empty list in a list

---

```
cddar : ((cons (cons W (cons Z (listof Y))) (listof X))
        ->
        (listof Y))
```

Purpose: to select the rest of the rest of the first list of a list

---

```
cdddr : ((cons W (cons Z (cons Y (listof X))))
        ->
        (listof X))
```

Purpose: to select the rest of the rest of the rest of a list

---

```
cddr : ((cons Z (cons Y (listof X))) -> (listof X))
```

Purpose: to select the rest of the rest of a list

---

```
cdr : ((cons Y (listof X)) -> (listof X))
```

Purpose: to select the rest of a non-empty list

---

```
cons : (X (listof X) -> (listof X))
```

Purpose: to construct a list

---

```
cons? : (any -> boolean)
```

Purpose: to determine whether some value is a constructed list

---

```
eighth : ((listof Y) -> Y)
```

Purpose: to select the eighth item of a non-empty list

---

```
empty? : (any -> boolean)
```

Purpose: to determine whether some value is the empty list

---

```
fifth : ((listof Y) -> Y)
```

Purpose: to select the fifth item of a non-empty list

---

```
first : ((cons Y (listof X)) -> Y)
```

Purpose: to select the first item of a non-empty list

---

```
fourth : ((listof Y) -> Y)
```

Purpose: to select the fourth item of a non-empty list

---

```
length : ((listof any) -> number)
```

Purpose: to compute the number of items on a list

---

```
list : (any ... -> (listof any))
```

Purpose: to construct a list of its arguments

---

```
list* : (any ... (listof any) -> (listof any))
```

Purpose: to construct a list by adding multiple items to a list

---

```
list-ref : ((listof X) natural-number -> X)
```

Purpose: to extract the indexed item from the list

---

```
make-list : (natural-number any -> (listof any))
```

Purpose: (make-list k x) constructs a list of k copies of x

---

```
member : (any (listof any) -> boolean)
```

Purpose: to determine whether some value is on the list (comparing values with equal?)

---

```
member? : (any (listof any) -> boolean)
```

Purpose: to determine whether some value is on the list (comparing values with equal?)

---

```
memq : (any (listof any) -> (union false list))
```

Purpose: to determine whether some value is on some list if so, it produces the suffix of the list that starts with x if not, it produces false. (It compares values with the eq? predicate.)

---

```
memv : (any (listof any) -> (union false list))
```

Purpose: to determine whether some value is on the list if so, it produces the suffix of the list that starts with x if not, it produces false. (it compares values with the eqv? predicate.)

---

```
null : empty
```

Purpose: the empty list

---

```
null? : (any -> boolean)
```

Purpose: to determine whether some value is the empty list

---

```
pair? : (any -> boolean)
```

Purpose: to determine whether some value is a constructed list

---

```
remove : (any (listof any) -> (listof any))
```

Purpose: to construct a list like the given one with the first occurrence of the given item removed (comparing values with equal?)

---

`rest` : ((cons Y (listof X)) -> (listof X))

Purpose: to select the rest of a non-empty list

---

`reverse` : ((listof any) -> list)

Purpose: to create a reversed version of a list

---

`second` : ((cons Z (cons Y (listof X))) -> Y)

Purpose: to select the second item of a non-empty list

---

`seventh` : ((listof Y) -> Y)

Purpose: to select the seventh item of a non-empty list

---

`sixth` : ((listof Y) -> Y)

Purpose: to select the sixth item of a non-empty list

---

`third` : ((cons W (cons Z (cons Y (listof X)))) -> Y)

Purpose: to select the third item of a non-empty list

### 2.3.5 Posns

---

`make-posn` : (number number -> posn)

Purpose: to construct a posn

---

`posn` : signature

Purpose: signature for posns

---

`posn-x` : (posn -> number)

Purpose: to extract the x component of a posn

---

`posn-y` : (posn -> number)

Purpose: to extract the y component of a posn

---

`posn?` : (anything -> boolean)

Purpose: to determine if its input is a posn

### 2.3.6 Characters

---

`char->integer` : (char -> integer)

Purpose: to lookup the number that corresponds to the given character in the ASCII table (if any)

---

`char-alphabetic?` : (char -> boolean)

Purpose: to determine whether a character represents an alphabetic character

---

`char-ci<=?` : (char char char ... -> boolean)

Purpose: to determine whether a character precedes another (or is equal to it) in a case-insensitive manner

---

`char-ci<?` : (char char char ... -> boolean)

Purpose: to determine whether a character precedes another in a case-insensitive manner

---

`char-ci=?` : (char char char ... -> boolean)

Purpose: to determine whether two characters are equal in a case-insensitive manner

---

`char-ci>=?` : (char char char ... -> boolean)

Purpose: to determine whether a character succeeds another (or is equal to it) in a case-insensitive manner

---

`char-ci>?` : (char char char ... -> boolean)

Purpose: to determine whether a character succeeds another in a case-insensitive manner

---

`char-downcase` : (char -> char)

Purpose: to determine the equivalent lower-case character

---

`char-lower-case?` : (char -> boolean)

Purpose: to determine whether a character is a lower-case character

---

`char-numeric?` : (char -> boolean)

Purpose: to determine whether a character represents a digit

---

`char-upcase` : (char -> char)

Purpose: to determine the equivalent upper-case character

---

`char-upper-case?` : (char -> boolean)

Purpose: to determine whether a character is an upper-case character

---

`char-whitespace?` : (char -> boolean)

Purpose: to determine whether a character represents space

---

`char<=?` : (char char char ... -> boolean)

Purpose: to determine whether a character precedes another (or is equal to it)

---

`char<?` : (char char char ... -> boolean)

Purpose: to determine whether a character precedes another

---

`char=?` : (char char char ... -> boolean)

Purpose: to determine whether two characters are equal

---

`char>=?` : (char char char ... -> boolean)

Purpose: to determine whether a character succeeds another (or is equal to it)

---

`char>?` : (char char char ... -> boolean)

Purpose: to determine whether a character succeeds another

---

`char?` : (any -> boolean)

Purpose: to determine whether a value is a character

### 2.3.7 Strings

---

`explode` : (string -> (listof string))

Purpose: to translate a string into a list of 1-letter strings

---

`format` : (string any ... -> string)

Purpose: to format a string, possibly embedding values

---

`implode` : ((listof string) -> string)

Purpose: to concatenate the list of 1-letter strings into one string

---

`int->string` : (integer -> string)

Purpose: to convert an integer in [0,55295] or [57344 1114111] to a 1-letter string

---

`list->string` : ((listof char) -> string)

Purpose: to convert a s list of characters into a string

---

`make-string` : (nat char -> string)

Purpose: to produce a string of given length from a single given character

---

`replicate` : (nat string -> string)

Purpose: to replicate the given string

---

`string` : (char ... -> string)

Purpose: (string c1 c2 ...) builds a string

---

`string->int` : (string -> integer)

Purpose: to convert a 1-letter string to an integer in [0,55295] or [57344, 1114111]

---

`string->list` : (string -> (listof char))

Purpose: to convert a string into a list of characters

---

`string->number` : (string -> (union number false))

Purpose: to convert a string into a number, produce false if impossible

---

`string->symbol` : (string -> symbol)

Purpose: to convert a string into a symbol

---

`string-alphabetic?` : (string -> boolean)

Purpose: to determine whether all 'letters' in the string are alphabetic

---

`string-append` : (string ... -> string)

Purpose: to juxtapose the characters of several strings

---

`string-ci<=?` : (string string string ... -> boolean)

Purpose: to determine whether one string alphabetically precedes another (or is equal to it) in a case-insensitive manner

---

`string-ci<?` : (string string string ... -> boolean)

Purpose: to determine whether one string alphabetically precedes another in a case-insensitive manner

---

`string-ci=?` : (string string string ... -> boolean)



Purpose: to compare two strings character-wise in a case-insensitive manner

---

```
string-ci>=? : (string string string ... -> boolean)
```

Purpose: to determine whether one string alphabetically succeeds another (or is equal to it) in a case-insensitive manner

---

```
string-ci>? : (string string string ... -> boolean)
```

Purpose: to determine whether one string alphabetically succeeds another in a case-insensitive manner

---

```
string-copy : (string -> string)
```

Purpose: to copy a string

---

```
string-ith : (string nat -> string)
```

Purpose: to extract the ith 1-letter substring from the given one

---

```
string-length : (string -> nat)
```

Purpose: to determine the length of a string

---

```
string-lower-case? : (string -> boolean)
```

Purpose: to determine whether all 'letters' in the string are lower case

---

```
string-numeric? : (string -> boolean)
```

Purpose: to determine whether all 'letters' in the string are numeric

---

```
string-ref : (string nat -> char)
```

Purpose: to extract the i-th character from a string

---

```
string-upper-case? : (string -> boolean)
```

Purpose: to determine whether all 'letters' in the string are upper case

---

`string-whitespace? : (string -> boolean)`

Purpose: to determine whether all 'letters' in the string are white space

---

`string<=? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically precedes another (or is equal to it)

---

`string<? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically precedes another

---

`string=? : (string string string ... -> boolean)`

Purpose: to compare two strings character-wise

---

`string>=? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically succeeds another (or is equal to it)

---

`string>? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically succeeds another

---

`string? : (any -> boolean)`

Purpose: to determine whether a value is a string

---

`substring : (string nat nat -> string)`

Purpose: to extract the substring starting at a 0-based index up to the second 0-based index (exclusive)

### 2.3.8 Images

---

`image=? : (image image -> boolean)`

Purpose: to determine whether two images are equal

---

`image?` : (any -> boolean)

Purpose: to determine whether a value is an image

### 2.3.9 Misc

---

`=~` : (real real non-negative-real -> boolean)

Purpose: to check whether two real numbers are within some amount (the third argument) of either other

---

`eof` : eof

Purpose: the end-of-file value

---

`eof-object?` : (any -> boolean)

Purpose: to determine whether some value is the end-of-file value

---

`eq?` : (any any -> boolean)

Purpose: to determine whether two values are equivalent from the computer's perspective (intensional)

---

`equal?` : (any any -> boolean)

Purpose: to determine whether two values are structurally equal where basic values are compared with the `eqv?` predicate

---

`equal~?` : (any any non-negative-real -> boolean)

Purpose: to compare like `equal?` on the first two arguments, except using `=~` in the case of real numbers

---

`eqv?` : (any any -> boolean)

Purpose: to determine whether two values are equivalent from the perspective of all functions that can be applied to it (extensional)

---

`error` : (any ... -> void)

Purpose: to signal an error, combining the given values into an error message.

If any of the values' printed representations is too long, it is truncated and “...” is put into the string. If the first value is a symbol, it is treated specially; it is suffixed with a colon and a space (the intention is that the symbol is the name of the function signalling the error).

---

`exit` : (-> void)

Purpose: to exit the running program

---

`identity` : (any -> any)

Purpose: to return the argument unchanged

---

`struct?` : (any -> boolean)

Purpose: to determine whether some value is a structure

## 2.4 Unchanged Forms

---

```
(define (id id id ...) expr)
(define id expr)
(define id (lambda (id id ...) expr))
lambda
```

The same as Beginning's `define`.

---

```
(define-struct structid (fieldid ...))
```

The same as Beginning's `define-struct`.

---

```
(cond [expr expr] ... [expr expr])
else
```

The same as Beginning's `cond`.

---

```
(if expr expr expr)
```

The same as Beginning's `if`.

---

```
(and expr expr expr ...)  
(or expr expr expr ...)
```

The same as Beginning's `and` and `or`.

---

```
(check-expect expr expr)  
(check-within expr expr expr)  
(check-error expr expr)  
(check-error expr)  
(check-member-of expr expr expr ...)  
(check-range expr expr expr)
```

The same as Beginning's `check-expect`, etc.

---

```
empty : empty?  
true : boolean?  
false : boolean?
```

Constants for the empty list, true, and false.

---

```
(require module-path)
```

The same as Beginning's `require`.

### 3 Intermediate Student

```
program = def-or-expr ...

def-or-expr = definition
             | expr
             | test-case
             | library-require

definition = (define (id id id ...) expr)
             | (define id expr)
             | (define id (lambda (id id ...) expr))
             | (define-struct id (id ...))

expr = (local [definition ...] expr)
      | (letrec ([id expr-for-let] ...) expr)
      | (let ([id expr-for-let] ...) expr)
      | (let* ([id expr-for-let] ...) expr)
      | (id expr expr ...) ; function call
      | (prim-op expr ...) ; primitive operation call
      | (cond [expr expr] ... [expr expr])
      | (cond [expr expr] ... [else expr])
      | (if expr expr expr)
      | (and expr expr expr ...)
      | (or expr expr expr ...)
      | (time expr)
      | empty
      | id ; identifier
      | prim-op ; primitive operation
      | 'quoted ; quoted value
      | 'quasiquoted ; quasiquote
      | number
      | true
      | false
      | string
      | character

expr-for-let = (lambda (id id ...) expr)
              | expr

quoted = id
        | number
        | string
        | character
        | (quoted ...)
```

```

| 'quoted
| 'quoted
| ,quoted
| ,@quoted

quasiquoted = id
| number
| string
| character
| (quasiquoted ...)
| 'quasiquoted
| 'quasiquoted
| ,expr
| ,@expr

test-case = (check-expect expr expr)
| (check-within expr expr expr)
| (check-member-of expr expr ...)
| (check-range expr expr expr)
| (check-error expr expr)
| (check-error expr)

library-require = (require string)
| (require (lib string string ...))
| (require (planet string package))

package = (string string number number)

```

An *id* is a sequence of characters not including a space or one of the following:

```
" , ' ' ( ) [ ] { } | ; #
```

A *number* is a number such as 123, 3/2, or 5.5.

A *string* is enclosed by a pair of `"`. Unlike symbols, strings may be split into characters and manipulated by a variety of primitive functions. For example, `"abcdef"`, `"This is a string"`, and `"This is a string with \" inside"` are all strings.

A *character* begins with `#\` and has the name of the character. For example, `#\a`, `#\b`, and `#\space` are characters.

A *prim-op* is one of:

**Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts**

```

< : (real real real ... -> boolean)
<= : (real real real ... -> boolean)
= : (number number number ... -> boolean)
> : (real real real ... -> boolean)

```

```

>= : (real real ... -> boolean)
abs : (real -> real)
acos : (number -> number)
add1 : (number -> number)
angle : (number -> real)
asin : (number -> number)
atan : (number -> number)
ceiling : (real -> integer)
complex? : (any -> boolean)
conjugate : (number -> number)
cos : (number -> number)
cosh : (number -> number)
current-seconds : (-> integer)
denominator : (rat -> integer)
e : real
even? : (integer -> boolean)
exact->inexact : (number -> number)
exact? : (number -> boolean)
exp : (number -> number)
expt : (number number -> number)
floor : (real -> integer)
gcd : (integer integer ... -> integer)
imag-part : (number -> real)
inexact->exact : (number -> number)
inexact? : (number -> boolean)
integer->char : (integer -> char)
integer-sqrt : (number -> integer)
integer? : (any -> boolean)
lcm : (integer integer ... -> integer)
log : (number -> number)
magnitude : (number -> real)
make-polar : (real real -> number)
make-rectangular : (real real -> number)
max : (real real ... -> real)
min : (real real ... -> real)
modulo : (integer integer -> integer)
negative? : (number -> boolean)
number->string : (number -> string)
number? : (any -> boolean)
numerator : (rat -> integer)
odd? : (integer -> boolean)
pi : real
positive? : (number -> boolean)
quotient : (integer integer -> integer)
random : (integer -> integer)
rational? : (any -> boolean)

```



```

real-part : (number -> real)
real? : (any -> boolean)
remainder : (integer integer -> integer)
round : (real -> integer)
sgn : (real -> (union 1 1.0 0 0.0 -1 -1.0))
sin : (number -> number)
sinh : (number -> number)
sqr : (number -> number)
sqrt : (number -> number)
sub1 : (number -> number)
tan : (number -> number)
zero? : (number -> boolean)

```

### Booleans

```

boolean=? : (boolean boolean -> boolean)
boolean? : (any -> boolean)
false? : (any -> boolean)
not : (boolean -> boolean)

```

### Symbols

```

symbol->string : (symbol -> string)
symbol=? : (symbol symbol -> boolean)
symbol? : (any -> boolean)

```

### Lists

```

append : ((listof any) ... -> (listof any))
assq : (X
      (listof (cons X Y))
      ->
      (union false (cons X Y)))
caaar : ((cons
        (cons (cons W (listof Z)) (listof Y))
        (listof X))
      ->
      W)
caadr : ((cons
        (cons (cons W (listof Z)) (listof Y))
        (listof X))
      ->
      (listof Z))
caar : ((cons (cons Z (listof Y)) (listof X)) -> Z)
cadar : ((cons (cons W (cons Z (listof Y))) (listof X))
      ->
      Z)
caddr : ((listof Y) -> Y)
caddr : ((cons W (cons Z (cons Y (listof X)))) -> Y)
cadr : ((cons Z (cons Y (listof X))) -> Y)
car : ((cons Y (listof X)) -> Y)

```

```

cdaar : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
         ->
         (listof Z))
cdadr : ((cons W (cons (cons Z (listof Y)) (listof X)))
         ->
         (listof Y))
cdar : ((cons (cons Z (listof Y)) (listof X))
        ->
        (listof Y))
cddar : ((cons (cons W (cons Z (listof Y))) (listof X))
         ->
         (listof Y))
cddddr : ((cons W (cons Z (cons Y (listof X))))
          ->
          (listof X))
cddr : ((cons Z (cons Y (listof X))) -> (listof X))
cdr : ((cons Y (listof X)) -> (listof X))
cons : (X (listof X) -> (listof X))
cons? : (any -> boolean)
eighth : ((listof Y) -> Y)
empty? : (any -> boolean)
fifth : ((listof Y) -> Y)
first : ((cons Y (listof X)) -> Y)
fourth : ((listof Y) -> Y)
length : ((listof any) -> number)
list : (any ... -> (listof any))
list* : (any ... (listof any) -> (listof any))
list-ref : ((listof X) natural-number -> X)
make-list : (natural-number any -> (listof any))
member : (any (listof any) -> boolean)
member? : (any (listof any) -> boolean)
memq : (any (listof any) -> (union false list))
memv : (any (listof any) -> (union false list))
null : empty
null? : (any -> boolean)
pair? : (any -> boolean)
remove : (any (listof any) -> (listof any))
rest : ((cons Y (listof X)) -> (listof X))
reverse : ((listof any) -> list)
second : ((cons Z (cons Y (listof X))) -> Y)
seventh : ((listof Y) -> Y)
sixth : ((listof Y) -> Y)
third : ((cons W (cons Z (cons Y (listof X)))) -> Y)

```

## Posns

```
make-posn : (number number -> posn)
posn : signature
posn-x : (posn -> number)
posn-y : (posn -> number)
posn? : (anything -> boolean)
```

### Characters

```
char->integer : (char -> integer)
char-alphabetic? : (char -> boolean)
char-ci<=? : (char char char ... -> boolean)
char-ci<? : (char char char ... -> boolean)
char-ci=? : (char char char ... -> boolean)
char-ci>=? : (char char char ... -> boolean)
char-ci>? : (char char char ... -> boolean)
char-downcase : (char -> char)
char-lower-case? : (char -> boolean)
char-numeric? : (char -> boolean)
char-upcase : (char -> char)
char-upper-case? : (char -> boolean)
char-whitespace? : (char -> boolean)
char<=? : (char char char ... -> boolean)
char<? : (char char char ... -> boolean)
char=? : (char char char ... -> boolean)
char>=? : (char char char ... -> boolean)
char>? : (char char char ... -> boolean)
char? : (any -> boolean)
```

### Strings

```
explode : (string -> (listof string))
format : (string any ... -> string)
implode : ((listof string) -> string)
int->string : (integer -> string)
list->string : ((listof char) -> string)
make-string : (nat char -> string)
replicate : (nat string -> string)
string : (char ... -> string)
string->int : (string -> integer)
string->list : (string -> (listof char))
string->number : (string -> (union number false))
string->symbol : (string -> symbol)
string-alphabetic? : (string -> boolean)
string-append : (string ... -> string)
string-ci<=? : (string string string ... -> boolean)
string-ci<? : (string string string ... -> boolean)
string-ci=? : (string string string ... -> boolean)
string-ci>=? : (string string string ... -> boolean)
string-ci>? : (string string string ... -> boolean)
string-copy : (string -> string)
```

```

string-ith : (string nat -> string)
string-length : (string -> nat)
string-lower-case? : (string -> boolean)
string-numeric? : (string -> boolean)
string-ref : (string nat -> char)
string-upper-case? : (string -> boolean)
string-whitespace? : (string -> boolean)
string<=? : (string string string ... -> boolean)
string<? : (string string string ... -> boolean)
string=? : (string string string ... -> boolean)
string>=? : (string string string ... -> boolean)
string>? : (string string string ... -> boolean)
string? : (any -> boolean)
substring : (string nat nat -> string)

```

### Images

```

image=? : (image image -> boolean)
image? : (any -> boolean)

```

### Misc

```

≈~ : (real real non-negative-real -> boolean)
eof : eof
eof-object? : (any -> boolean)
eq? : (any any -> boolean)
equal? : (any any -> boolean)
equal~? : (any any non-negative-real -> boolean)
eqv? : (any any -> boolean)
error : (any ... -> void)
exit : (-> void)
identity : (any -> any)
struct? : (any -> boolean)

```

### Numbers (relaxed conditions)

```

* : (number ... -> number)
+ : (number ... -> number)
- : (number ... -> number)
/ : (number ... -> number)

```

### Higher-Order Functions

```

andmap : ((X -> boolean) (listof X) -> boolean)
apply : ((X-1 ... X-N -> Y)
         X-1
         ...
         X-i
         (list X-i+1 ... X-N)
         ->
         Y)
argmax : ((X -> real) (listof X) -> X)
argmin : ((X -> real) (listof X) -> X)
build-list : (nat (nat -> X) -> (listof X))

```

```

build-string : (nat (nat -> char) -> string)
compose : ((Y-1 -> Z)
  ...
  (Y-N -> Y-N-1)
  (X-1 ... X-N -> Y-N)
  ->
  (X-1 ... X-N -> Z))
filter : ((X -> boolean) (listof X) -> (listof X))
foldl : ((X Y -> Y) Y (listof X) -> Y)
foldr : ((X Y -> Y) Y (listof X) -> Y)
for-each : ((any ... -> any) (listof any) ... -> void)
map : ((X ... -> Z) (listof X) ... -> (listof Z))
memf : ((X -> boolean)
  (listof X)
  ->
  (union false (listof X)))
ormap : ((X -> boolean) (listof X) -> boolean)
procedure? : (any -> boolean)
quicksort : ((listof X) (X X -> boolean) -> (listof X))
sort : ((listof X) (X X -> boolean) -> (listof X))

```

### 3.1 define

---

```

(define (id id id ...) expr)
(define id expr)
(define id (lambda (id id ...) expr))

```

Besides working in `local`, definition forms are the same as Beginning's `define`.

---

`lambda`

As in Beginning, `lambda` keyword can only be used with `define` in the alternative function-definition syntax.

### 3.2 define-struct

---

```

(define-struct structid (fieldid ...))

```

Besides working in `local`, this form is the same as Beginning's `define-struct`.

### 3.3 local

---

```
(local [definition ...] expr)
```

Groups related definitions for use in *expr*. Each *definition* is evaluated in order, and finally the body *expr* is evaluated. Only the expressions within the `local` form (including the right-hand-sides of the *definitions* and the *expr*) may refer to the names defined by the *definitions*. If a name defined in the `local` form is the same as a top-level binding, the inner one “shadows” the outer one. That is, inside the `local` form, any references to that name refer to the inner one.

Since `local` is an expression and may occur anywhere an expression may occur, it introduces the notion of lexical scope. Expressions within the `local` may “escape” the scope of the `local`, but these expressions may still refer to the bindings established by the `local`.

### 3.4 letrec, let, and let\*

---

```
(letrec ([id expr-for-let] ...) expr)
```

Similar to `local`, but essentially omitting the `define` for each definition.

A *expr-for-let* can be either an expression for a constant definition or a lambda form for a function definition.

---

```
(let ([id expr-for-let] ...) expr)
```

Like `letrec`, but the defined *ids* can be used only in the last *expr*, not the *expr-for-lets* next to the *ids*.

---

```
(let* ([id expr-for-let] ...) expr)
```

Like `let`, but each *id* can be used in any subsequent *expr-for-let*, in addition to *expr*.

### 3.5 Function Calls

---

```
(id expr expr ...)
```

A function call in Intermediate is the same as a Beginning function call, except that it can also call locally defined functions or functions passed as arguments. That is, *id* can be a function defined in `local` or an argument name while in a function.

---

```
(#%app id expr expr ...)
```

A function call can be written with `#%app`, though it's practically never written that way.

### 3.6 time

---

```
(time expr)
```

This form is used to measure the time taken to evaluate `expr`. After evaluating `expr`, Scheme prints out the time taken by the evaluation (including real time, time taken by the cpu, and the time spent collecting free memory) and returns the result of the expression.

(The reported time is measured as the number of milliseconds of CPU time required to obtain this result, the number of “real” milliseconds required for the result, and the number of milliseconds of CPU time (included in the first result) spent on garbage collection. The reliability of the timing numbers depends on the platform.)

### 3.7 Identifiers

---

```
id
```

An `id` refers to a defined constant (possibly local), defined function (possibly local), or argument within a function body. If no definition or argument matches the `id` name, an error is reported.

### 3.8 Primitive Operations

---

```
prim-op
```

The name of a primitive operation can be used as an expression. If it is passed to a function, then it can be used in a function call within the function's body.

#### 3.8.1 Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts

---

```
< : (real real real ... -> boolean)
```

Purpose: to compare real numbers for less-than

---

```
<= : (real real real ... -> boolean)
```

Purpose: to compare real numbers for less-than or equality

---

```
= : (number number number ... -> boolean)
```

Purpose: to compare numbers for equality

---

```
> : (real real real ... -> boolean)
```

Purpose: to compare real numbers for greater-than

---

```
>= : (real real ... -> boolean)
```

Purpose: to compare real numbers for greater-than or equality

---

```
abs : (real -> real)
```

Purpose: to compute the absolute value of a real number

---

```
acos : (number -> number)
```

Purpose: to compute the arccosine (inverse of cos) of a number

---

```
add1 : (number -> number)
```

Purpose: to compute a number one larger than a given number

---

```
angle : (number -> real)
```

Purpose: to extract the angle from a complex number

---

```
asin : (number -> number)
```

Purpose: to compute the arcsine (inverse of sin) of a number

---

```
atan : (number -> number)
```



Purpose: to compute the arctan (inverse of tan) of a number

---

`ceiling` : (real -> integer)

Purpose: to determine the closest integer (exact or inexact) above a real number

---

`complex?` : (any -> boolean)

Purpose: to determine whether some value is complex

---

`conjugate` : (number -> number)

Purpose: to compute the conjugate of a complex number

---

`cos` : (number -> number)

Purpose: to compute the cosine of a number (radians)

---

`cosh` : (number -> number)

Purpose: to compute the hyperbolic cosine of a number

---

`current-seconds` : (-> integer)

Purpose: to compute the current time in seconds elapsed (since a platform-specific starting date)

---

`denominator` : (rat -> integer)

Purpose: to compute the denominator of a rational

---

`e` : real

Purpose: Euler's number

---

`even?` : (integer -> boolean)

Purpose: to determine if some integer (exact or inexact) is even or not

---

`exact->inexact` : (number -> number)

Purpose: to convert an exact number to an inexact one

---

```
exact? : (number -> boolean)
```

Purpose: to determine whether some number is exact

---

```
exp : (number -> number)
```

Purpose: to compute e raised to a number

---

```
expt : (number number -> number)
```

Purpose: to compute the power of the first to the second number

---

```
floor : (real -> integer)
```

Purpose: to determine the closest integer (exact or inexact) below a real number

---

```
gcd : (integer integer ... -> integer)
```

Purpose: to compute the greatest common divisor of two integers (exact or inexact)

---

```
imag-part : (number -> real)
```

Purpose: to extract the imaginary part from a complex number

---

```
inexact->exact : (number -> number)
```

Purpose: to approximate an inexact number by an exact one

---

```
inexact? : (number -> boolean)
```

Purpose: to determine whether some number is inexact

---

```
integer->char : (integer -> char)
```

Purpose: to lookup the character that corresponds to the given integer (exact only!) in the ASCII table (if any)

---

```
integer-sqrt : (number -> integer)
```

Purpose: to compute the integer (exact or inexact) square root of a number

---

`integer?` : (any -> boolean)

Purpose: to determine whether some value is an integer (exact or inexact)

---

`lcm` : (integer integer ... -> integer)

Purpose: to compute the least common multiple of two integers (exact or inexact)

---

`log` : (number -> number)

Purpose: to compute the base-e logarithm of a number

---

`magnitude` : (number -> real)

Purpose: to determine the magnitude of a complex number

---

`make-polar` : (real real -> number)

Purpose: to create a complex from a magnitude and angle

---

`make-rectangular` : (real real -> number)

Purpose: to create a complex from a real and an imaginary part

---

`max` : (real real ... -> real)

Purpose: to determine the largest number

---

`min` : (real real ... -> real)

Purpose: to determine the smallest number

---

`modulo` : (integer integer -> integer)

Purpose: to find the remainder of the division of the first number by the second; try (modulo 4 3) (modulo 4 -3)

---

`negative?` : (number -> boolean)

Purpose: to determine if some value is strictly smaller than zero

---

`number->string` : (number -> string)

Purpose: to convert a number to a string

---

`number?` : (any -> boolean)

Purpose: to determine whether some value is a number

---

`numerator` : (rat -> integer)

Purpose: to compute the numerator of a rational

---

`odd?` : (integer -> boolean)

Purpose: to determine if some integer (exact or inexact) is odd or not

---

`pi` : real

Purpose: the ratio of a circle's circumference to its diameter

---

`positive?` : (number -> boolean)

Purpose: to determine if some value is strictly larger than zero

---

`quotient` : (integer integer -> integer)

Purpose: to divide the first integer (exact or inexact) into the second; try (quotient 3 4) and (quotient 4 3)

---

`random` : (integer -> integer)

Purpose: to generate a random natural number less than some given integer (exact only!)

---

`rational?` : (any -> boolean)

Purpose: to determine whether some value is a rational number

---

`real-part` : (number -> real)

Purpose: to extract the real part from a complex number

---

`real?` : (any -> boolean)

Purpose: to determine whether some value is a real number

---

`remainder` : (integer integer -> integer)

Purpose: to determine the remainder of dividing the first by the second integer (exact or inexact)

---

`round` : (real -> integer)

Purpose: to round a real number to an integer (rounds to even to break ties)

---

`sgn` : (real -> (union 1 1.0 0 0.0 -1 -1.0))

Purpose: to compute the sign of a real number

---

`sin` : (number -> number)

Purpose: to compute the sine of a number (radians)

---

`sinh` : (number -> number)

Purpose: to compute the hyperbolic sine of a number

---

`sqr` : (number -> number)

Purpose: to compute the square of a number

---

`sqrt` : (number -> number)

Purpose: to compute the square root of a number

---

`sub1` : (number -> number)

Purpose: to compute a number one smaller than a given number

---

`tan` : (number -> number)

Purpose: to compute the tangent of a number (radians)

---

```
zero? : (number -> boolean)
```

Purpose: to determine if some value is zero or not

### 3.8.2 Booleans

---

```
boolean=? : (boolean boolean -> boolean)
```

Purpose: to determine whether two booleans are equal

---

```
boolean? : (any -> boolean)
```

Purpose: to determine whether some value is a boolean

---

```
false? : (any -> boolean)
```

Purpose: to determine whether a value is false

---

```
not : (boolean -> boolean)
```

Purpose: to compute the negation of a boolean value

### 3.8.3 Symbols

---

```
symbol->string : (symbol -> string)
```

Purpose: to convert a symbol to a string

---

```
symbol=? : (symbol symbol -> boolean)
```

Purpose: to determine whether two symbols are equal

---

```
symbol? : (any -> boolean)
```

Purpose: to determine whether some value is a symbol

### 3.8.4 Lists

---

```
append : ((listof any) ... -> (listof any))
```

Purpose: to create a single list from several, by juxtaposition of the items

---

```
assq : (X
      (listof (cons X Y))
      ->
      (union false (cons X Y)))
```

Purpose: to determine whether some item is the first item of a pair in a list of pairs

---

```
caaar : ((cons
        (cons (cons W (listof Z)) (listof Y))
        (listof X))
        ->
        W)
```

Purpose: to select the first item of the first list in the first list of a list

---

```
caadr : ((cons
        (cons (cons W (listof Z)) (listof Y))
        (listof X))
        ->
        (listof Z))
```

Purpose: to select the rest of the first list in the first list of a list

---

```
caar : ((cons (cons Z (listof Y)) (listof X)) -> Z)
```

Purpose: to select the first item of the first list in a list

---

```
cadar : ((cons (cons W (cons Z (listof Y))) (listof X))
        ->
        Z)
```

Purpose: to select the second item of the first list of a list

---

```
caddr : ((listof Y) -> Y)
```

Purpose: to select the fourth item of a non-empty list

---

```
caddr : ((cons W (cons Z (cons Y (listof X)))) -> Y)
```

Purpose: to select the third item of a non-empty list

---

```
cadr : ((cons Z (cons Y (listof X))) -> Y)
```

Purpose: to select the second item of a non-empty list

---

```
car : ((cons Y (listof X)) -> Y)
```

Purpose: to select the first item of a non-empty list

---

```
cdaar : ((cons  
          (cons (cons W (listof Z)) (listof Y))  
          (listof X))  
         ->  
         (listof Z))
```

Purpose: to select the rest of the first list in the first list of a list

---

```
cdadr : ((cons W (cons (cons Z (listof Y)) (listof X)))  
        ->  
        (listof Y))
```

Purpose: to select the rest of the first list in the rest of a list

---

```
cdar : ((cons (cons Z (listof Y)) (listof X))  
       ->  
       (listof Y))
```

Purpose: to select the rest of a non-empty list in a list

---

```
cddar : ((cons (cons W (cons Z (listof Y))) (listof X))  
        ->  
        (listof Y))
```

Purpose: to select the rest of the rest of the first list of a list



---

```
cdddr : ((cons W (cons Z (cons Y (listof X))))  
        ->  
        (listof X))
```

Purpose: to select the rest of the rest of the rest of a list

---

```
cddr : ((cons Z (cons Y (listof X))) -> (listof X))
```

Purpose: to select the rest of the rest of a list

---

```
cdr : ((cons Y (listof X)) -> (listof X))
```

Purpose: to select the rest of a non-empty list

---

```
cons : (X (listof X) -> (listof X))
```

Purpose: to construct a list

---

```
cons? : (any -> boolean)
```

Purpose: to determine whether some value is a constructed list

---

```
eighth : ((listof Y) -> Y)
```

Purpose: to select the eighth item of a non-empty list

---

```
empty? : (any -> boolean)
```

Purpose: to determine whether some value is the empty list

---

```
fifth : ((listof Y) -> Y)
```

Purpose: to select the fifth item of a non-empty list

---

```
first : ((cons Y (listof X)) -> Y)
```

Purpose: to select the first item of a non-empty list

---

```
fourth : ((listof Y) -> Y)
```

Purpose: to select the fourth item of a non-empty list

---

```
length : ((listof any) -> number)
```

Purpose: to compute the number of items on a list

---

```
list : (any ... -> (listof any))
```

Purpose: to construct a list of its arguments

---

```
list* : (any ... (listof any) -> (listof any))
```

Purpose: to construct a list by adding multiple items to a list

---

```
list-ref : ((listof X) natural-number -> X)
```

Purpose: to extract the indexed item from the list

---

```
make-list : (natural-number any -> (listof any))
```

Purpose: (make-list k x) constructs a list of k copies of x

---

```
member : (any (listof any) -> boolean)
```

Purpose: to determine whether some value is on the list (comparing values with equal?)

---

```
member? : (any (listof any) -> boolean)
```

Purpose: to determine whether some value is on the list (comparing values with equal?)

---

```
memq : (any (listof any) -> (union false list))
```

Purpose: to determine whether some value is on some list if so, it produces the suffix of the list that starts with x if not, it produces false. (It compares values with the eq? predicate.)

---

```
memv : (any (listof any) -> (union false list))
```

Purpose: to determine whether some value is on the list if so, it produces the suffix of the list that starts with x if not, it produces false. (it compares values with the eqv? predicate.)

---

`null` : empty

Purpose: the empty list

---

`null?` : (any -> boolean)

Purpose: to determine whether some value is the empty list

---

`pair?` : (any -> boolean)

Purpose: to determine whether some value is a constructed list

---

`remove` : (any (listof any) -> (listof any))

Purpose: to construct a list like the given one with the first occurrence of the given item removed (comparing values with equal?)

---

`rest` : ((cons Y (listof X)) -> (listof X))

Purpose: to select the rest of a non-empty list

---

`reverse` : ((listof any) -> list)

Purpose: to create a reversed version of a list

---

`second` : ((cons Z (cons Y (listof X))) -> Y)

Purpose: to select the second item of a non-empty list

---

`seventh` : ((listof Y) -> Y)

Purpose: to select the seventh item of a non-empty list

---

`sixth` : ((listof Y) -> Y)

Purpose: to select the sixth item of a non-empty list

---

`third` : ((cons W (cons Z (cons Y (listof X)))) -> Y)

Purpose: to select the third item of a non-empty list

---

### 3.8.5 Posns

---

`make-posn` : (number number -> posn)

Purpose: to construct a posn

---

`posn` : signature

Purpose: signature for posns

---

`posn-x` : (posn -> number)

Purpose: to extract the x component of a posn

---

`posn-y` : (posn -> number)

Purpose: to extract the y component of a posn

---

`posn?` : (anything -> boolean)

Purpose: to determine if its input is a posn

### 3.8.6 Characters

---

`char->integer` : (char -> integer)

Purpose: to lookup the number that corresponds to the given character in the ASCII table (if any)

---

`char-alphabetic?` : (char -> boolean)

Purpose: to determine whether a character represents an alphabetic character

---

`char-ci<=?` : (char char char ... -> boolean)

Purpose: to determine whether a character precedes another (or is equal to it) in a case-insensitive manner

---

`char-ci<?` : (char char char ... -> boolean)

Purpose: to determine whether a character precedes another in a case-insensitive manner

---

```
char-ci=? : (char char char ... -> boolean)
```

Purpose: to determine whether two characters are equal in a case-insensitive manner

---

```
char-ci>=? : (char char char ... -> boolean)
```

Purpose: to determine whether a character succeeds another (or is equal to it) in a case-insensitive manner

---

```
char-ci>? : (char char char ... -> boolean)
```

Purpose: to determine whether a character succeeds another in a case-insensitive manner

---

```
char-downcase : (char -> char)
```

Purpose: to determine the equivalent lower-case character

---

```
char-lower-case? : (char -> boolean)
```

Purpose: to determine whether a character is a lower-case character

---

```
char-numeric? : (char -> boolean)
```

Purpose: to determine whether a character represents a digit

---

```
char-upcase : (char -> char)
```

Purpose: to determine the equivalent upper-case character

---

```
char-upper-case? : (char -> boolean)
```

Purpose: to determine whether a character is an upper-case character

---

```
char-whitespace? : (char -> boolean)
```

Purpose: to determine whether a character represents space

---

```
char<=? : (char char char ... -> boolean)
```

Purpose: to determine whether a character precedes another (or is equal to it)

---

`char<? : (char char char ... -> boolean)`

Purpose: to determine whether a character precedes another

---

`char=? : (char char char ... -> boolean)`

Purpose: to determine whether two characters are equal

---

`char>=? : (char char char ... -> boolean)`

Purpose: to determine whether a character succeeds another (or is equal to it)

---

`char>? : (char char char ... -> boolean)`

Purpose: to determine whether a character succeeds another

---

`char? : (any -> boolean)`

Purpose: to determine whether a value is a character

### 3.8.7 Strings

---

`explode : (string -> (listof string))`

Purpose: to translate a string into a list of 1-letter strings

---

`format : (string any ... -> string)`

Purpose: to format a string, possibly embedding values

---

`implode : ((listof string) -> string)`

Purpose: to concatenate the list of 1-letter strings into one string

---

`int->string : (integer -> string)`

Purpose: to convert an integer in [0,55295] or [57344 1114111] to a 1-letter string

---

`list->string` : ((listof char) -> string)

Purpose: to convert a s list of characters into a string

---

`make-string` : (nat char -> string)

Purpose: to produce a string of given length from a single given character

---

`replicate` : (nat string -> string)

Purpose: to replicate the given string

---

`string` : (char ... -> string)

Purpose: (string c1 c2 ...) builds a string

---

`string->int` : (string -> integer)

Purpose: to convert a 1-letter string to an integer in [0,55295] or [57344, 1114111]

---

`string->list` : (string -> (listof char))

Purpose: to convert a string into a list of characters

---

`string->number` : (string -> (union number false))

Purpose: to convert a string into a number, produce false if impossible

---

`string->symbol` : (string -> symbol)

Purpose: to convert a string into a symbol

---

`string-alphabetic?` : (string -> boolean)

Purpose: to determine whether all 'letters' in the string are alphabetic

---

`string-append` : (string ... -> string)

Purpose: to juxtapose the characters of several strings

---

`string-ci<=?` : (string string string ... -> boolean)

Purpose: to determine whether one string alphabetically precedes another (or is equal to it) in a case-insensitive manner

---

`string-ci<?` : (string string string ... -> boolean)

Purpose: to determine whether one string alphabetically precedes another in a case-insensitive manner

---

`string-ci=?` : (string string string ... -> boolean)

Purpose: to compare two strings character-wise in a case-insensitive manner

---

`string-ci>=?` : (string string string ... -> boolean)

Purpose: to determine whether one string alphabetically succeeds another (or is equal to it) in a case-insensitive manner

---

`string-ci>?` : (string string string ... -> boolean)

Purpose: to determine whether one string alphabetically succeeds another in a case-insensitive manner

---

`string-copy` : (string -> string)

Purpose: to copy a string

---

`string-ith` : (string nat -> string)

Purpose: to extract the *i*th 1-letter substring from the given one

---

`string-length` : (string -> nat)

Purpose: to determine the length of a string

---

`string-lower-case?` : (string -> boolean)

Purpose: to determine whether all 'letters' in the string are lower case



---

`string-numeric?` : (string -> boolean)

Purpose: to determine whether all 'letters' in the string are numeric

---

`string-ref` : (string nat -> char)

Purpose: to extract the i-th character from a string

---

`string-upper-case?` : (string -> boolean)

Purpose: to determine whether all 'letters' in the string are upper case

---

`string-whitespace?` : (string -> boolean)

Purpose: to determine whether all 'letters' in the string are white space

---

`string<=?` : (string string string ... -> boolean)

Purpose: to determine whether one string alphabetically precedes another (or is equal to it)

---

`string<?` : (string string string ... -> boolean)

Purpose: to determine whether one string alphabetically precedes another

---

`string=?` : (string string string ... -> boolean)

Purpose: to compare two strings character-wise

---

`string>=?` : (string string string ... -> boolean)

Purpose: to determine whether one string alphabetically succeeds another (or is equal to it)

---

`string>?` : (string string string ... -> boolean)

Purpose: to determine whether one string alphabetically succeeds another

---

`string?` : (any -> boolean)

Purpose: to determine whether a value is a string

---

`substring` : (string nat nat -> string)

Purpose: to extract the substring starting at a 0-based index up to the second 0-based index (exclusive)

### 3.8.8 Images

---

`image=?` : (image image -> boolean)

Purpose: to determine whether two images are equal

---

`image?` : (any -> boolean)

Purpose: to determine whether a value is an image

### 3.8.9 Misc

---

`=~` : (real real non-negative-real -> boolean)

Purpose: to check whether two real numbers are within some amount (the third argument) of either other

---

`eof` : eof

Purpose: the end-of-file value

---

`eof-object?` : (any -> boolean)

Purpose: to determine whether some value is the end-of-file value

---

`eq?` : (any any -> boolean)

Purpose: to determine whether two values are equivalent from the computer's perspective (intensional)

---

`equal?` : (any any -> boolean)

Purpose: to determine whether two values are structurally equal where basic values are

compared with the `eqv?` predicate

---

`equal~?` : (any any non-negative-real -> boolean)

Purpose: to compare like `equal?` on the first two arguments, except using `=~` in the case of real numbers

---

`eqv?` : (any any -> boolean)

Purpose: to determine whether two values are equivalent from the perspective of all functions that can be applied to it (extensional)

---

`error` : (any ... -> void)

Purpose: to signal an error, combining the given values into an error message.

If any of the values' printed representations is too long, it is truncated and “...” is put into the string. If the first value is a symbol, it is treated specially; it is suffixed with a colon and a space (the intention is that the symbol is the name of the function signalling the error).

---

`exit` : (-> void)

Purpose: to exit the running program

---

`identity` : (any -> any)

Purpose: to return the argument unchanged

---

`struct?` : (any -> boolean)

Purpose: to determine whether some value is a structure

### 3.8.10 Numbers (relaxed conditions)

---

`*` : (number ... -> number)

Purpose: to multiply all given numbers

---

`+` : (number ... -> number)

Purpose: to add all given numbers

---

```
- : (number ... -> number)
```

Purpose: to subtract from the first all remaining numbers

---

```
/ : (number ... -> number)
```

Purpose: to divide the first by all remaining numbers

### 3.8.11 Higher-Order Functions

---

```
andmap : ((X -> boolean) (listof X) -> boolean)
```

Purpose:  $(\text{andmap } p \text{ (list } x-1 \dots x-n)) = (\text{and } (p \ x-1) \dots (p \ x-n))$

---

```
apply : ((X-1 ... X-N -> Y)
         X-1
         ...
         X-i
         (list X-i+1 ... X-N)
         ->
         Y)
```

Purpose: to apply a function using items from a list as the arguments

---

```
argmax : ((X -> real) (listof X) -> X)
```

Purpose: to find the (first) element of the list that maximizes the output of the function

---

```
argmin : ((X -> real) (listof X) -> X)
```

Purpose: to find the (first) element of the list that minimizes the output of the function

---

```
build-list : (nat (nat -> X) -> (listof X))
```

Purpose:  $(\text{build-list } n \ f) = (\text{list } (f \ 0) \dots (f \ (- \ n \ 1)))$

---

```
build-string : (nat (nat -> char) -> string)
```

Purpose: (build-string n f) = (string (f 0) ... (f (- n 1)))

---

```
compose : ((Y-1 -> Z)
           ...
           (Y-N -> Y-N-1)
           (X-1 ... X-N -> Y-N)
           ->
           (X-1 ... X-N -> Z))
```

Purpose: to compose a sequence of procedures into a single procedure

---

```
filter : ((X -> boolean) (listof X) -> (listof X))
```

Purpose: to construct a list from all those items on a list for which the predicate holds

---

```
foldl : ((X Y -> Y) Y (listof X) -> Y)
```

Purpose: (foldl f base (list x-1 ... x-n)) = (f x-n ... (f x-1 base))

---

```
foldr : ((X Y -> Y) Y (listof X) -> Y)
```

Purpose: (foldr f base (list x-1 ... x-n)) = (f x-1 ... (f x-n base))

---

```
for-each : ((any ... -> any) (listof any) ... -> void)
```

Purpose: to apply a function to each item on one or more lists for effect only

---

```
map : ((X ... -> Z) (listof X) ... -> (listof Z))
```

Purpose: to construct a new list by applying a function to each item on one or more existing lists

---

```
memf : ((X -> boolean)
        (listof X)
        ->
        (union false (listof X)))
```

Purpose: to determine whether the first argument produces true for some value in the second argument

---

```
ormap : ((X -> boolean) (listof X) -> boolean)
```

Purpose: (ormap p (list x-1 ... x-n)) = (or (p x-1) ... (p x-n))

---

```
procedure? : (any -> boolean)
```

Purpose: to determine if a value is a procedure

---

```
quicksort : ((listof X) (X X -> boolean) -> (listof X))
```

Purpose: to construct a list from all items on a list in an order according to a predicate

---

```
sort : ((listof X) (X X -> boolean) -> (listof X))
```

Purpose: to construct a list from all items on a list in an order according to a predicate

### 3.9 Unchanged Forms

---

```
(cond [expr expr] ... [expr expr])  
else
```

The same as Beginning's cond.

---

```
(if expr expr expr)
```

The same as Beginning's if.

---

```
(and expr expr expr ...)  
(or expr expr expr ...)
```

The same as Beginning's and and or.

---

```
(check-expect expr expr)  
(check-within expr expr expr)  
(check-error expr expr)  
(check-error expr)  
(check-member-of expr expr expr ...)  
(check-range expr expr expr)
```

The same as Beginning's check-expect, etc.

---

```
empty : empty?  
true  : boolean?  
false : boolean?
```

Constants for the empty list, true, and false.

---

```
(require module-path)
```

The same as Beginning's require.

## 4 Intermediate Student with Lambda

```
program = def-or-expr ...

def-or-expr = definition
            | expr
            | test-case
            | library-require

definition = (define (id id id ...) expr)
            | (define id expr)
            | (define-struct id (id ...))

expr = (lambda (id id ...) expr)
      | (λ (id id ...) expr)
      | (local [definition ...] expr)
      | (letrec ([id expr] ...) expr)
      | (let ([id expr] ...) expr)
      | (let* ([id expr] ...) expr)
      | (expr expr expr ...) ; function call
      | (cond [expr expr] ... [expr expr])
      | (cond [expr expr] ... [else expr])
      | (if expr expr expr)
      | (and expr expr expr ...)
      | (or expr expr expr ...)
      | (time expr)
      | empty
      | id ; identifier
      | prim-op ; primitive operation
      | 'quoted ; quoted value
      | 'quasiquoted ; quasiquote
      | number
      | true
      | false
      | string
      | character

quoted = id
        | number
        | string
        | character
        | (quoted ...)
        | 'quoted
        | 'quoted
        | ,quoted
```



```

| ,@quoted

quasiquoted = id
| number
| string
| character
| (quasiquoted ...)
| 'quasiquoted
| `quasiquoted
| ,expr
| ,@expr

test-case = (check-expect expr expr)
| (check-within expr expr expr)
| (check-member-of expr expr ...)
| (check-range expr expr expr)
| (check-error expr expr)
| (check-error expr)

library-require = (require string)
| (require (lib string string ...))
| (require (planet string package))

package = (string string number number)

```

An *id* is a sequence of characters not including a space or one of the following:

```
" , ' ( ) [ ] { } | ; #
```

A *number* is a number such as 123, 3/2, or 5.5.

A *string* is enclosed by a pair of `"`. Unlike symbols, strings may be split into characters and manipulated by a variety of primitive functions. For example, `"abcdef"`, `"This is a string"`, and `"This is a string with \" inside"` are all strings.

A *character* begins with `#\` and has the name of the character. For example, `#\a`, `#\b`, and `#\space` are characters.

A *prim-op* is one of:

**Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts**

```

< : (real real real ... -> boolean)
<= : (real real real ... -> boolean)
= : (number number number ... -> boolean)
> : (real real real ... -> boolean)
>= : (real real ... -> boolean)
abs : (real -> real)
acos : (number -> number)

```

```

add1 : (number -> number)
angle : (number -> real)
asin : (number -> number)
atan : (number -> number)
ceiling : (real -> integer)
complex? : (any -> boolean)
conjugate : (number -> number)
cos : (number -> number)
cosh : (number -> number)
current-seconds : (-> integer)
denominator : (rat -> integer)
e : real
even? : (integer -> boolean)
exact->inexact : (number -> number)
exact? : (number -> boolean)
exp : (number -> number)
expt : (number number -> number)
floor : (real -> integer)
gcd : (integer integer ... -> integer)
imag-part : (number -> real)
inexact->exact : (number -> number)
inexact? : (number -> boolean)
integer->char : (integer -> char)
integer-sqrt : (number -> integer)
integer? : (any -> boolean)
lcm : (integer integer ... -> integer)
log : (number -> number)
magnitude : (number -> real)
make-polar : (real real -> number)
make-rectangular : (real real -> number)
max : (real real ... -> real)
min : (real real ... -> real)
modulo : (integer integer -> integer)
negative? : (number -> boolean)
number->string : (number -> string)
number? : (any -> boolean)
numerator : (rat -> integer)
odd? : (integer -> boolean)
pi : real
positive? : (number -> boolean)
quotient : (integer integer -> integer)
random : (integer -> integer)
rational? : (any -> boolean)
real-part : (number -> real)
real? : (any -> boolean)
remainder : (integer integer -> integer)

```

```

round : (real -> integer)
sgn : (real -> (union 1 1.0 0 0.0 -1 -1.0))
sin : (number -> number)
sinh : (number -> number)
sqr : (number -> number)
sqrt : (number -> number)
sub1 : (number -> number)
tan : (number -> number)
zero? : (number -> boolean)

```

### Booleans

```

boolean=? : (boolean boolean -> boolean)
boolean? : (any -> boolean)
false? : (any -> boolean)
not : (boolean -> boolean)

```

### Symbols

```

symbol->string : (symbol -> string)
symbol=? : (symbol symbol -> boolean)
symbol? : (any -> boolean)

```

### Lists

```

append : ((listof any) ... -> (listof any))
assq : (X
        (listof (cons X Y))
        ->
        (union false (cons X Y)))
caaar : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
        ->
        W)
caadr : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
        ->
        (listof Z))
caar : ((cons (cons Z (listof Y)) (listof X)) -> Z)
cadar : ((cons (cons W (cons Z (listof Y))) (listof X))
        ->
        Z)
caddr : ((listof Y) -> Y)
caddr : ((cons W (cons Z (cons Y (listof X)))) -> Y)
cadr : ((cons Z (cons Y (listof X))) -> Y)
car : ((cons Y (listof X)) -> Y)

```

```

cdaar : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
         ->
         (listof Z))
cdadr : ((cons W (cons (cons Z (listof Y)) (listof X)))
         ->
         (listof Y))
cdar : ((cons (cons Z (listof Y)) (listof X))
        ->
        (listof Y))
cddar : ((cons (cons W (cons Z (listof Y))) (listof X))
         ->
         (listof Y))
cddddr : ((cons W (cons Z (cons Y (listof X))))
          ->
          (listof X))
cddr : ((cons Z (cons Y (listof X))) -> (listof X))
cdr : ((cons Y (listof X)) -> (listof X))
cons : (X (listof X) -> (listof X))
cons? : (any -> boolean)
eighth : ((listof Y) -> Y)
empty? : (any -> boolean)
fifth : ((listof Y) -> Y)
first : ((cons Y (listof X)) -> Y)
fourth : ((listof Y) -> Y)
length : ((listof any) -> number)
list : (any ... -> (listof any))
list* : (any ... (listof any) -> (listof any))
list-ref : ((listof X) natural-number -> X)
make-list : (natural-number any -> (listof any))
member : (any (listof any) -> boolean)
member? : (any (listof any) -> boolean)
memq : (any (listof any) -> (union false list))
memv : (any (listof any) -> (union false list))
null : empty
null? : (any -> boolean)
pair? : (any -> boolean)
remove : (any (listof any) -> (listof any))
rest : ((cons Y (listof X)) -> (listof X))
reverse : ((listof any) -> list)
second : ((cons Z (cons Y (listof X))) -> Y)
seventh : ((listof Y) -> Y)
sixth : ((listof Y) -> Y)
third : ((cons W (cons Z (cons Y (listof X)))) -> Y)

```

## Posns

```
make-posn : (number number -> posn)
posn : signature
posn-x : (posn -> number)
posn-y : (posn -> number)
posn? : (anything -> boolean)
```

### Characters

```
char->integer : (char -> integer)
char-alphabetic? : (char -> boolean)
char-ci<=? : (char char char ... -> boolean)
char-ci<? : (char char char ... -> boolean)
char-ci=? : (char char char ... -> boolean)
char-ci>=? : (char char char ... -> boolean)
char-ci>? : (char char char ... -> boolean)
char-downcase : (char -> char)
char-lower-case? : (char -> boolean)
char-numeric? : (char -> boolean)
char-upcase : (char -> char)
char-upper-case? : (char -> boolean)
char-whitespace? : (char -> boolean)
char<=? : (char char char ... -> boolean)
char<? : (char char char ... -> boolean)
char=? : (char char char ... -> boolean)
char>=? : (char char char ... -> boolean)
char>? : (char char char ... -> boolean)
char? : (any -> boolean)
```

### Strings

```
explode : (string -> (listof string))
format : (string any ... -> string)
implode : ((listof string) -> string)
int->string : (integer -> string)
list->string : ((listof char) -> string)
make-string : (nat char -> string)
replicate : (nat string -> string)
string : (char ... -> string)
string->int : (string -> integer)
string->list : (string -> (listof char))
string->number : (string -> (union number false))
string->symbol : (string -> symbol)
string-alphabetic? : (string -> boolean)
string-append : (string ... -> string)
string-ci<=? : (string string string ... -> boolean)
string-ci<? : (string string string ... -> boolean)
string-ci=? : (string string string ... -> boolean)
string-ci>=? : (string string string ... -> boolean)
string-ci>? : (string string string ... -> boolean)
string-copy : (string -> string)
```

```

string-ith : (string nat -> string)
string-length : (string -> nat)
string-lower-case? : (string -> boolean)
string-numeric? : (string -> boolean)
string-ref : (string nat -> char)
string-upper-case? : (string -> boolean)
string-whitespace? : (string -> boolean)
string<=? : (string string string ... -> boolean)
string<? : (string string string ... -> boolean)
string=? : (string string string ... -> boolean)
string>=? : (string string string ... -> boolean)
string>? : (string string string ... -> boolean)
string? : (any -> boolean)
substring : (string nat nat -> string)

```

### Images

```

image=? : (image image -> boolean)
image? : (any -> boolean)

```

### Misc

```

≈~ : (real real non-negative-real -> boolean)
eof : eof
eof-object? : (any -> boolean)
eq? : (any any -> boolean)
equal? : (any any -> boolean)
equal~? : (any any non-negative-real -> boolean)
eqv? : (any any -> boolean)
error : (any ... -> void)
exit : (-> void)
identity : (any -> any)
struct? : (any -> boolean)

```

### Numbers (relaxed conditions)

```

* : (number ... -> number)
+ : (number ... -> number)
- : (number ... -> number)
/ : (number ... -> number)

```

### Higher-Order Functions

```

andmap : ((X -> boolean) (listof X) -> boolean)
apply : ((X-1 ... X-N -> Y)
         X-1
         ...
         X-i
         (list X-i+1 ... X-N)
         ->
         Y)
argmax : ((X -> real) (listof X) -> X)
argmin : ((X -> real) (listof X) -> X)
build-list : (nat (nat -> X) -> (listof X))

```

```

build-string : (nat (nat -> char) -> string)
compose : ((Y-1 -> Z)
  ...
  (Y-N -> Y-N-1)
  (X-1 ... X-N -> Y-N)
  ->
  (X-1 ... X-N -> Z))
filter : ((X -> boolean) (listof X) -> (listof X))
foldl : ((X Y -> Y) Y (listof X) -> Y)
foldr : ((X Y -> Y) Y (listof X) -> Y)
for-each : ((any ... -> any) (listof any) ... -> void)
map : ((X ... -> Z) (listof X) ... -> (listof Z))
memf : ((X -> boolean)
  (listof X)
  ->
  (union false (listof X)))
ormap : ((X -> boolean) (listof X) -> boolean)
procedure? : (any -> boolean)
quicksort : ((listof X) (X X -> boolean) -> (listof X))
sort : ((listof X) (X X -> boolean) -> (listof X))

```

## 4.1 define

---

```

(define (id id id ...) expr)
(define id expr)

```

The same as Intermediate's `define`. No special case is needed for `lambda`, since a `lambda` form is an expression.

## 4.2 lambda

---

```

(lambda (id id ...) expr)

```

Creates a function that takes as many arguments as given *ids*, and whose body is *expr*.

---

```

(λ (id id ...) expr)

```

The Greek letter  $\lambda$  is a synonym for `lambda`.

### 4.3 Function Calls

---

```
(expr expr expr ...)
```

Like a Beginning function call, except that the function position can be an arbitrary expression—perhaps a lambda expression or a *prim-op*.

---

```
(#%app expr expr expr ...)
```

A function call can be written with `%app`, though it's practically never written that way.

### 4.4 Primitive Operation Names

---

*prim-op*

The name of a primitive operation can be used as an expression. It produces a function version of the operation.

#### 4.4.1 Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts

---

```
< : (real real real ... -> boolean)
```

Purpose: to compare real numbers for less-than

---

```
<= : (real real real ... -> boolean)
```

Purpose: to compare real numbers for less-than or equality

---

```
= : (number number number ... -> boolean)
```

Purpose: to compare numbers for equality

---

```
> : (real real real ... -> boolean)
```

Purpose: to compare real numbers for greater-than

---

```
>= : (real real ... -> boolean)
```



Purpose: to compare real numbers for greater-than or equality

---

`abs` : (real -> real)

Purpose: to compute the absolute value of a real number

---

`acos` : (number -> number)

Purpose: to compute the arccosine (inverse of cos) of a number

---

`add1` : (number -> number)

Purpose: to compute a number one larger than a given number

---

`angle` : (number -> real)

Purpose: to extract the angle from a complex number

---

`asin` : (number -> number)

Purpose: to compute the arcsine (inverse of sin) of a number

---

`atan` : (number -> number)

Purpose: to compute the arctan (inverse of tan) of a number

---

`ceiling` : (real -> integer)

Purpose: to determine the closest integer (exact or inexact) above a real number

---

`complex?` : (any -> boolean)

Purpose: to determine whether some value is complex

---

`conjugate` : (number -> number)

Purpose: to compute the conjugate of a complex number

---

`cos` : (number -> number)

Purpose: to compute the cosine of a number (radians)

---

`cosh` : (number -> number)

Purpose: to compute the hyperbolic cosine of a number

---

`current-seconds` : (-> integer)

Purpose: to compute the current time in seconds elapsed (since a platform-specific starting date)

---

`denominator` : (rat -> integer)

Purpose: to compute the denominator of a rational

---

`e` : real

Purpose: Euler's number

---

`even?` : (integer -> boolean)

Purpose: to determine if some integer (exact or inexact) is even or not

---

`exact->inexact` : (number -> number)

Purpose: to convert an exact number to an inexact one

---

`exact?` : (number -> boolean)

Purpose: to determine whether some number is exact

---

`exp` : (number -> number)

Purpose: to compute e raised to a number

---

`expt` : (number number -> number)

Purpose: to compute the power of the first to the second number

---

`floor` : (real -> integer)

Purpose: to determine the closest integer (exact or inexact) below a real number

---

`gcd` : (integer integer ... -> integer)

Purpose: to compute the greatest common divisor of two integers (exact or inexact)

---

`imag-part` : (number -> real)

Purpose: to extract the imaginary part from a complex number

---

`inexact->exact` : (number -> number)

Purpose: to approximate an inexact number by an exact one

---

`inexact?` : (number -> boolean)

Purpose: to determine whether some number is inexact

---

`integer->char` : (integer -> char)

Purpose: to lookup the character that corresponds to the given integer (exact only!) in the ASCII table (if any)

---

`integer-sqrt` : (number -> integer)

Purpose: to compute the integer (exact or inexact) square root of a number

---

`integer?` : (any -> boolean)

Purpose: to determine whether some value is an integer (exact or inexact)

---

`lcm` : (integer integer ... -> integer)

Purpose: to compute the least common multiple of two integers (exact or inexact)

---

`log` : (number -> number)

Purpose: to compute the base-e logarithm of a number

---

`magnitude` : (number -> real)

Purpose: to determine the magnitude of a complex number

---

`make-polar` : (real real -> number)

Purpose: to create a complex from a magnitude and angle

---

`make-rectangular` : (real real -> number)

Purpose: to create a complex from a real and an imaginary part

---

`max` : (real real ... -> real)

Purpose: to determine the largest number

---

`min` : (real real ... -> real)

Purpose: to determine the smallest number

---

`modulo` : (integer integer -> integer)

Purpose: to find the remainder of the division of the first number by the second; try (modulo 4 3) (modulo 4 -3)

---

`negative?` : (number -> boolean)

Purpose: to determine if some value is strictly smaller than zero

---

`number->string` : (number -> string)

Purpose: to convert a number to a string

---

`number?` : (any -> boolean)

Purpose: to determine whether some value is a number

---

`numerator` : (rat -> integer)

Purpose: to compute the numerator of a rational

---

`odd?` : (integer -> boolean)

Purpose: to determine if some integer (exact or inexact) is odd or not

---

`pi` : real

Purpose: the ratio of a circle's circumference to its diameter

---

`positive?` : (number -> boolean)

Purpose: to determine if some value is strictly larger than zero

---

`quotient` : (integer integer -> integer)

Purpose: to divide the first integer (exact or inexact) into the second; try (quotient 3 4) and (quotient 4 3)

---

`random` : (integer -> integer)

Purpose: to generate a random natural number less than some given integer (exact only!)

---

`rational?` : (any -> boolean)

Purpose: to determine whether some value is a rational number

---

`real-part` : (number -> real)

Purpose: to extract the real part from a complex number

---

`real?` : (any -> boolean)

Purpose: to determine whether some value is a real number

---

`remainder` : (integer integer -> integer)

Purpose: to determine the remainder of dividing the first by the second integer (exact or inexact)

---

`round` : (real -> integer)

Purpose: to round a real number to an integer (rounds to even to break ties)

---

`sgn` : (real -> (union 1 1.0 0 0.0 -1 -1.0))

Purpose: to compute the sign of a real number

---

`sin` : (number -> number)

Purpose: to compute the sine of a number (radians)

---

`sinh` : (number -> number)

Purpose: to compute the hyperbolic sine of a number

---

`sqr` : (number -> number)

Purpose: to compute the square of a number

---

`sqrt` : (number -> number)

Purpose: to compute the square root of a number

---

`sub1` : (number -> number)

Purpose: to compute a number one smaller than a given number

---

`tan` : (number -> number)

Purpose: to compute the tangent of a number (radians)

---

`zero?` : (number -> boolean)

Purpose: to determine if some value is zero or not

---

#### 4.4.2 Booleans

---

`boolean=?` : (boolean boolean -> boolean)

Purpose: to determine whether two booleans are equal

---

`boolean?` : (any -> boolean)

Purpose: to determine whether some value is a boolean

---

`false?` : (any -> boolean)

Purpose: to determine whether a value is false

---

`not` : (boolean -> boolean)

Purpose: to compute the negation of a boolean value

---

### 4.4.3 Symbols

---

`symbol->string` : (symbol -> string)

Purpose: to convert a symbol to a string

---

`symbol=?` : (symbol symbol -> boolean)

Purpose: to determine whether two symbols are equal

---

`symbol?` : (any -> boolean)

Purpose: to determine whether some value is a symbol

---

### 4.4.4 Lists

---

`append` : ((listof any) ... -> (listof any))

Purpose: to create a single list from several, by juxtaposition of the items

---

`assq` : (X  
    (listof (cons X Y))  
    ->  
    (union false (cons X Y)))

Purpose: to determine whether some item is the first item of a pair in a list of pairs

---

---

```
caaar : ((cons
         (cons (cons W (listof Z)) (listof Y))
         (listof X))
        ->
        W)
```

Purpose: to select the first item of the first list in the first list of a list

---

```
caadr : ((cons
         (cons (cons W (listof Z)) (listof Y))
         (listof X))
        ->
        (listof Z))
```

Purpose: to select the rest of the first list in the first list of a list

---

```
caar : ((cons (cons Z (listof Y)) (listof X)) -> Z)
```

Purpose: to select the first item of the first list in a list

---

```
cadar : ((cons (cons W (cons Z (listof Y))) (listof X))
        ->
        Z)
```

Purpose: to select the second item of the first list of a list

---

```
caddr : ((listof Y) -> Y)
```

Purpose: to select the fourth item of a non-empty list

---

```
caddr : ((cons W (cons Z (cons Y (listof X)))) -> Y)
```

Purpose: to select the third item of a non-empty list

---

```
cadr : ((cons Z (cons Y (listof X))) -> Y)
```

Purpose: to select the second item of a non-empty list

---

```
car : ((cons Y (listof X)) -> Y)
```

Purpose: to select the first item of a non-empty list



---

```
cdaar : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
         ->
         (listof Z))
```

Purpose: to select the rest of the first list in the first list of a list

---

```
cdadr : ((cons W (cons (cons Z (listof Y)) (listof X)))
         ->
         (listof Y))
```

Purpose: to select the rest of the first list in the rest of a list

---

```
cdar : ((cons (cons Z (listof Y)) (listof X))
        ->
        (listof Y))
```

Purpose: to select the rest of a non-empty list in a list

---

```
cddar : ((cons (cons W (cons Z (listof Y))) (listof X))
         ->
         (listof Y))
```

Purpose: to select the rest of the rest of the first list of a list

---

```
cddr : ((cons W (cons Z (cons Y (listof X))))
        ->
        (listof X))
```

Purpose: to select the rest of the rest of the rest of a list

---

```
cddr : ((cons Z (cons Y (listof X))) -> (listof X))
```

Purpose: to select the rest of the rest of a list

---

```
cdr : ((cons Y (listof X)) -> (listof X))
```

Purpose: to select the rest of a non-empty list

---

```
cons : (X (listof X) -> (listof X))
```

Purpose: to construct a list

---

```
cons? : (any -> boolean)
```

Purpose: to determine whether some value is a constructed list

---

```
eighth : ((listof Y) -> Y)
```

Purpose: to select the eighth item of a non-empty list

---

```
empty? : (any -> boolean)
```

Purpose: to determine whether some value is the empty list

---

```
fifth : ((listof Y) -> Y)
```

Purpose: to select the fifth item of a non-empty list

---

```
first : ((cons Y (listof X)) -> Y)
```

Purpose: to select the first item of a non-empty list

---

```
fourth : ((listof Y) -> Y)
```

Purpose: to select the fourth item of a non-empty list

---

```
length : ((listof any) -> number)
```

Purpose: to compute the number of items on a list

---

```
list : (any ... -> (listof any))
```

Purpose: to construct a list of its arguments

---

```
list* : (any ... (listof any) -> (listof any))
```

Purpose: to construct a list by adding multiple items to a list

---

```
list-ref : ((listof X) natural-number -> X)
```

Purpose: to extract the indexed item from the list

---

```
make-list : (natural-number any -> (listof any))
```

Purpose: (make-list k x) constructs a list of k copies of x

---

```
member : (any (listof any) -> boolean)
```

Purpose: to determine whether some value is on the list (comparing values with equal?)

---

```
member? : (any (listof any) -> boolean)
```

Purpose: to determine whether some value is on the list (comparing values with equal?)

---

```
memq : (any (listof any) -> (union false list))
```

Purpose: to determine whether some value is on some list if so, it produces the suffix of the list that starts with x if not, it produces false. (It compares values with the eq? predicate.)

---

```
memv : (any (listof any) -> (union false list))
```

Purpose: to determine whether some value is on the list if so, it produces the suffix of the list that starts with x if not, it produces false. (it compares values with the eqv? predicate.)

---

```
null : empty
```

Purpose: the empty list

---

```
null? : (any -> boolean)
```

Purpose: to determine whether some value is the empty list

---

```
pair? : (any -> boolean)
```

Purpose: to determine whether some value is a constructed list

---

```
remove : (any (listof any) -> (listof any))
```

Purpose: to construct a list like the given one with the first occurrence of the given item removed (comparing values with equal?)

---

`rest` : ((cons Y (listof X)) -> (listof X))

Purpose: to select the rest of a non-empty list

---

`reverse` : ((listof any) -> list)

Purpose: to create a reversed version of a list

---

`second` : ((cons Z (cons Y (listof X))) -> Y)

Purpose: to select the second item of a non-empty list

---

`seventh` : ((listof Y) -> Y)

Purpose: to select the seventh item of a non-empty list

---

`sixth` : ((listof Y) -> Y)

Purpose: to select the sixth item of a non-empty list

---

`third` : ((cons W (cons Z (cons Y (listof X)))) -> Y)

Purpose: to select the third item of a non-empty list

#### 4.4.5 Posns

---

`make-posn` : (number number -> posn)

Purpose: to construct a posn

---

`posn` : signature

Purpose: signature for posns

---

`posn-x` : (posn -> number)

Purpose: to extract the x component of a posn

---

`posn-y` : (posn -> number)

Purpose: to extract the y component of a posn

---

`posn?` : (anything -> boolean)

Purpose: to determine if its input is a posn

#### 4.4.6 Characters

---

`char->integer` : (char -> integer)

Purpose: to lookup the number that corresponds to the given character in the ASCII table (if any)

---

`char-alphabetic?` : (char -> boolean)

Purpose: to determine whether a character represents an alphabetic character

---

`char-ci<=?` : (char char char ... -> boolean)

Purpose: to determine whether a character precedes another (or is equal to it) in a case-insensitive manner

---

`char-ci<?` : (char char char ... -> boolean)

Purpose: to determine whether a character precedes another in a case-insensitive manner

---

`char-ci=?` : (char char char ... -> boolean)

Purpose: to determine whether two characters are equal in a case-insensitive manner

---

`char-ci>=?` : (char char char ... -> boolean)

Purpose: to determine whether a character succeeds another (or is equal to it) in a case-insensitive manner

---

`char-ci>?` : (char char char ... -> boolean)

Purpose: to determine whether a character succeeds another in a case-insensitive manner

---

`char-downcase` : (char -> char)

Purpose: to determine the equivalent lower-case character

---

`char-lower-case?` : (char -> boolean)

Purpose: to determine whether a character is a lower-case character

---

`char-numeric?` : (char -> boolean)

Purpose: to determine whether a character represents a digit

---

`char-upcase` : (char -> char)

Purpose: to determine the equivalent upper-case character

---

`char-upper-case?` : (char -> boolean)

Purpose: to determine whether a character is an upper-case character

---

`char-whitespace?` : (char -> boolean)

Purpose: to determine whether a character represents space

---

`char<=?` : (char char char ... -> boolean)

Purpose: to determine whether a character precedes another (or is equal to it)

---

`char<?` : (char char char ... -> boolean)

Purpose: to determine whether a character precedes another

---

`char=?` : (char char char ... -> boolean)

Purpose: to determine whether two characters are equal

---

`char>=?` : (char char char ... -> boolean)

Purpose: to determine whether a character succeeds another (or is equal to it)

---

`char>?` : (char char char ... -> boolean)

Purpose: to determine whether a character succeeds another

---

`char?` : (any -> boolean)

Purpose: to determine whether a value is a character

#### 4.4.7 Strings

---

`explode` : (string -> (listof string))

Purpose: to translate a string into a list of 1-letter strings

---

`format` : (string any ... -> string)

Purpose: to format a string, possibly embedding values

---

`implode` : ((listof string) -> string)

Purpose: to concatenate the list of 1-letter strings into one string

---

`int->string` : (integer -> string)

Purpose: to convert an integer in [0,55295] or [57344 1114111] to a 1-letter string

---

`list->string` : ((listof char) -> string)

Purpose: to convert a s list of characters into a string

---

`make-string` : (nat char -> string)

Purpose: to produce a string of given length from a single given character

---

`replicate` : (nat string -> string)

Purpose: to replicate the given string

---

`string` : (char ... -> string)

Purpose: (string c1 c2 ...) builds a string

---

`string->int` : (string -> integer)

Purpose: to convert a 1-letter string to an integer in [0,55295] or [57344, 1114111]

---

`string->list` : (string -> (listof char))

Purpose: to convert a string into a list of characters

---

`string->number` : (string -> (union number false))

Purpose: to convert a string into a number, produce false if impossible

---

`string->symbol` : (string -> symbol)

Purpose: to convert a string into a symbol

---

`string-alphabetic?` : (string -> boolean)

Purpose: to determine whether all 'letters' in the string are alphabetic

---

`string-append` : (string ... -> string)

Purpose: to juxtapose the characters of several strings

---

`string-ci<=?` : (string string string ... -> boolean)

Purpose: to determine whether one string alphabetically precedes another (or is equal to it) in a case-insensitive manner

---

`string-ci<?` : (string string string ... -> boolean)

Purpose: to determine whether one string alphabetically precedes another in a case-insensitive manner

---

`string-ci=?` : (string string string ... -> boolean)



Purpose: to compare two strings character-wise in a case-insensitive manner

---

`string-ci>=?` : (string string string ... -> boolean)

Purpose: to determine whether one string alphabetically succeeds another (or is equal to it) in a case-insensitive manner

---

`string-ci>?` : (string string string ... -> boolean)

Purpose: to determine whether one string alphabetically succeeds another in a case-insensitive manner

---

`string-copy` : (string -> string)

Purpose: to copy a string

---

`string-ith` : (string nat -> string)

Purpose: to extract the ith 1-letter substring from the given one

---

`string-length` : (string -> nat)

Purpose: to determine the length of a string

---

`string-lower-case?` : (string -> boolean)

Purpose: to determine whether all 'letters' in the string are lower case

---

`string-numeric?` : (string -> boolean)

Purpose: to determine whether all 'letters' in the string are numeric

---

`string-ref` : (string nat -> char)

Purpose: to extract the i-the character from a string

---

`string-upper-case?` : (string -> boolean)

Purpose: to determine whether all 'letters' in the string are upper case

---

`string-whitespace? : (string -> boolean)`

Purpose: to determine whether all 'letters' in the string are white space

---

`string<=? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically precedes another (or is equal to it)

---

`string<? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically precedes another

---

`string=? : (string string string ... -> boolean)`

Purpose: to compare two strings character-wise

---

`string>=? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically succeeds another (or is equal to it)

---

`string>? : (string string string ... -> boolean)`

Purpose: to determine whether one string alphabetically succeeds another

---

`string? : (any -> boolean)`

Purpose: to determine whether a value is a string

---

`substring : (string nat nat -> string)`

Purpose: to extract the substring starting at a 0-based index up to the second 0-based index (exclusive)

#### 4.4.8 Images

---

`image=? : (image image -> boolean)`

Purpose: to determine whether two images are equal

---

`image?` : (any -> boolean)

Purpose: to determine whether a value is an image

#### 4.4.9 Misc

---

`=~` : (real real non-negative-real -> boolean)

Purpose: to check whether two real numbers are within some amount (the third argument) of either other

---

`eof` : eof

Purpose: the end-of-file value

---

`eof-object?` : (any -> boolean)

Purpose: to determine whether some value is the end-of-file value

---

`eq?` : (any any -> boolean)

Purpose: to determine whether two values are equivalent from the computer's perspective (intensional)

---

`equal?` : (any any -> boolean)

Purpose: to determine whether two values are structurally equal where basic values are compared with the `eqv?` predicate

---

`equal~?` : (any any non-negative-real -> boolean)

Purpose: to compare like `equal?` on the first two arguments, except using `=~` in the case of real numbers

---

`eqv?` : (any any -> boolean)

Purpose: to determine whether two values are equivalent from the perspective of all functions that can be applied to it (extensional)

---

`error` : (any ... -> void)

Purpose: to signal an error, combining the given values into an error message.

If any of the values' printed representations is too long, it is truncated and “...” is put into the string. If the first value is a symbol, it is treated specially; it is suffixed with a colon and a space (the intention is that the symbol is the name of the function signalling the error).

---

`exit` : (-> void)

Purpose: to exit the running program

---

`identity` : (any -> any)

Purpose: to return the argument unchanged

---

`struct?` : (any -> boolean)

Purpose: to determine whether some value is a structure

#### 4.4.10 Numbers (relaxed conditions)

---

`*` : (number ... -> number)

Purpose: to multiply all given numbers

---

`+` : (number ... -> number)

Purpose: to add all given numbers

---

`-` : (number ... -> number)

Purpose: to subtract from the first all remaining numbers

---

`/` : (number ... -> number)

Purpose: to divide the first by all remaining numbers

#### 4.4.11 Higher-Order Functions

---

`andmap` : ((X -> boolean) (listof X) -> boolean)

Purpose: (andmap p (list x-1 ... x-n)) = (and (p x-1) ... (p x-n))

---

`apply` : ((X-1 ... X-N -> Y)  
X-1  
...  
X-i  
(list X-i+1 ... X-N)  
->  
Y)

Purpose: to apply a function using items from a list as the arguments

---

`argmax` : ((X -> real) (listof X) -> X)

Purpose: to find the (first) element of the list that maximizes the output of the function

---

`argmin` : ((X -> real) (listof X) -> X)

Purpose: to find the (first) element of the list that minimizes the output of the function

---

`build-list` : (nat (nat -> X) -> (listof X))

Purpose: (build-list n f) = (list (f 0) ... (f (- n 1)))

---

`build-string` : (nat (nat -> char) -> string)

Purpose: (build-string n f) = (string (f 0) ... (f (- n 1)))

---

`compose` : ((Y-1 -> Z)  
...  
(Y-N -> Y-N-1)  
(X-1 ... X-N -> Y-N)  
->  
(X-1 ... X-N -> Z))

Purpose: to compose a sequence of procedures into a single procedure

---

`filter` : ((X -> boolean) (listof X) -> (listof X))

Purpose: to construct a list from all those items on a list for which the predicate holds

---

`foldl` : ((X Y -> Y) Y (listof X) -> Y)

Purpose: (foldl f base (list x-1 ... x-n)) = (f x-n ... (f x-1 base))

---

`foldr` : ((X Y -> Y) Y (listof X) -> Y)

Purpose: (foldr f base (list x-1 ... x-n)) = (f x-1 ... (f x-n base))

---

`for-each` : ((any ... -> any) (listof any) ... -> void)

Purpose: to apply a function to each item on one or more lists for effect only

---

`map` : ((X ... -> Z) (listof X) ... -> (listof Z))

Purpose: to construct a new list by applying a function to each item on one or more existing lists

---

`memf` : ((X -> boolean)  
          (listof X)  
          ->  
          (union false (listof X)))

Purpose: to determine whether the first argument produces true for some value in the second argument

---

`ormap` : ((X -> boolean) (listof X) -> boolean)

Purpose: (ormap p (list x-1 ... x-n)) = (or (p x-1) ... (p x-n))

---

`procedure?` : (any -> boolean)

Purpose: to determine if a value is a procedure

---

`quicksort` : ((listof X) (X X -> boolean) -> (listof X))

Purpose: to construct a list from all items on a list in an order according to a predicate

---

```
sort : ((listof X) (X X -> boolean) -> (listof X))
```

Purpose: to construct a list from all items on a list in an order according to a predicate

## 4.5 Unchanged Forms

---

```
(define-struct structid (fieldid ...))
```

The same as Intermediate's `define-struct`.

---

```
(local [definition ...] expr)  
(letrec ([id expr-for-let] ...) expr)  
(let ([id expr-for-let] ...) expr)  
(let* ([id expr-for-let] ...) expr)
```

The same as Intermediate's `local`, `letrec`, `let`, and `let*`.

---

```
(cond [expr expr] ... [expr expr])  
else
```

The same as Beginning's `cond`.

---

```
(if expr expr expr)
```

The same as Beginning's `if`.

---

```
(and expr expr expr ...)  
(or expr expr expr ...)
```

The same as Beginning's `and` and `or`.

---

```
(time expr)
```

The same as Intermediate's `time`.

---

```
(check-expect expr expr)  
(check-within expr expr expr)  
(check-error expr expr)  
(check-error expr)
```

```
(check-member-of expr expr expr ...)  
(check-range expr expr expr)
```

The same as Beginning's `check-expect`, etc.

---

```
empty : empty?  
true : boolean?  
false : boolean?
```

Constants for the empty list, true, and false.

---

```
(require module-path)
```

The same as Beginning's `require`.



## 5 Advanced Student

```
program = def-or-expr ...

def-or-expr = definition
            | expr
            | test-case
            | library-require

definition = (define (id id id ...) expr)
            | (define id expr)
            | (define-struct id (id ...))
            | (define-datatype id (id id ...) ...)

expr = (begin expr expr ...)
      | (begin0 expr expr ...)
      | (set! id expr)
      | (delay expr)
      | (lambda (id ...) expr)
      | (λ (id ...) expr)
      | (local [definition ...] expr)
      | (letrec ([id expr] ...) expr)
      | (shared ([id expr] ...) expr)
      | (let ([id expr] ...) expr)
      | (let id ([id expr] ...) expr)
      | (let* ([id expr] ...) expr)
      | (recur id ([id expr] ...) expr)
      | (expr expr ...) ; function call
      | (cond [expr expr] ... [expr expr])
      | (cond [expr expr] ... [else expr])
      | (case expr [(choice choice ...) expr] ...
            [(choice choice ...) expr])
      | (case expr [(choice choice ...) expr] ...
            [else expr])
      | (match expr [pattern expr] ...)
      | (if expr expr expr)
      | (when expr expr)
      | (unless expr expr)
      | (and expr expr expr ...)
      | (or expr expr expr ...)
      | (time expr)
      | empty
      | id ; identifier
      | prim-op ; primitive operation
      | 'quoted ; quoted value
```

```

| 'quasiquoted ; quasiquote
| number
| true
| false
| string
| character

choice = id ; treated as a symbol
| number

pattern = _
| empty
| id
| number
| true
| false
| string
| character
| 'quoted
| 'quasiquoted-pattern
| (cons pattern pattern)
| (list pattern ...)
| (list* pattern ...)
| (struct id (pattern ...))
| (vector pattern ...)
| (box pattern)

quasiquoted-pattern = id
| number
| string
| character
| (quasiquoted-pattern ...)
| 'quasiquoted-pattern
| 'quasiquoted-pattern
| ,pattern
| ,@pattern

quoted = id
| number
| string
| character
| (quoted ...)
| 'quoted
| 'quoted
| ,quoted
| ,@quoted

```

```

quasiquoted = id
              | number
              | string
              | character
              | (quasiquoted ...)
              | 'quasiquoted
              | `quasiquoted
              | ,expr
              | ,@expr

test-case = (check-expect expr expr)
            | (check-within expr expr expr)
            | (check-member-of expr expr ...)
            | (check-range expr expr expr)
            | (check-error expr expr)
            | (check-error expr)

library-require = (require string)
                 | (require (lib string string ...))
                 | (require (planet string package))

package = (string string number number)

```

An *id* is a sequence of characters not including a space or one of the following:

```
" , ' ( ) [ ] { } | ; #
```

A *number* is a number such as 123, 3/2, or 5.5.

A *string* is enclosed by a pair of ". Unlike symbols, strings may be split into characters and manipulated by a variety of primitive functions. For example, "abcdef", "This is a string", and "This is a string with \" inside" are all strings.

A *character* begins with #\ and has the name of the character. For example, #\a, #\b, and #\space are characters.

A *prim-op* is one of:

**Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts**

```

< : (real real real ... -> boolean)
<= : (real real real ... -> boolean)
= : (number number number ... -> boolean)
> : (real real real ... -> boolean)
>= : (real real ... -> boolean)
abs : (real -> real)
acos : (number -> number)
add1 : (number -> number)

```

```

angle : (number -> real)
asin : (number -> number)
atan : (number -> number)
ceiling : (real -> integer)
complex? : (any -> boolean)
conjugate : (number -> number)
cos : (number -> number)
cosh : (number -> number)
current-seconds : (-> integer)
denominator : (rat -> integer)
e : real
even? : (integer -> boolean)
exact->inexact : (number -> number)
exact? : (number -> boolean)
exp : (number -> number)
expt : (number number -> number)
floor : (real -> integer)
gcd : (integer integer ... -> integer)
imag-part : (number -> real)
inexact->exact : (number -> number)
inexact? : (number -> boolean)
integer->char : (integer -> char)
integer-sqrt : (number -> integer)
integer? : (any -> boolean)
lcm : (integer integer ... -> integer)
log : (number -> number)
magnitude : (number -> real)
make-polar : (real real -> number)
make-rectangular : (real real -> number)
max : (real real ... -> real)
min : (real real ... -> real)
modulo : (integer integer -> integer)
negative? : (number -> boolean)
number->string : (number -> string)
number? : (any -> boolean)
numerator : (rat -> integer)
odd? : (integer -> boolean)
pi : real
positive? : (number -> boolean)
quotient : (integer integer -> integer)
random : (case->
  (integer -> integer)
  (-> (and/c real inexact? (>/c 0) (</c 1))))
rational? : (any -> boolean)
real-part : (number -> real)
real? : (any -> boolean)

```

```

remainder : (integer integer -> integer)
round : (real -> integer)
sgn : (real -> (union 1 1.0 0 0.0 -1 -1.0))
sin : (number -> number)
sinh : (number -> number)
sqr : (number -> number)
sqrt : (number -> number)
sub1 : (number -> number)
tan : (number -> number)
zero? : (number -> boolean)

```

### Booleans

```

boolean=? : (boolean boolean -> boolean)
boolean? : (any -> boolean)
false? : (any -> boolean)
not : (boolean -> boolean)

```

### Symbols

```

symbol->string : (symbol -> string)
symbol=? : (symbol symbol -> boolean)
symbol? : (any -> boolean)

```

### Lists

```

append : ((listof any) ... -> (listof any))
assoc : (any (listof any) -> (listof any) or false)
assq : (X
      (listof (cons X Y))
      ->
      (union false (cons X Y)))
caaar : ((cons
      (cons (cons W (listof Z)) (listof Y))
      (listof X))
      ->
      W)
caadr : ((cons
      (cons (cons W (listof Z)) (listof Y))
      (listof X))
      ->
      (listof Z))
caar : ((cons (cons Z (listof Y)) (listof X)) -> Z)
cadar : ((cons (cons W (cons Z (listof Y))) (listof X))
      ->
      Z)
caddr : ((listof Y) -> Y)
caddr : ((cons W (cons Z (cons Y (listof X)))) -> Y)
cadr : ((cons Z (cons Y (listof X))) -> Y)
car : ((cons Y (listof X)) -> Y)

```

```

cdaar : ((cons
          (cons (cons W (listof Z)) (listof Y))
          (listof X))
         ->
         (listof Z))
cdadr : ((cons W (cons (cons Z (listof Y)) (listof X)))
         ->
         (listof Y))
cdar : ((cons (cons Z (listof Y)) (listof X))
        ->
        (listof Y))
cddar : ((cons (cons W (cons Z (listof Y))) (listof X))
         ->
         (listof Y))
cddddr : ((cons W (cons Z (cons Y (listof X))))
          ->
          (listof X))
cddr : ((cons Z (cons Y (listof X))) -> (listof X))
cdr : ((cons Y (listof X)) -> (listof X))
cons : (X (listof X) -> (listof X))
cons? : (any -> boolean)
eighth : ((listof Y) -> Y)
empty? : (any -> boolean)
fifth : ((listof Y) -> Y)
first : ((cons Y (listof X)) -> Y)
fourth : ((listof Y) -> Y)
length : ((listof any) -> number)
list : (any ... -> (listof any))
list* : (any ... (listof any) -> (listof any))
list-ref : ((listof X) natural-number -> X)
list? : (any -> boolean)
make-list : (natural-number any -> (listof any))
member : (any (listof any) -> boolean)
member? : (any (listof any) -> boolean)
memq : (any (listof any) -> (union false list))
memv : (any (listof any) -> (union false list))
null : empty
null? : (any -> boolean)
pair? : (any -> boolean)
remove : (any (listof any) -> (listof any))
rest : ((cons Y (listof X)) -> (listof X))
reverse : ((listof any) -> list)
second : ((cons Z (cons Y (listof X))) -> Y)
seventh : ((listof Y) -> Y)
sixth : ((listof Y) -> Y)
third : ((cons W (cons Z (cons Y (listof X)))) -> Y)

```

## Posns

```
make-posn : (number number -> posn)
posn : signature
posn-x : (posn -> number)
posn-y : (posn -> number)
posn? : (anything -> boolean)
set-posn-x! : (posn number -> void)
set-posn-y! : (posn number -> void)
```

## Characters

```
char->integer : (char -> integer)
char-alphabetic? : (char -> boolean)
char-ci<=? : (char char char ... -> boolean)
char-ci<? : (char char char ... -> boolean)
char-ci=? : (char char char ... -> boolean)
char-ci>=? : (char char char ... -> boolean)
char-ci>? : (char char char ... -> boolean)
char-downcase : (char -> char)
char-lower-case? : (char -> boolean)
char-numeric? : (char -> boolean)
char-upcase : (char -> char)
char-upper-case? : (char -> boolean)
char-whitespace? : (char -> boolean)
char<=? : (char char char ... -> boolean)
char<? : (char char char ... -> boolean)
char=? : (char char char ... -> boolean)
char>=? : (char char char ... -> boolean)
char>? : (char char char ... -> boolean)
char? : (any -> boolean)
```

## Strings

```
explode : (string -> (listof string))
format : (string any ... -> string)
implode : ((listof string) -> string)
int->string : (integer -> string)
list->string : ((listof char) -> string)
make-string : (nat char -> string)
replicate : (nat string -> string)
string : (char ... -> string)
string->int : (string -> integer)
string->list : (string -> (listof char))
string->number : (string -> (union number false))
string->symbol : (string -> symbol)
string-alphabetic? : (string -> boolean)
string-append : (string ... -> string)
string-ci<=? : (string string string ... -> boolean)
string-ci<? : (string string string ... -> boolean)
string-ci=? : (string string string ... -> boolean)
```

```

string-ci>=? : (string string string ... -> boolean)
string-ci>? : (string string string ... -> boolean)
string-copy : (string -> string)
string-ith : (string nat -> string)
string-length : (string -> nat)
string-lower-case? : (string -> boolean)
string-numeric? : (string -> boolean)
string-ref : (string nat -> char)
string-upper-case? : (string -> boolean)
string-whitespace? : (string -> boolean)
string<=? : (string string string ... -> boolean)
string<? : (string string string ... -> boolean)
string=? : (string string string ... -> boolean)
string>=? : (string string string ... -> boolean)
string>? : (string string string ... -> boolean)
string? : (any -> boolean)
substring : (string nat nat -> string)

```

### Images

```

image=? : (image image -> boolean)
image? : (any -> boolean)

```

### Misc

```

=~ : (real real non-negative-real -> boolean)
current-milliseconds : (-> exact-integer)
eof : eof
eof-object? : (any -> boolean)
eq? : (any any -> boolean)
equal? : (any any -> boolean)
equal~? : (any any non-negative-real -> boolean)
eqv? : (any any -> boolean)
error : (any ... -> void)
exit : (-> void)
force : (delay -> any)
gensym : (-> symbol?)
identity : (any -> any)
promise? : (any -> boolean)
sleep : (-> positive-number void)
struct? : (any -> boolean)
void : (-> void)
void? : (any -> boolean)

```

### Numbers (relaxed conditions)

```

* : (number ... -> number)
+ : (number ... -> number)
- : (number ... -> number)
/ : (number ... -> number)

```

### Higher-Order Functions

```

andmap : ((X -> boolean) (listof X) -> boolean)

```



```

apply : ((X-1 ... X-N -> Y)
         X-1
         ...
         X-i
         (list X-i+1 ... X-N)
         ->
         Y)
argmax : ((X -> real) (listof X) -> X)
argmin : ((X -> real) (listof X) -> X)
build-list : (nat (nat -> X) -> (listof X))
build-string : (nat (nat -> char) -> string)
compose : ((Y-1 -> Z)
          ...
          (Y-N -> Y-N-1)
          (X-1 ... X-N -> Y-N)
          ->
          (X-1 ... X-N -> Z))
filter : ((X -> boolean) (listof X) -> (listof X))
foldl : ((X Y -> Y) Y (listof X) -> Y)
foldr : ((X Y -> Y) Y (listof X) -> Y)
for-each : ((any ... -> any) (listof any) ... -> void)
map : ((X ... -> Z) (listof X) ... -> (listof Z))
memf : ((X -> boolean)
        (listof X)
        ->
        (union false (listof X)))
ormap : ((X -> boolean) (listof X) -> boolean)
procedure? : (any -> boolean)
quicksort : ((listof X) (X X -> boolean) -> (listof X))
sort : ((listof X) (X X -> boolean) -> (listof X))

```

### Reading and Printing

```

display : (any -> void)
newline : (-> void)
pretty-print : (any -> void)
print : (any -> void)
printf : (string any ... -> void)
read : (-> sexp)
with-input-from-file : (string (-> any) -> any)
with-input-from-string : (string (-> any) -> any)
with-output-to-file : (string (-> any) -> any)
with-output-to-string : (string (-> any) -> any)
write : (any -> void)

```

### Vectors

```

build-vector : (nat (nat -> X) -> (vectorof X))
make-vector : (number X -> (vectorof X))

```

```

vector : (X ... -> (vector X ...))
vector-length : ((vector X) -> nat)
vector-ref : ((vector X) nat -> X)
vector-set! : ((vectorof X) nat X -> void)
vector? : (any -> boolean)

```

### Boxes

```

box : (any -> box)
box? : (any -> boolean)
set-box! : (box any -> void)
unbox : (box -> any)

```

### Hash Tables

```

hash-copy : (hash -> hash)
hash-count : (hash -> integer)
hash-eq? : (hash -> boolean)
hash-equal? : (hash -> boolean)
hash-eqv? : (hash -> boolean)
hash-for-each : ((hash X Y) (X Y -> any) -> void)
hash-has-key? : ((hash X Y) X -> boolean)
hash-map : ((hash X Y) (X Y -> A) -> (listof A))
hash-ref : (case->
  ((hash X Y) X -> Y)
  ((hash X Y) X Y -> Y)
  ((hash X Y) X (-> Y) -> Y))
hash-ref! : (case->
  ((hash X Y) X Y -> Y)
  ((hash X Y) X (-> Y) -> Y))
hash-remove : ((hash X Y) X -> (hash X Y))
hash-remove! : ((hash X Y) X -> void)
hash-set : ((hash X Y) X Y -> (hash X Y))
hash-set! : ((hash X Y) X Y -> void)
hash-update : (case->
  ((hash X Y) X (Y -> Y) -> (hash X Y))
  ((hash X Y) X (Y -> Y) Y -> (hash X Y))
  ((hash X Y) X (Y -> Y) (-> Y) -> (hash X Y)))
hash-update! : (case->
  ((hash X Y) X (Y -> Y) -> void)
  ((hash X Y) X (Y -> Y) Y -> void)
  ((hash X Y) X (Y -> Y) (-> Y) -> void))
hash? : (any -> boolean)
make-hash : (case->
  (-> (hash X Y))
  ((listof (list X Y)) -> (hash X Y)))
make-hasheq : (case->
  (-> (hash X Y))
  ((listof (list X Y)) -> (hash X Y)))

```

```

make-hasheqv : (case->
  (-> (hash X Y))
  ((listof (list X Y)) -> (hash X Y)))
make-immutable-hash : (case->
  (-> (hash X Y))
  ((listof (list X Y)) -> (hash X Y)))
make-immutable-hasheq : (case->
  (-> (hash X Y))
  ((listof (list X Y)) -> (hash X Y)))
make-immutable-hasheqv : (case->
  (-> (hash X Y))
  ((listof (list X Y)) -> (hash X Y)))

```

## 5.1 define

---

```

(define (id id ...) expr)
(define id expr)

```

The same as Intermediate with Lambda's `define`, except that a function is allowed to accept zero arguments.

## 5.2 define-struct

---

```

(define-struct structid (fieldid ...))

```

The same as Intermediate's `define-struct`, but defines an additional set of operations:

- `set-structid-fieldid!` : takes an instance of the structure and a value, and changes the instance's field to the given value.

## 5.3 define-datatype

---

```

(define-datatype datatypeid [variantid fieldid ...] ...)

```

A short-hand for defining a group of related structures. A `define-datatype` form

```

(define-datatype datatypeid
  [variantid fieldid ...]
  ...)

```

is equivalent to

```
(define (datatypeid? x)
  (or (variantid? x) ...))
(define-struct variantid (fieldid ...))
...
```

## 5.4 lambda

---

```
(lambda (id ...) expr)
(λ (id ...) expr)
```

The same as Intermediate with Lambda's lambda, except that a function is allowed to accept zero arguments.

## 5.5 Function Calls

---

```
(expr expr ...)
```

A function call in Advanced is the same as an Intermediate with Lambda function call, except that zero arguments are allowed.

---

```
(#%app expr expr ...)
```

A function call can be written with `%app`, though it's practically never written that way.

## 5.6 begin

---

```
(begin expr expr ...)
```

Evaluates the `exprs` in order from left to right. The value of the `begin` expression is the value of the last `expr`.

## 5.7 begin0

---

```
(begin0 expr expr ...)
```

Evaluates the *exprs* in order from left to right. The value of the begin expression is the value of the first *expr*.

## 5.8 set!

---

```
(set! id expr)
```

Evaluates *expr*, and then changes the definition *id* to have *expr*'s value. The *id* must be defined or bound by `letrec`, `let`, or `let*`.

## 5.9 delay

---

```
(delay expr)
```

Produces a “promise” to evaluate *expr*. The *expr* is not evaluated until the promise is forced through the `force` operator; when the promise is forced, the result is recorded, so that any further `force` of the promise always produces the remembered value.

## 5.10 shared

---

```
(shared ([id expr] ...) expr)
```

Like `letrec`, but when an *expr* next to an *id* is a `cons`, `list`, `vector`, quasiquoted expression, or `make-structid` from a `define-struct`, the *expr* can refer directly to any *id*, not just *ids* defined earlier. Thus, `shared` can be used to create cyclic data structures.

## 5.11 let

---

```
(let ([id expr] ...) expr)  
(let id ([id expr] ...) expr)
```

The first form of `let` is the same as Intermediate's `let`.

The second form is equivalent to a `recur` form.

## 5.12 recur

---

```
(recur id ([id expr] ...) expr)
```

A short-hand recursion construct. The first *id* corresponds to the name of the recursive function. The parenthesized *ids* are the function’s arguments, and each corresponding *expr* is a value supplied for that argument in an initial starting call of the function. The last *expr* is the body of the function.

More precisely, a recur form

```
(recur func-id ([arg-id arg-expr] ...)
  body-expr)
```

is equivalent to

```
((local [(define (func-id arg-id ...)
  body-expr)]
  func-id)
  arg-expr ...)
```

## 5.13 case

---

```
(case expr [(choice ...) expr] ... [(choice ...) expr])
```

A case form contains one or more “lines” that are surrounded by parentheses or square brackets. Each line contains a sequence of choices—numbers and names for symbols—and an answer *expr*. The initial *expr* is evaluated, and the resulting value is compared to the choices in each line, where the lines are considered in order. The first line that contains a matching choice provides an answer *expr* whose value is the result of the whole case expression. If none of the lines contains a matching choice, it is an error.

---

```
(case expr [(choice ...) expr] ... [else expr])
```

This form of case is similar to the prior one, except that the final `else` clause is always taken if no prior line contains a choice matching the value of the initial *expr*. In other words, so there is no possibility to “fall off the end” of the case form.

## 5.14 match

---

```
(match expr [pattern expr] ...)
```

A match form contains one or more “lines” that are surrounded by parentheses or square brackets. Each line contains a pattern—a description of a value—and an answer *expr*. The initial *expr* is evaluated, and the resulting value is matched against the pattern in each line, where the lines are considered in order. The first line that contains a matching pattern provides an answer *expr* whose value is the result of the whole match expression. This *expr* may reference identifiers bound in the matching pattern. If none of the lines contains a matching pattern, it is an error.

## 5.15 when and unless

---

```
(when expr expr)
```

The first *expr* (known as the “test” expression) is evaluated. If it evaluates to `true`, the result of the when expression is the result of evaluating the second *expr*, otherwise the result is `(void)` and the second *expr* is not evaluated. If the result of evaluating the test *expr* is neither `true` nor `false`, it is an error.

---

```
(unless expr expr)
```

Like when, but the second *expr* is evaluated when the first *expr* produces `false` instead of `true`.

## 5.16 Primitive Operations

### 5.16.1 Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts

---

```
< : (real real real ... -> boolean)
```

Purpose: to compare real numbers for less-than

---

```
<= : (real real real ... -> boolean)
```

Purpose: to compare real numbers for less-than or equality

---

`= : (number number number ... -> boolean)`

Purpose: to compare numbers for equality

---

`> : (real real real ... -> boolean)`

Purpose: to compare real numbers for greater-than

---

`>= : (real real ... -> boolean)`

Purpose: to compare real numbers for greater-than or equality

---

`abs : (real -> real)`

Purpose: to compute the absolute value of a real number

---

`acos : (number -> number)`

Purpose: to compute the arccosine (inverse of cos) of a number

---

`add1 : (number -> number)`

Purpose: to compute a number one larger than a given number

---

`angle : (number -> real)`

Purpose: to extract the angle from a complex number

---

`asin : (number -> number)`

Purpose: to compute the arcsine (inverse of sin) of a number

---

`atan : (number -> number)`

Purpose: to compute the arctan (inverse of tan) of a number

---

`ceiling : (real -> integer)`

Purpose: to determine the closest integer (exact or inexact) above a real number



---

`complex?` : (any -> boolean)

Purpose: to determine whether some value is complex

---

`conjugate` : (number -> number)

Purpose: to compute the conjugate of a complex number

---

`cos` : (number -> number)

Purpose: to compute the cosine of a number (radians)

---

`cosh` : (number -> number)

Purpose: to compute the hyperbolic cosine of a number

---

`current-seconds` : (-> integer)

Purpose: to compute the current time in seconds elapsed (since a platform-specific starting date)

---

`denominator` : (rat -> integer)

Purpose: to compute the denominator of a rational

---

`e` : real

Purpose: Euler's number

---

`even?` : (integer -> boolean)

Purpose: to determine if some integer (exact or inexact) is even or not

---

`exact->inexact` : (number -> number)

Purpose: to convert an exact number to an inexact one

---

`exact?` : (number -> boolean)

Purpose: to determine whether some number is exact

---

`exp` : (number -> number)

Purpose: to compute e raised to a number

---

`expt` : (number number -> number)

Purpose: to compute the power of the first to the second number

---

`floor` : (real -> integer)

Purpose: to determine the closest integer (exact or inexact) below a real number

---

`gcd` : (integer integer ... -> integer)

Purpose: to compute the greatest common divisor of two integers (exact or inexact)

---

`imag-part` : (number -> real)

Purpose: to extract the imaginary part from a complex number

---

`inexact->exact` : (number -> number)

Purpose: to approximate an inexact number by an exact one

---

`inexact?` : (number -> boolean)

Purpose: to determine whether some number is inexact

---

`integer->char` : (integer -> char)

Purpose: to lookup the character that corresponds to the given integer (exact only!) in the ASCII table (if any)

---

`integer-sqrt` : (number -> integer)

Purpose: to compute the integer (exact or inexact) square root of a number

---

`integer?` : (any -> boolean)

Purpose: to determine whether some value is an integer (exact or inexact)

---

`lcm` : (integer integer ... -> integer)

Purpose: to compute the least common multiple of two integers (exact or inexact)

---

`log` : (number -> number)

Purpose: to compute the base-e logarithm of a number

---

`magnitude` : (number -> real)

Purpose: to determine the magnitude of a complex number

---

`make-polar` : (real real -> number)

Purpose: to create a complex from a magnitude and angle

---

`make-rectangular` : (real real -> number)

Purpose: to create a complex from a real and an imaginary part

---

`max` : (real real ... -> real)

Purpose: to determine the largest number

---

`min` : (real real ... -> real)

Purpose: to determine the smallest number

---

`modulo` : (integer integer -> integer)

Purpose: to find the remainder of the division of the first number by the second; try (modulo 4 3) (modulo 4 -3)

---

`negative?` : (number -> boolean)

Purpose: to determine if some value is strictly smaller than zero

---

`number->string` : (number -> string)

Purpose: to convert a number to a string

---

`number?` : (any -> boolean)

Purpose: to determine whether some value is a number

---

`numerator` : (rat -> integer)

Purpose: to compute the numerator of a rational

---

`odd?` : (integer -> boolean)

Purpose: to determine if some integer (exact or inexact) is odd or not

---

`pi` : real

Purpose: the ratio of a circle's circumference to its diameter

---

`positive?` : (number -> boolean)

Purpose: to determine if some value is strictly larger than zero

---

`quotient` : (integer integer -> integer)

Purpose: to divide the first integer (exact or inexact) into the second; try (quotient 3 4) and (quotient 4 3)

---

`random` : (case->  
    (integer -> integer)  
    (-> (and/c real inexact? (>/c 0) (</c 1))))

Purpose: to generate a random natural number less than some given integer, or to generate a random inexact number between 0.0 and 1.0 exclusive

---

`rational?` : (any -> boolean)

Purpose: to determine whether some value is a rational number

---

`real-part` : (number -> real)

Purpose: to extract the real part from a complex number

---

---

`real?` : (any -> boolean)

Purpose: to determine whether some value is a real number

---

`remainder` : (integer integer -> integer)

Purpose: to determine the remainder of dividing the first by the second integer (exact or inexact)

---

`round` : (real -> integer)

Purpose: to round a real number to an integer (rounds to even to break ties)

---

`sgn` : (real -> (union 1 1.0 0 0.0 -1 -1.0))

Purpose: to compute the sign of a real number

---

`sin` : (number -> number)

Purpose: to compute the sine of a number (radians)

---

`sinh` : (number -> number)

Purpose: to compute the hyperbolic sine of a number

---

`sqr` : (number -> number)

Purpose: to compute the square of a number

---

`sqrt` : (number -> number)

Purpose: to compute the square root of a number

---

`sub1` : (number -> number)

Purpose: to compute a number one smaller than a given number

---

`tan` : (number -> number)

Purpose: to compute the tangent of a number (radians)

---

`zero?` : (number -> boolean)

Purpose: to determine if some value is zero or not

### 5.16.2 Booleans

---

`boolean=?` : (boolean boolean -> boolean)

Purpose: to determine whether two booleans are equal

---

`boolean?` : (any -> boolean)

Purpose: to determine whether some value is a boolean

---

`false?` : (any -> boolean)

Purpose: to determine whether a value is false

---

`not` : (boolean -> boolean)

Purpose: to compute the negation of a boolean value

### 5.16.3 Symbols

---

`symbol->string` : (symbol -> string)

Purpose: to convert a symbol to a string

---

`symbol=?` : (symbol symbol -> boolean)

Purpose: to determine whether two symbols are equal

---

`symbol?` : (any -> boolean)

Purpose: to determine whether some value is a symbol

#### 5.16.4 Lists

---

`append` : ((listof any) ... -> (listof any))

Purpose: to create a single list from several

---

`assoc` : (any (listof any) -> (listof any) or false)

Purpose: to produce the first element on the list whose first is equal? to v; otherwise it produces false

---

`assq` : (X  
  (listof (cons X Y))  
  ->  
  (union false (cons X Y)))

Purpose: to determine whether some item is the first item of a pair in a list of pairs

---

`caaar` : ((cons  
  (cons (cons W (listof Z)) (listof Y))  
  (listof X))  
  ->  
  W)

Purpose: to select the first item of the first list in the first list of a list

---

`caadr` : ((cons  
  (cons (cons W (listof Z)) (listof Y))  
  (listof X))  
  ->  
  (listof Z))

Purpose: to select the rest of the first list in the first list of a list

---

`caar` : ((cons (cons Z (listof Y)) (listof X)) -> Z)

Purpose: to select the first item of the first list in a list

---

`cadar` : ((cons (cons W (cons Z (listof Y))) (listof X))  
  ->  
  Z)

Purpose: to select the second item of the first list of a list

---

```
caddr : ((listof Y) -> Y)
```

Purpose: to select the fourth item of a non-empty list

---

```
caddr : ((cons W (cons Z (cons Y (listof X)))) -> Y)
```

Purpose: to select the third item of a non-empty list

---

```
cadr : ((cons Z (cons Y (listof X))) -> Y)
```

Purpose: to select the second item of a non-empty list

---

```
car : ((cons Y (listof X)) -> Y)
```

Purpose: to select the first item of a non-empty list

---

```
cdaar : ((cons  
          (cons (cons W (listof Z)) (listof Y))  
          (listof X))  
         ->  
         (listof Z))
```

Purpose: to select the rest of the first list in the first list of a list

---

```
cdadr : ((cons W (cons (cons Z (listof Y)) (listof X)))  
        ->  
        (listof Y))
```

Purpose: to select the rest of the first list in the rest of a list

---

```
cdar : ((cons (cons Z (listof Y)) (listof X))  
        ->  
        (listof Y))
```

Purpose: to select the rest of a non-empty list in a list

---

```
cddar : ((cons (cons W (cons Z (listof Y))) (listof X))  
        ->  
        (listof Y))
```



Purpose: to select the rest of the rest of the first list of a list

---

```
cdddr : ((cons W (cons Z (cons Y (listof X))))
        ->
        (listof X))
```

Purpose: to select the rest of the rest of the rest of a list

---

```
cddr : ((cons Z (cons Y (listof X))) -> (listof X))
```

Purpose: to select the rest of the rest of a list

---

```
cdr : ((cons Y (listof X)) -> (listof X))
```

Purpose: to select the rest of a non-empty list

---

```
cons : (X (listof X) -> (listof X))
```

Purpose: to construct a list

---

```
cons? : (any -> boolean)
```

Purpose: to determine whether some value is a constructed list

---

```
eighth : ((listof Y) -> Y)
```

Purpose: to select the eighth item of a non-empty list

---

```
empty? : (any -> boolean)
```

Purpose: to determine whether some value is the empty list

---

```
fifth : ((listof Y) -> Y)
```

Purpose: to select the fifth item of a non-empty list

---

```
first : ((cons Y (listof X)) -> Y)
```

Purpose: to select the first item of a non-empty list

---

`fourth` : ((listof Y) -> Y)

Purpose: to select the fourth item of a non-empty list

---

`length` : ((listof any) -> number)

Purpose: to compute the number of items on a list

---

`list` : (any ... -> (listof any))

Purpose: to construct a list of its arguments

---

`list*` : (any ... (listof any) -> (listof any))

Purpose: to construct a list by adding multiple items to a list

---

`list-ref` : ((listof X) natural-number -> X)

Purpose: to extract the indexed item from the list

---

`list?` : (any -> boolean)

Purpose: to determine whether some value is a list

---

`make-list` : (natural-number any -> (listof any))

Purpose: (make-list k x) constructs a list of k copies of x

---

`member` : (any (listof any) -> boolean)

Purpose: to determine whether some value is on the list (comparing values with equal?)

---

`member?` : (any (listof any) -> boolean)

Purpose: to determine whether some value is on the list (comparing values with equal?)

---

`memq` : (any (listof any) -> (union false list))

Purpose: to determine whether some value is on some list if so, it produces the suffix of the list that starts with x if not, it produces false. (It compares values with the eq? predicate.)

---

`memv` : (any (listof any) -> (union false list))

Purpose: to determine whether some value is on the list if so, it produces the suffix of the list that starts with x if not, it produces false. (it compares values with the `eqv?` predicate.)

---

`null` : empty

Purpose: the empty list

---

`null?` : (any -> boolean)

Purpose: to determine whether some value is the empty list

---

`pair?` : (any -> boolean)

Purpose: to determine whether some value is a constructed list

---

`remove` : (any (listof any) -> (listof any))

Purpose: to construct a list like the given one with the first occurrence of the given item removed (comparing values with `equal?`)

---

`rest` : ((cons Y (listof X)) -> (listof X))

Purpose: to select the rest of a non-empty list

---

`reverse` : ((listof any) -> list)

Purpose: to create a reversed version of a list

---

`second` : ((cons Z (cons Y (listof X))) -> Y)

Purpose: to select the second item of a non-empty list

---

`seventh` : ((listof Y) -> Y)

Purpose: to select the seventh item of a non-empty list

---

`sixth` : ((listof Y) -> Y)

Purpose: to select the sixth item of a non-empty list

---

```
third : ((cons W (cons Z (cons Y (listof X)))) -> Y)
```

Purpose: to select the third item of a non-empty list

### 5.16.5 Posns

---

```
make-posn : (number number -> posn)
```

Purpose: to construct a posn

---

```
posn : signature
```

Purpose: signature for posns

---

```
posn-x : (posn -> number)
```

Purpose: to extract the x component of a posn

---

```
posn-y : (posn -> number)
```

Purpose: to extract the y component of a posn

---

```
posn? : (anything -> boolean)
```

Purpose: to determine if its input is a posn

---

```
set-posn-x! : (posn number -> void)
```

Purpose: to update the x component of a posn

---

```
set-posn-y! : (posn number -> void)
```

Purpose: to update the x component of a posn

### 5.16.6 Characters

---

`char->integer` : (char -> integer)

Purpose: to lookup the number that corresponds to the given character in the ASCII table (if any)

---

`char-alphabetic?` : (char -> boolean)

Purpose: to determine whether a character represents an alphabetic character

---

`char-ci<=?` : (char char char ... -> boolean)

Purpose: to determine whether a character precedes another (or is equal to it) in a case-insensitive manner

---

`char-ci<` : (char char char ... -> boolean)

Purpose: to determine whether a character precedes another in a case-insensitive manner

---

`char-ci=?` : (char char char ... -> boolean)

Purpose: to determine whether two characters are equal in a case-insensitive manner

---

`char-ci>=?` : (char char char ... -> boolean)

Purpose: to determine whether a character succeeds another (or is equal to it) in a case-insensitive manner

---

`char-ci>` : (char char char ... -> boolean)

Purpose: to determine whether a character succeeds another in a case-insensitive manner

---

`char-downcase` : (char -> char)

Purpose: to determine the equivalent lower-case character

---

`char-lower-case?` : (char -> boolean)

Purpose: to determine whether a character is a lower-case character

---

`char-numeric?` : (char -> boolean)

Purpose: to determine whether a character represents a digit

---

`char-upcase` : (char -> char)

Purpose: to determine the equivalent upper-case character

---

`char-upper-case?` : (char -> boolean)

Purpose: to determine whether a character is an upper-case character

---

`char-whitespace?` : (char -> boolean)

Purpose: to determine whether a character represents space

---

`char<=?` : (char char char ... -> boolean)

Purpose: to determine whether a character precedes another (or is equal to it)

---

`char<?` : (char char char ... -> boolean)

Purpose: to determine whether a character precedes another

---

`char=?` : (char char char ... -> boolean)

Purpose: to determine whether two characters are equal

---

`char>=?` : (char char char ... -> boolean)

Purpose: to determine whether a character succeeds another (or is equal to it)

---

`char>?` : (char char char ... -> boolean)

Purpose: to determine whether a character succeeds another

---

`char?` : (any -> boolean)

Purpose: to determine whether a value is a character

### 5.16.7 Strings

---

`explode` : (string -> (listof string))

Purpose: to translate a string into a list of 1-letter strings

---

`format` : (string any ... -> string)

Purpose: to format a string, possibly embedding values

---

`implode` : ((listof string) -> string)

Purpose: to concatenate the list of 1-letter strings into one string

---

`int->string` : (integer -> string)

Purpose: to convert an integer in [0,55295] or [57344 1114111] to a 1-letter string

---

`list->string` : ((listof char) -> string)

Purpose: to convert a s list of characters into a string

---

`make-string` : (nat char -> string)

Purpose: to produce a string of given length from a single given character

---

`replicate` : (nat string -> string)

Purpose: to replicate the given string

---

`string` : (char ... -> string)

Purpose: (string c1 c2 ...) builds a string

---

`string->int` : (string -> integer)

Purpose: to convert a 1-letter string to an integer in [0,55295] or [57344, 1114111]

---

`string->list` : (string -> (listof char))

Purpose: to convert a string into a list of characters

---

```
string->number : (string -> (union number false))
```

Purpose: to convert a string into a number, produce false if impossible

---

```
string->symbol : (string -> symbol)
```

Purpose: to convert a string into a symbol

---

```
string-alphabetic? : (string -> boolean)
```

Purpose: to determine whether all 'letters' in the string are alphabetic

---

```
string-append : (string ... -> string)
```

Purpose: to juxtapose the characters of several strings

---

```
string-ci<=? : (string string string ... -> boolean)
```

Purpose: to determine whether one string alphabetically precedes another (or is equal to it) in a case-insensitive manner

---

```
string-ci<? : (string string string ... -> boolean)
```

Purpose: to determine whether one string alphabetically precedes another in a case-insensitive manner

---

```
string-ci=? : (string string string ... -> boolean)
```

Purpose: to compare two strings character-wise in a case-insensitive manner

---

```
string-ci>=? : (string string string ... -> boolean)
```

Purpose: to determine whether one string alphabetically succeeds another (or is equal to it) in a case-insensitive manner

---

```
string-ci>? : (string string string ... -> boolean)
```

Purpose: to determine whether one string alphabetically succeeds another in a case-insensitive manner



---

`string-copy` : (string -> string)

Purpose: to copy a string

---

`string-ith` : (string nat -> string)

Purpose: to extract the ith 1-letter substring from the given one

---

`string-length` : (string -> nat)

Purpose: to determine the length of a string

---

`string-lower-case?` : (string -> boolean)

Purpose: to determine whether all 'letters' in the string are lower case

---

`string-numeric?` : (string -> boolean)

Purpose: to determine whether all 'letters' in the string are numeric

---

`string-ref` : (string nat -> char)

Purpose: to extract the i-th character from a string

---

`string-upper-case?` : (string -> boolean)

Purpose: to determine whether all 'letters' in the string are upper case

---

`string-whitespace?` : (string -> boolean)

Purpose: to determine whether all 'letters' in the string are white space

---

`string<=?` : (string string string ... -> boolean)

Purpose: to determine whether one string alphabetically precedes another (or is equal to it)

---

`string<?` : (string string string ... -> boolean)

Purpose: to determine whether one string alphabetically precedes another

---

`string=?` : (string string string ... -> boolean)

Purpose: to compare two strings character-wise

---

`string>=?` : (string string string ... -> boolean)

Purpose: to determine whether one string alphabetically succeeds another (or is equal to it)

---

`string>?` : (string string string ... -> boolean)

Purpose: to determine whether one string alphabetically succeeds another

---

`string?` : (any -> boolean)

Purpose: to determine whether a value is a string

---

`substring` : (string nat nat -> string)

Purpose: to extract the substring starting at a 0-based index up to the second 0-based index (exclusive)

### 5.16.8 Images

---

`image=?` : (image image -> boolean)

Purpose: to determine whether two images are equal

---

`image?` : (any -> boolean)

Purpose: to determine whether a value is an image

### 5.16.9 Misc

---

`=~` : (real real non-negative-real -> boolean)

Purpose: to check whether two real numbers are within some amount (the third argument) of either other

---

`current-milliseconds` : (`-> exact-integer`)

Purpose: to return the current “time” in fixnum milliseconds (possibly negative)

---

`eof` : eof

Purpose: the end-of-file value

---

`eof-object?` : (`any -> boolean`)

Purpose: to determine whether some value is the end-of-file value

---

`eq?` : (`any any -> boolean`)

Purpose: to determine whether two values are equivalent from the computer’s perspective (intensional)

---

`equal?` : (`any any -> boolean`)

Purpose: to determine whether two values are structurally equal where basic values are compared with the `eqv?` predicate

---

`equal~?` : (`any any non-negative-real -> boolean`)

Purpose: to compare like `equal?` on the first two arguments, except using `=~` in the case of real numbers

---

`eqv?` : (`any any -> boolean`)

Purpose: to determine whether two values are equivalent from the perspective of all functions that can be applied to it (extensional)

---

`error` : (`any ... -> void`)

Purpose: to signal an error, combining the given values into an error message.

If any of the values’ printed representations is too long, it is truncated and “...” is put into the string. If the first value is a symbol, it is treated specially; it is suffixed with a colon and a space (the intention is that the symbol is the name of the function signalling the error).

---

`exit` : (-> void)

Purpose: to exit the running program

---

`force` : (delay -> any)

Purpose: to find the delayed value; see also delay

---

`gensym` : (-> symbol?)

Purpose: to generate a new symbol, different from all symbols in the program

---

`identity` : (any -> any)

Purpose: to return the argument unchanged

---

`promise?` : (any -> boolean)

Purpose: to determine if a value is delayed

---

`sleep` : (-> positive-number void)

Purpose: to cause the program to sleep for the given number of seconds

---

`struct?` : (any -> boolean)

Purpose: to determine whether some value is a structure

---

`void` : (-> void)

Purpose: produces a void value

---

`void?` : (any -> boolean)

Purpose: to determine if a value is void

### 5.16.10 Numbers (relaxed conditions)

---

`* : (number ... -> number)`

Purpose: to multiply all given numbers

---

`+ : (number ... -> number)`

Purpose: to add all given numbers

---

`- : (number ... -> number)`

Purpose: to subtract from the first all remaining numbers

---

`/ : (number ... -> number)`

Purpose: to divide the first by all remaining numbers

### 5.16.11 Higher-Order Functions

---

`andmap : ((X -> boolean) (listof X) -> boolean)`

Purpose:  $(\text{andmap } p \text{ (list } x-1 \dots x-n)) = (\text{and } (p \ x-1) \dots (p \ x-n))$

---

`apply : ((X-1 ... X-N -> Y)  
          X-1  
          ...  
          X-i  
          (list X-i+1 ... X-N)  
          ->  
          Y)`

Purpose: to apply a function using items from a list as the arguments

---

`argmax : ((X -> real) (listof X) -> X)`

Purpose: to find the (first) element of the list that maximizes the output of the function

---

`argmin : ((X -> real) (listof X) -> X)`

Purpose: to find the (first) element of the list that minimizes the output of the function

---

```
build-list : (nat (nat -> X) -> (listof X))
```

Purpose: (build-list n f) = (list (f 0) ... (f (- n 1)))

---

```
build-string : (nat (nat -> char) -> string)
```

Purpose: (build-string n f) = (string (f 0) ... (f (- n 1)))

---

```
compose : ((Y-1 -> Z)
           ...
           (Y-N -> Y-N-1)
           (X-1 ... X-N -> Y-N)
           ->
           (X-1 ... X-N -> Z))
```

Purpose: to compose a sequence of procedures into a single procedure

---

```
filter : ((X -> boolean) (listof X) -> (listof X))
```

Purpose: to construct a list from all those items on a list for which the predicate holds

---

```
foldl : ((X Y -> Y) Y (listof X) -> Y)
```

Purpose: (foldl f base (list x-1 ... x-n)) = (f x-n ... (f x-1 base))

---

```
foldr : ((X Y -> Y) Y (listof X) -> Y)
```

Purpose: (foldr f base (list x-1 ... x-n)) = (f x-1 ... (f x-n base))

---

```
for-each : ((any ... -> any) (listof any) ... -> void)
```

Purpose: to apply a function to each item on one or more lists for effect only

---

```
map : ((X ... -> Z) (listof X) ... -> (listof Z))
```

Purpose: to construct a new list by applying a function to each item on one or more existing lists

---

```
memf : ((X -> boolean)
        (listof X)
        ->
        (union false (listof X)))
```

Purpose: to determine whether the first argument produces true for some value in the second argument

---

```
ormap : ((X -> boolean) (listof X) -> boolean)
```

Purpose: (ormap p (list x-1 ... x-n)) = (or (p x-1) ... (p x-n))

---

```
procedure? : (any -> boolean)
```

Purpose: to determine if a value is a procedure

---

```
quicksort : ((listof X) (X X -> boolean) -> (listof X))
```

Purpose: to construct a list from all items on a list in an order according to a predicate

---

```
sort : ((listof X) (X X -> boolean) -> (listof X))
```

Purpose: to construct a list from all items on a list in an order according to a predicate

### 5.16.12 Reading and Printing

---

```
display : (any -> void)
```

Purpose: to print the argument to stdout (without quotes on symbols and strings, etc.)

---

```
newline : (-> void)
```

Purpose: to print a newline to stdout

---

```
pretty-print : (any -> void)
```

Purpose: like write, but with standard newlines and indentation

---

```
print : (any -> void)
```

Purpose: to print the argument as a value to stdout

---

`printf` : (string any ... -> void)

Purpose: to format the rest of the arguments according to the first argument and print it to stdout

---

`read` : (-> sexp)

Purpose: to read input from the user

---

`with-input-from-file` : (string (-> any) -> any)

Purpose: to open the named input file and to extract all input from there

---

`with-input-from-string` : (string (-> any) -> any)

Purpose: to turn the given string into input for read\* operations

---

`with-output-to-file` : (string (-> any) -> any)

Purpose: to open the named output file and to put all output there

---

`with-output-to-string` : (string (-> any) -> any)

Purpose: to produce a string from all write/display/print operations

---

`write` : (any -> void)

Purpose: to print the argument to stdout (in a traditional style that is somewhere between print and display)

### 5.16.13 Vectors

---

`build-vector` : (nat (nat -> X) -> (vectorof X))

Purpose: to construct a vector

---

`make-vector` : (number X -> (vectorof X))



Purpose: to construct a vector

---

```
vector : (X ... -> (vector X ...))
```

Purpose: to construct a vector

---

```
vector-length : ((vector X) -> nat)
```

Purpose: to determine the length of a vector

---

```
vector-ref : ((vector X) nat -> X)
```

Purpose: to extract an element from a vector

---

```
vector-set! : ((vectorof X) nat X -> void)
```

Purpose: to update a vector

---

```
vector? : (any -> boolean)
```

Purpose: to determine if a value is a vector

#### 5.16.14 Boxes

---

```
box : (any -> box)
```

Purpose: to construct a box

---

```
box? : (any -> boolean)
```

Purpose: to determine if a value is a box

---

```
set-box! : (box any -> void)
```

Purpose: to update a box

---

```
unbox : (box -> any)
```

Purpose: to extract the boxed value

### 5.16.15 Hash Tables

---

`hash-copy` : (hash -> hash)

Purpose: to copy a hash table

---

`hash-count` : (hash -> integer)

Purpose: to determine the number of keys mapped by a hash table

---

`hash-eq?` : (hash -> boolean)

Purpose: to determine if a hash table uses eq? for comparisons

---

`hash-equal?` : (hash -> boolean)

Purpose: to determine if a hash table uses equal? for comparisons

---

`hash-eqv?` : (hash -> boolean)

Purpose: to determine if a hash table uses eqv? for comparisons

---

`hash-for-each` : ((hash X Y) (X Y -> any) -> void)

Purpose: to apply a function to each mapping of a hash table for effect only

---

`hash-has-key?` : ((hash X Y) X -> boolean)

Purpose: to determine if a key is associated with a value in a hash table

---

`hash-map` : ((hash X Y) (X Y -> A) -> (listof A))

Purpose: to construct a new list by applying a function to each mapping of a hash table

---

`hash-ref` : (case->  
    ((hash X Y) X -> Y)  
    ((hash X Y) X Y -> Y)  
    ((hash X Y) X (-> Y) -> Y))

Purpose: to extract the value associated with a key from a hash table; the three argument

case allows a default value or default value computation

---

```
hash-ref! : (case->
             ((hash X Y) X Y -> Y)
             ((hash X Y) X (-> Y) -> Y))
```

Purpose: to extract the value associated with a key from a mutable hash table; if the key does not have an mapping, the third argument is used as the value (or used to compute the value) and is added to the hash table associated with the key

---

```
hash-remove : ((hash X Y) X -> (hash X Y))
```

Purpose: to construct an immutable hash table with one less mapping than an existing immutable hash table

---

```
hash-remove! : ((hash X Y) X -> void)
```

Purpose: to remove an mapping from a mutable hash table

---

```
hash-set : ((hash X Y) X Y -> (hash X Y))
```

Purpose: to construct an immutable hash table with one new mapping from an existing immutable hash table

---

```
hash-set! : ((hash X Y) X Y -> void)
```

Purpose: to update a mutable hash table with a new mapping

---

```
hash-update : (case->
              ((hash X Y) X (Y -> Y) -> (hash X Y))
              ((hash X Y) X (Y -> Y) Y -> (hash X Y))
              ((hash X Y) X (Y -> Y) (-> Y) -> (hash X Y)))
```

Purpose: to compose hash-ref and hash-set to update an existing mapping; the third argument is used to compute the new mapping value; the fourth argument is used as the third argument to hash-ref

---

```
hash-update! : (case->
               ((hash X Y) X (Y -> Y) -> void)
               ((hash X Y) X (Y -> Y) Y -> void)
               ((hash X Y) X (Y -> Y) (-> Y) -> void))
```

Purpose: to compose hash-ref and hash-set! to update an existing mapping; the third argument is used to compute the new mapping value; the fourth argument is used as the third argument to hash-ref

---

`hash?` : (any -> boolean)

Purpose: to determine if a value is a hash table

---

`make-hash` : (case->  
 (-> (hash X Y))  
 ((listof (list X Y)) -> (hash X Y)))

Purpose: to construct a mutable hash table from an optional list of mappings that uses equal? for comparisons

---

`make-hasheq` : (case->  
 (-> (hash X Y))  
 ((listof (list X Y)) -> (hash X Y)))

Purpose: to construct a mutable hash table from an optional list of mappings that uses eq? for comparisons

---

`make-hasheqv` : (case->  
 (-> (hash X Y))  
 ((listof (list X Y)) -> (hash X Y)))

Purpose: to construct a mutable hash table from an optional list of mappings that uses eqv? for comparisons

---

`make-immutable-hash` : (case->  
 (-> (hash X Y))  
 ((listof (list X Y)) -> (hash X Y)))

Purpose: to construct an immutable hash table from an optional list of mappings that uses equal? for comparisons

---

`make-immutable-hasheq` : (case->  
 (-> (hash X Y))  
 ((listof (list X Y)) -> (hash X Y)))

Purpose: to construct an immutable hash table from an optional list of mappings that uses eq? for comparisons

---

```
make-immutable-hasheqv : (case->
  (-> (hash X Y))
  ((listof (list X Y)) -> (hash X Y)))
```

Purpose: to construct an immutable hash table from an optional list of mappings that uses `eqv?` for comparisons

## 5.17 Unchanged Forms

---

```
(local [definition ...] expr)
(letrec ([id expr-for-let] ...) expr)
(let* ([id expr-for-let] ...) expr)
```

The same as Intermediate's `local`, `letrec`, and `let*`.

---

```
(cond [expr expr] ... [expr expr])
else
```

The same as Beginning's `cond`, except that `else` can be used with `case`.

---

```
(if expr expr expr)
```

The same as Beginning's `if`.

---

```
(and expr expr expr ...)
(or expr expr expr ...)
```

The same as Beginning's `and` and `or`.

---

```
(time expr)
```

The same as Intermediate's `time`.

---

```
(check-expect expr expr)
(check-within expr expr expr)
(check-error expr expr)
(check-error expr)
(check-member-of expr expr expr ...)
(check-range expr expr expr)
```

The same as Beginning's `check-expect`, etc.

---

```
empty : empty?  
true  : boolean?  
false : boolean?
```

Constants for the empty list, true, and false.

---

```
(require module-path)
```

The same as Beginning's `require`.

## Index

`##app`, 112  
`##app`, 79  
`##app`, 148  
`##app`, 14  
`*`, 47  
`*`, 173  
`*`, 99  
`*`, 132  
`*`, 19  
`+`, 173  
`+`, 19  
`+`, 132  
`+`, 99  
`+`, 48  
`-`, 19  
`-`, 132  
`-`, 100  
`-`, 48  
`-`, 173  
`/`, 19  
`/`, 173  
`/`, 48  
`/`, 100  
`/`, 132  
`<`, 19  
`<`, 48  
`<`, 79  
`<`, 112  
`<`, 151  
`<=`, 19  
`<=`, 112  
`<=`, 80  
`<=`, 48  
`<=`, 151  
`=`, 112  
`=`, 19  
`=`, 152  
`=`, 48  
`=`, 80  
`=~`, 131

`=~`, 38  
`=~`, 67  
`=~`, 170  
`=~`, 98  
`>`, 80  
`>`, 48  
`>`, 19  
`>`, 112  
`>`, 152  
`>=`, 19  
`>=`, 152  
`>=`, 80  
`>=`, 48  
`>=`, 112  
`abs`, 48  
`abs`, 20  
`abs`, 113  
`abs`, 80  
`abs`, 152  
`acos`, 80  
`acos`, 113  
`acos`, 152  
`acos`, 48  
`acos`, 20  
`add1`, 113  
`add1`, 20  
`add1`, 152  
`add1`, 49  
`add1`, 80  
Advanced Student, 137  
`and`, 16  
`and`, 102  
`and`, 135  
`and`, 69  
`and`, 16  
`and`, 181  
`andmap`, 100  
`andmap`, 133  
`andmap`, 173  
`angle`, 49  
`angle`, 80  
`angle`, 20

angle, 113  
 angle, 152  
 append, 87  
 append, 119  
 append, 55  
 append, 26  
 append, 159  
 apply, 173  
 apply, 100  
 apply, 133  
 argmax, 100  
 argmax, 173  
 argmax, 133  
 argmin, 133  
 argmin, 100  
 argmin, 173  
 asin, 49  
 asin, 20  
 asin, 152  
 asin, 80  
 asin, 113  
 assoc, 159  
 assq, 159  
 assq, 119  
 assq, 87  
 assq, 55  
 assq, 27  
 atan, 152  
 atan, 49  
 atan, 20  
 atan, 113  
 atan, 80  
 begin, 148  
 begin, 148  
 begin0, 148  
 begin0, 148  
 Beginning Student, 7  
 Beginning Student with List Abbreviations,  
 40  
 boolean=?, 54  
 boolean=?, 158  
 boolean=?, 86  
 boolean=?, 118  
 boolean=?, 25  
 boolean?, 54  
 boolean?, 119  
 boolean?, 158  
 boolean?, 86  
 boolean?, 26  
 Booleans, 158  
 Booleans, 54  
 Booleans, 25  
 Booleans, 118  
 Booleans, 86  
 box, 177  
 box?, 177  
 Boxes, 177  
 build-list, 100  
 build-list, 174  
 build-list, 133  
 build-string, 174  
 build-string, 100  
 build-string, 133  
 build-vector, 176  
 caaar, 120  
 caaar, 27  
 caaar, 159  
 caaar, 56  
 caaar, 87  
 caadr, 159  
 caadr, 120  
 caadr, 87  
 caadr, 27  
 caadr, 56  
 caar, 87  
 caar, 159  
 caar, 27  
 caar, 120  
 caar, 56  
 cadar, 120  
 cadar, 87  
 cadar, 27  
 cadar, 56  
 cadar, 159



caddr, 120  
caddr, 56  
caddr, 27  
caddr, 87  
caddr, 160  
caddr, 88  
caddr, 56  
caddr, 27  
caddr, 160  
caddr, 120  
cadr, 88  
cadr, 56  
cadr, 120  
cadr, 160  
cadr, 28  
car, 56  
car, 160  
car, 28  
car, 88  
car, 120  
case, 150  
case, 150  
cdaar, 160  
cdaar, 121  
cdaar, 57  
cdaar, 28  
cdaar, 88  
cdadr, 88  
cdadr, 160  
cdadr, 28  
cdadr, 121  
cdadr, 57  
cdar, 160  
cdar, 121  
cdar, 28  
cdar, 57  
cdar, 88  
cddar, 57  
cddar, 88  
cddar, 28  
cddar, 160  
cddar, 121  
cddr, 28  
cddr, 121  
cddr, 89  
cddr, 161  
cddr, 57  
cddr, 57  
cddr, 89  
cddr, 28  
cddr, 121  
cddr, 161  
cdr, 89  
cdr, 121  
cdr, 161  
cdr, 29  
cdr, 57  
ceiling, 20  
ceiling, 152  
ceiling, 113  
ceiling, 81  
ceiling, 49  
char->integer, 125  
char->integer, 32  
char->integer, 165  
char->integer, 92  
char->integer, 61  
char-alphabetic?, 92  
char-alphabetic?, 165  
char-alphabetic?, 125  
char-alphabetic?, 61  
char-alphabetic?, 32  
char-ci<=?, 61  
char-ci<=?, 92  
char-ci<=?, 32  
char-ci<=?, 125  
char-ci<=?, 165  
char-ci<?, 165  
char-ci<?, 32  
char-ci<?, 61  
char-ci<?, 125  
char-ci<?, 92  
char-ci=?, 165  
char-ci=?, 125

[char-ci=?, 61](#)  
[char-ci=?, 32](#)  
[char-ci=?, 93](#)  
[char-ci>=?, 61](#)  
[char-ci>=?, 33](#)  
[char-ci>=?, 93](#)  
[char-ci>=?, 125](#)  
[char-ci>=?, 165](#)  
[char-ci>?, 125](#)  
[char-ci>?, 165](#)  
[char-ci>?, 33](#)  
[char-ci>?, 93](#)  
[char-ci>?, 61](#)  
[char-downcase, 126](#)  
[char-downcase, 165](#)  
[char-downcase, 33](#)  
[char-downcase, 62](#)  
[char-downcase, 93](#)  
[char-lower-case?, 33](#)  
[char-lower-case?, 126](#)  
[char-lower-case?, 62](#)  
[char-lower-case?, 93](#)  
[char-lower-case?, 165](#)  
[char-numeric?, 33](#)  
[char-numeric?, 93](#)  
[char-numeric?, 166](#)  
[char-numeric?, 126](#)  
[char-numeric?, 62](#)  
[char-upcase, 93](#)  
[char-upcase, 62](#)  
[char-upcase, 166](#)  
[char-upcase, 126](#)  
[char-upcase, 33](#)  
[char-upper-case?, 126](#)  
[char-upper-case?, 62](#)  
[char-upper-case?, 93](#)  
[char-upper-case?, 166](#)  
[char-upper-case?, 33](#)  
[char-whitespace?, 33](#)  
[char-whitespace?, 62](#)  
[char-whitespace?, 166](#)  
[char-whitespace?, 126](#)  
[char-whitespace?, 93](#)  
[char<=?, 62](#)  
[char<=?, 93](#)  
[char<=?, 126](#)  
[char<=?, 33](#)  
[char<=?, 166](#)  
[char<?, 166](#)  
[char<?, 62](#)  
[char<?, 33](#)  
[char<?, 126](#)  
[char<?, 94](#)  
[char=?, 94](#)  
[char=?, 34](#)  
[char=?, 166](#)  
[char=?, 62](#)  
[char=?, 126](#)  
[char>=?, 166](#)  
[char>=?, 94](#)  
[char>=?, 62](#)  
[char>=?, 126](#)  
[char>=?, 34](#)  
[char>?, 94](#)  
[char>?, 63](#)  
[char>?, 127](#)  
[char>?, 34](#)  
[char>?, 166](#)  
[char?, 63](#)  
[char?, 94](#)  
[char?, 127](#)  
[char?, 34](#)  
[char?, 166](#)  
[Characters, 165](#)  
[Characters, 61](#)  
[Characters, 32](#)  
[Characters, 125](#)  
[Characters, 92](#)  
[check-error, 135](#)  
[check-error, 69](#)  
[check-error, 102](#)  
[check-error, 16](#)  
[check-error, 181](#)  
[check-expect, 181](#)

check-expect, 135  
 check-expect, 102  
 check-expect, 69  
 check-expect, 16  
 check-member-of, 69  
 check-member-of, 181  
 check-member-of, 16  
 check-member-of, 102  
 check-member-of, 136  
 check-range, 69  
 check-range, 102  
 check-range, 17  
 check-range, 181  
 check-range, 136  
 check-within, 181  
 check-within, 135  
 check-within, 69  
 check-within, 102  
 check-within, 16  
 complex?, 81  
 complex?, 113  
 complex?, 49  
 complex?, 20  
 complex?, 153  
 compose, 133  
 compose, 101  
 compose, 174  
 cond, 15  
 cond, 15  
 cond, 102  
 cond, 135  
 cond, 68  
 cond, 181  
 conjugate, 20  
 conjugate, 113  
 conjugate, 153  
 conjugate, 49  
 conjugate, 81  
 cons, 29  
 cons, 89  
 cons, 161  
 cons, 57  
 cons, 121  
 cons?, 122  
 cons?, 58  
 cons?, 89  
 cons?, 29  
 cons?, 161  
 cos, 20  
 cos, 153  
 cos, 113  
 cos, 49  
 cos, 81  
 cosh, 153  
 cosh, 49  
 cosh, 21  
 cosh, 114  
 cosh, 81  
 current-milliseconds, 171  
 current-seconds, 114  
 current-seconds, 21  
 current-seconds, 49  
 current-seconds, 81  
 current-seconds, 153  
 define, 147  
 define, 13  
 define, 77  
 define, 111  
 define, 111  
 define, 13  
 define, 147  
 define, 68  
 define, 77  
 define-datatype, 147  
 define-datatype, 147  
 define-struct, 147  
 define-struct, 14  
 define-struct, 77  
 define-struct, 147  
 define-struct, 77  
 define-struct, 14  
 define-struct, 68  
 define-struct, 135  
 delay, 149

delay, 149  
 denominator, 81  
 denominator, 21  
 denominator, 153  
 denominator, 50  
 denominator, 114  
 display, 175  
 e, 21  
 e, 153  
 e, 81  
 e, 114  
 e, 50  
 eighth, 29  
 eighth, 89  
 eighth, 122  
 eighth, 161  
 eighth, 58  
 else, 68  
 else, 135  
 else, 181  
 else, 102  
 else, 15  
 empty, 17  
 empty, 182  
 empty, 69  
 empty, 136  
 empty, 17  
 empty, 103  
 empty?, 122  
 empty?, 58  
 empty?, 161  
 empty?, 29  
 empty?, 89  
 eof, 171  
 eof, 98  
 eof, 67  
 eof, 131  
 eof, 38  
 eof-object?, 131  
 eof-object?, 171  
 eof-object?, 98  
 eof-object?, 67  
 eof-object?, 38  
 eq?, 98  
 eq?, 38  
 eq?, 131  
 eq?, 67  
 eq?, 171  
 equal?, 98  
 equal?, 38  
 equal?, 67  
 equal?, 171  
 equal?, 131  
 equal~?, 99  
 equal~?, 38  
 equal~?, 67  
 equal~?, 171  
 equal~?, 131  
 eqv?, 67  
 eqv?, 99  
 eqv?, 39  
 eqv?, 131  
 eqv?, 171  
 error, 132  
 error, 68  
 error, 99  
 error, 171  
 error, 39  
 even?, 21  
 even?, 81  
 even?, 114  
 even?, 50  
 even?, 153  
 exact->inexact, 81  
 exact->inexact, 114  
 exact->inexact, 50  
 exact->inexact, 21  
 exact->inexact, 153  
 exact?, 21  
 exact?, 153  
 exact?, 50  
 exact?, 82  
 exact?, 114  
 exit, 68

exit, 39  
exit, 99  
exit, 132  
exit, 172  
exp, 154  
exp, 114  
exp, 82  
exp, 21  
exp, 50  
explode, 127  
explode, 63  
explode, 94  
explode, 34  
explode, 167  
expt, 21  
expt, 50  
expt, 154  
expt, 114  
expt, 82  
false, 136  
false, 103  
false, 69  
false, 18  
false, 182  
false?, 119  
false?, 86  
false?, 54  
false?, 158  
false?, 26  
fifth, 29  
fifth, 89  
fifth, 58  
fifth, 161  
fifth, 122  
filter, 134  
filter, 174  
filter, 101  
first, 58  
first, 122  
first, 29  
first, 89  
first, 161  
floor, 82  
floor, 114  
floor, 50  
floor, 21  
floor, 154  
foldl, 134  
foldl, 101  
foldl, 174  
foldr, 134  
foldr, 101  
foldr, 174  
for-each, 134  
for-each, 101  
for-each, 174  
force, 172  
format, 34  
format, 94  
format, 127  
format, 167  
format, 63  
fourth, 122  
fourth, 162  
fourth, 89  
fourth, 58  
fourth, 29  
Function Calls, 148  
Function Calls, 14  
Function Calls, 78  
Function Calls, 112  
gcd, 22  
gcd, 82  
gcd, 154  
gcd, 115  
gcd, 50  
gensym, 172  
Hash Tables, 178  
hash-copy, 178  
hash-count, 178  
hash-eq?, 178  
hash-equal?, 178  
hash-eqv?, 178  
hash-for-each, 178

`hash-has-key?`, 178  
`hash-map`, 178  
`hash-ref`, 178  
`hash-ref!`, 179  
`hash-remove`, 179  
`hash-remove!`, 179  
`hash-set`, 179  
`hash-set!`, 179  
`hash-update`, 179  
`hash-update!`, 179  
`hash?`, 180  
Higher-Order Functions, 173  
Higher-Order Functions, 133  
Higher-Order Functions, 100  
*How to Design Programs* Languages, 1  
Identifiers, 17  
Identifiers, 79  
`identity`, 132  
`identity`, 68  
`identity`, 99  
`identity`, 39  
`identity`, 172  
`if`, 15  
`if`, 181  
`if`, 135  
`if`, 15  
`if`, 68  
`if`, 102  
`imag-part`, 154  
`imag-part`, 50  
`imag-part`, 22  
`imag-part`, 115  
`imag-part`, 82  
`image=?`, 38  
`image=?`, 130  
`image=?`, 66  
`image=?`, 170  
`image=?`, 98  
`image?`, 170  
`image?`, 98  
`image?`, 67  
`image?`, 131  
`image?`, 38  
Images, 170  
Images, 66  
Images, 38  
Images, 130  
Images, 98  
`implode`, 167  
`implode`, 127  
`implode`, 94  
`implode`, 63  
`implode`, 34  
`inexact->exact`, 22  
`inexact->exact`, 51  
`inexact->exact`, 154  
`inexact->exact`, 82  
`inexact->exact`, 115  
`inexact?`, 51  
`inexact?`, 115  
`inexact?`, 154  
`inexact?`, 82  
`inexact?`, 22  
`int->string`, 127  
`int->string`, 94  
`int->string`, 34  
`int->string`, 167  
`int->string`, 63  
`integer->char`, 115  
`integer->char`, 154  
`integer->char`, 22  
`integer->char`, 82  
`integer->char`, 51  
`integer-sqrt`, 51  
`integer-sqrt`, 22  
`integer-sqrt`, 82  
`integer-sqrt`, 115  
`integer-sqrt`, 154  
`integer?`, 115  
`integer?`, 154  
`integer?`, 22  
`integer?`, 83  
`integer?`, 51  
Intermediate Student, 70

Intermediate Student with Lambda, 104  
 lambda, 148  
 lambda, 111  
 lambda, 148  
 lambda, 13  
 lambda, 111  
 lambda, 68  
 lambda, 77  
 lcm, 83  
 lcm, 22  
 lcm, 51  
 lcm, 115  
 lcm, 155  
 length, 90  
 length, 162  
 length, 29  
 length, 58  
 length, 122  
 let, 149  
 let, 78  
 let, 149  
 let, 135  
 let\*, 135  
 let\*, 181  
 let\*, 78  
 letrec, 181  
 letrec, 78  
 letrec, 135  
 letrec, let, and let\*, 78  
 list, 90  
 list, 58  
 list, 162  
 list, 122  
 list, 29  
 list\*, 162  
 list\*, 30  
 list\*, 58  
 list\*, 122  
 list\*, 90  
 list->string, 34  
 list->string, 167  
 list->string, 95  
 list->string, 127  
 list->string, 63  
 list-ref, 30  
 list-ref, 122  
 list-ref, 58  
 list-ref, 162  
 list-ref, 90  
 list?, 162  
 Lists, 159  
 Lists, 55  
 Lists, 26  
 Lists, 119  
 Lists, 87  
 local, 78  
 local, 78  
 local, 181  
 local, 135  
 log, 22  
 log, 51  
 log, 83  
 log, 115  
 log, 155  
 magnitude, 155  
 magnitude, 51  
 magnitude, 115  
 magnitude, 83  
 magnitude, 22  
 make-hash, 180  
 make-hasheq, 180  
 make-hasheqv, 180  
 make-immutable-hash, 180  
 make-immutable-hasheq, 180  
 make-immutable-hasheqv, 181  
 make-list, 162  
 make-list, 30  
 make-list, 90  
 make-list, 59  
 make-list, 123  
 make-polar, 83  
 make-polar, 116  
 make-polar, 23  
 make-polar, 51

make-polar, 155  
make-posn, 31  
make-posn, 124  
make-posn, 92  
make-posn, 164  
make-posn, 60  
make-rectangular, 155  
make-rectangular, 116  
make-rectangular, 83  
make-rectangular, 23  
make-rectangular, 51  
make-string, 35  
make-string, 127  
make-string, 167  
make-string, 63  
make-string, 95  
make-vector, 176  
map, 101  
map, 134  
map, 174  
match, 151  
match, 151  
max, 52  
max, 155  
max, 23  
max, 116  
max, 83  
member, 162  
member, 90  
member, 59  
member, 30  
member, 123  
member?, 30  
member?, 123  
member?, 162  
member?, 59  
member?, 90  
memf, 101  
memf, 175  
memf, 134  
memq, 30  
memq, 59  
memq, 90  
memq, 123  
memq, 162  
memv, 90  
memv, 59  
memv, 123  
memv, 30  
memv, 163  
min, 83  
min, 52  
min, 155  
min, 116  
min, 23  
Misc, 170  
Misc, 67  
Misc, 38  
Misc, 131  
Misc, 98  
modulo, 155  
modulo, 23  
modulo, 52  
modulo, 83  
modulo, 116  
negative?, 116  
negative?, 52  
negative?, 23  
negative?, 83  
negative?, 155  
newline, 175  
not, 86  
not, 158  
not, 26  
not, 119  
not, 55  
null, 30  
null, 91  
null, 59  
null, 163  
null, 123  
null?, 123  
null?, 59  
null?, 163



[null?](#), 91  
[null?](#), 30  
[number->string](#), 84  
[number->string](#), 23  
[number->string](#), 155  
[number->string](#), 52  
[number->string](#), 116  
[number?](#), 116  
[number?](#), 84  
[number?](#), 52  
[number?](#), 156  
[number?](#), 23  
Numbers (relaxed conditions), 173  
Numbers (relaxed conditions), 132  
Numbers (relaxed conditions), 99  
Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts, 151  
Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts, 47  
Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts, 19  
Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts, 112  
Numbers: Integers, Rationals, Reals, Complex, Exacts, Inexacts, 79  
[numerator](#), 156  
[numerator](#), 52  
[numerator](#), 23  
[numerator](#), 84  
[numerator](#), 116  
[odd?](#), 116  
[odd?](#), 52  
[odd?](#), 84  
[odd?](#), 156  
[odd?](#), 23  
or, 16  
or, 16  
or, 181  
or, 69  
or, 102  
or, 135  
[ormap](#), 175  
[ormap](#), 101  
[ormap](#), 134  
[pair?](#), 59  
[pair?](#), 123  
[pair?](#), 163  
[pair?](#), 31  
[pair?](#), 91  
[pi](#), 24  
[pi](#), 117  
[pi](#), 84  
[pi](#), 156  
[pi](#), 52  
[positive?](#), 117  
[positive?](#), 156  
[positive?](#), 52  
[positive?](#), 24  
[positive?](#), 84  
[posn](#), 32  
[posn](#), 60  
[posn](#), 92  
[posn](#), 124  
[posn](#), 164  
[posn-x](#), 164  
[posn-x](#), 124  
[posn-x](#), 32  
[posn-x](#), 92  
[posn-x](#), 60  
[posn-y](#), 125  
[posn-y](#), 164  
[posn-y](#), 92  
[posn-y](#), 61  
[posn-y](#), 32  
[posn?](#), 164  
[posn?](#), 61  
[posn?](#), 125  
[posn?](#), 92  
[posn?](#), 32  
Posns, 164  
Posns, 60  
Posns, 31  
Posns, 124  
Posns, 92

[pretty-print](#), 175  
 Primitive Calls, 14  
 Primitive Operation Names, 112  
 Primitive Operations, 151  
 Primitive Operations, 47  
 Primitive Operations, 19  
 Primitive Operations, 79  
[print](#), 175  
[printf](#), 176  
[procedure?](#), 102  
[procedure?](#), 134  
[procedure?](#), 175  
[promise?](#), 172  
 Quasiquote, 47  
 quasiquote, 47  
[quicksort](#), 102  
[quicksort](#), 134  
[quicksort](#), 175  
 Quote, 46  
 quote, 17  
 quote, 46  
[quotient](#), 24  
[quotient](#), 156  
[quotient](#), 53  
[quotient](#), 84  
[quotient](#), 117  
[random](#), 84  
[random](#), 117  
[random](#), 24  
[random](#), 156  
[random](#), 53  
[rational?](#), 156  
[rational?](#), 117  
[rational?](#), 53  
[rational?](#), 84  
[rational?](#), 24  
[read](#), 176  
 Reading and Printing, 175  
[real-part](#), 117  
[real-part](#), 53  
[real-part](#), 156  
[real-part](#), 84  
[real-part](#), 24  
[real?](#), 24  
[real?](#), 85  
[real?](#), 157  
[real?](#), 117  
[real?](#), 53  
 recur, 150  
 recur, 150  
[remainder](#), 117  
[remainder](#), 157  
[remainder](#), 53  
[remainder](#), 24  
[remainder](#), 85  
[remove](#), 31  
[remove](#), 59  
[remove](#), 163  
[remove](#), 91  
[remove](#), 123  
[replicate](#), 95  
[replicate](#), 35  
[replicate](#), 63  
[replicate](#), 167  
[replicate](#), 127  
 require, 18  
 require, 103  
 require, 18  
 require, 136  
 require, 69  
 require, 182  
[rest](#), 163  
[rest](#), 60  
[rest](#), 124  
[rest](#), 31  
[rest](#), 91  
[reverse](#), 124  
[reverse](#), 91  
[reverse](#), 163  
[reverse](#), 31  
[reverse](#), 60  
[round](#), 117  
[round](#), 53  
[round](#), 157

round, 85  
round, 24  
second, 31  
second, 91  
second, 124  
second, 163  
second, 60  
set!, 149  
set!, 149  
set-box!, 177  
set-posn-x!, 164  
set-posn-y!, 164  
seventh, 163  
seventh, 91  
seventh, 31  
seventh, 60  
seventh, 124  
sgn, 157  
sgn, 53  
sgn, 118  
sgn, 25  
sgn, 85  
shared, 149  
shared, 149  
sin, 118  
sin, 25  
sin, 157  
sin, 85  
sin, 53  
sinh, 54  
sinh, 85  
sinh, 118  
sinh, 25  
sinh, 157  
sixth, 163  
sixth, 31  
sixth, 124  
sixth, 60  
sixth, 91  
sleep, 172  
sort, 175  
sort, 135  
sort, 102  
sqr, 118  
sqr, 157  
sqr, 54  
sqr, 85  
sqr, 25  
sqrt, 54  
sqrt, 157  
sqrt, 85  
sqrt, 25  
sqrt, 118  
string, 167  
string, 95  
string, 128  
string, 64  
string, 35  
string->int, 167  
string->int, 35  
string->int, 95  
string->int, 64  
string->int, 128  
string->list, 95  
string->list, 167  
string->list, 64  
string->list, 35  
string->list, 128  
string->number, 128  
string->number, 95  
string->number, 35  
string->number, 168  
string->number, 64  
string->symbol, 168  
string->symbol, 95  
string->symbol, 128  
string->symbol, 35  
string->symbol, 64  
string-alphabetic?, 128  
string-alphabetic?, 95  
string-alphabetic?, 168  
string-alphabetic?, 35  
string-alphabetic?, 64  
string-append, 64

string-append, 95  
string-append, 168  
string-append, 35  
string-append, 128  
string-ci<=?, 35  
string-ci<=?, 96  
string-ci<=?, 168  
string-ci<=?, 128  
string-ci<=?, 64  
string-ci<?, 96  
string-ci<?, 168  
string-ci<?, 128  
string-ci<?, 36  
string-ci<?, 64  
string-ci=?, 96  
string-ci=?, 168  
string-ci=?, 36  
string-ci=?, 64  
string-ci=?, 128  
string-ci>=?, 96  
string-ci>=?, 129  
string-ci>=?, 65  
string-ci>=?, 36  
string-ci>=?, 168  
string-ci>?, 168  
string-ci>?, 65  
string-ci>?, 129  
string-ci>?, 96  
string-ci>?, 36  
string-copy, 65  
string-copy, 129  
string-copy, 169  
string-copy, 96  
string-copy, 36  
string-ith, 129  
string-ith, 36  
string-ith, 96  
string-ith, 169  
string-ith, 65  
string-length, 65  
string-length, 36  
string-length, 96  
string-length, 129  
string-length, 169  
string-lower-case?, 129  
string-lower-case?, 36  
string-lower-case?, 169  
string-lower-case?, 65  
string-lower-case?, 96  
string-numeric?, 36  
string-numeric?, 97  
string-numeric?, 129  
string-numeric?, 65  
string-numeric?, 169  
string-ref, 169  
string-ref, 36  
string-ref, 97  
string-ref, 65  
string-ref, 129  
string-upper-case?, 169  
string-upper-case?, 65  
string-upper-case?, 97  
string-upper-case?, 37  
string-upper-case?, 129  
string-whitespace?, 37  
string-whitespace?, 130  
string-whitespace?, 169  
string-whitespace?, 97  
string-whitespace?, 66  
string<=?, 169  
string<=?, 130  
string<=?, 66  
string<=?, 37  
string<=?, 97  
string<?, 169  
string<?, 66  
string<?, 97  
string<?, 37  
string<?, 130  
string=?, 170  
string=?, 66  
string=?, 130  
string=?, 97  
string=?, 37

[string>=?](#), 170  
[string>=?](#), 66  
[string>=?](#), 97  
[string>=?](#), 130  
[string>=?](#), 37  
[string>?](#), 170  
[string>?](#), 37  
[string>?](#), 66  
[string>?](#), 130  
[string>?](#), 97  
[string?](#), 130  
[string?](#), 170  
[string?](#), 66  
[string?](#), 37  
[string?](#), 97  
Strings, 167  
Strings, 63  
Strings, 34  
Strings, 127  
Strings, 94  
[struct?](#), 132  
[struct?](#), 39  
[struct?](#), 99  
[struct?](#), 172  
[struct?](#), 68  
[sub1](#), 157  
[sub1](#), 54  
[sub1](#), 25  
[sub1](#), 118  
[sub1](#), 85  
[substring](#), 170  
[substring](#), 130  
[substring](#), 66  
[substring](#), 98  
[substring](#), 37  
[symbol->string](#), 158  
[symbol->string](#), 86  
[symbol->string](#), 55  
[symbol->string](#), 119  
[symbol->string](#), 26  
[symbol=?](#), 86  
[symbol=?](#), 119  
[symbol=?](#), 55  
[symbol=?](#), 26  
[symbol=?](#), 158  
[symbol?](#), 158  
[symbol?](#), 86  
[symbol?](#), 26  
[symbol?](#), 119  
[symbol?](#), 55  
Symbols, 158  
Symbols, 55  
Symbols, 26  
Symbols, 119  
Symbols, 86  
Symbols, 17  
[tan](#), 25  
[tan](#), 85  
[tan](#), 118  
[tan](#), 157  
[tan](#), 54  
Test Cases, 16  
[third](#), 60  
[third](#), 31  
[third](#), 91  
[third](#), 164  
[third](#), 124  
time, 79  
time, 79  
time, 135  
time, 181  
[true](#), 103  
[true](#), 69  
[true](#), 136  
[true](#), 182  
[true](#), 18  
[true and false](#), 18  
[unbox](#), 177  
Unchanged Forms, 68  
Unchanged Forms, 181  
Unchanged Forms, 135  
Unchanged Forms, 102  
[unless](#), 151  
[unquote](#), 47

- unquote-splicing, 47
- vector, 177
- vector-length, 177
- vector-ref, 177
- vector-set!, 177
- vector?, 177
- Vectors, 176
- void, 172
- void?, 172
- when, 151
- when and unless, 151
- with-input-from-file, 176
- with-input-from-string, 176
- with-output-to-file, 176
- with-output-to-string, 176
- write, 176
- zero?, 118
- zero?, 25
- zero?, 86
- zero?, 54
- zero?, 158
- λ, 148
- λ, 111