

Scheme: Compatibility Libraries and Executables

Version 5.3.3

February 13, 2013

Racket was once called “PLT Scheme,” and a number of libraries with names starting `scheme` provide compatibility with the old name. A few old executables are also provided.

Do not use `#lang scheme` to start new projects; `#lang racket` is the preferred language.

Contents

| | | |
|-----------|-----------------------------------|-----------|
| 1 | <code>scheme</code> | 6 |
| 2 | <code>scheme/base</code> | 7 |
| 3 | <code>scheme/async-channel</code> | 8 |
| 4 | <code>scheme/bool</code> | 9 |
| 5 | <code>scheme/class</code> | 10 |
| 6 | <code>scheme/cmdline</code> | 11 |
| 7 | <code>scheme/contract</code> | 12 |
| 8 | <code>scheme/control</code> | 13 |
| 9 | <code>scheme/date</code> | 14 |
| 10 | <code>scheme/dict</code> | 15 |
| 11 | <code>scheme/file</code> | 16 |
| 12 | <code>scheme/fixnum</code> | 17 |
| 13 | <code>scheme/flonum</code> | 18 |
| 14 | <code>scheme/foreign</code> | 19 |
| 15 | <code>scheme/function</code> | 20 |
| 16 | <code>scheme/future</code> | 21 |

| | | |
|-----------|-----------------------------------|-----------|
| 17 | <code>scheme/generator</code> | 22 |
| 18 | <code>scheme/gui</code> | 23 |
| 19 | <code>scheme/gui/base</code> | 24 |
| 20 | <code>scheme/gui/dynamic</code> | 25 |
| 21 | <code>scheme/help</code> | 26 |
| 22 | <code>scheme/include</code> | 27 |
| 23 | <code>scheme/init</code> | 28 |
| 24 | <code>scheme/language-info</code> | 29 |
| 25 | <code>scheme/list</code> | 30 |
| 26 | <code>scheme/load</code> | 31 |
| 27 | <code>scheme/local</code> | 32 |
| 28 | <code>scheme/match</code> | 33 |
| 29 | <code>scheme/math</code> | 34 |
| 30 | <code>scheme/mpair</code> | 35 |
| 31 | <code>scheme/nest</code> | 36 |
| 32 | <code>scheme/package</code> | 37 |
| 33 | <code>scheme/path</code> | 38 |

| | | |
|-----------|---------------------------------------|-----------|
| 34 | <code>scheme/port</code> | 39 |
| 35 | <code>scheme/pretty</code> | 40 |
| 36 | <code>scheme/promise</code> | 41 |
| 37 | <code>scheme/provide</code> | 42 |
| 38 | <code>scheme/provide-syntax</code> | 43 |
| 39 | <code>scheme/provide-transform</code> | 44 |
| 40 | <code>scheme/require</code> | 45 |
| 41 | <code>scheme/require-syntax</code> | 46 |
| 42 | <code>scheme/require-transform</code> | 47 |
| 43 | <code>scheme/runtime-config</code> | 48 |
| 44 | <code>scheme/runtime-path</code> | 49 |
| 45 | <code>scheme/sandbox</code> | 50 |
| 46 | <code>scheme/serialize</code> | 51 |
| 47 | <code>scheme/set</code> | 52 |
| 48 | <code>scheme/signature</code> | 53 |
| 49 | <code>scheme/shared</code> | 54 |
| 50 | <code>scheme/splicing</code> | 55 |

| | | |
|----|--------------------------------------|----|
| 51 | <code>scheme/string</code> | 56 |
| 52 | <code>scheme/struct-info</code> | 57 |
| 53 | <code>scheme/stxparam</code> | 58 |
| 54 | <code>scheme/stxparam-exptime</code> | 59 |
| 55 | <code>scheme/surrogate</code> | 60 |
| 56 | <code>scheme/system</code> | 61 |
| 57 | <code>scheme/tcp</code> | 62 |
| 58 | <code>scheme/trait</code> | 63 |
| 59 | <code>scheme/udp</code> | 64 |
| 60 | <code>scheme/unit</code> | 65 |
| 61 | <code>scheme/unit-exptime</code> | 66 |
| 62 | <code>scheme/unsafe/ops</code> | 67 |
| 63 | <code>scheme/vector</code> | 68 |
| 64 | <code>mred</code> | 69 |
| 65 | Compatibility Executables | 70 |

1 scheme

```
(require scheme)
```

The `scheme` library re-exports `racket`, except based on `scheme/base` instead of `racket/base`, the `struct` and `struct/ctc` from `scheme/unit` is exported, `scheme/set` is not re-exported, `scheme/system` is not re-exported, `pretty-print` is re-directed in as `scheme/pretty`, and `scheme/nest` is re-exported.

2 scheme/base

```
(require scheme/base)
```

The `scheme/base` library re-exports `racket/base`, except that `racket`'s `struct`, `hash`, `hasheq`, `hasheqv`, `in-directory`, and `local-require` are not exported, and `make-base-namespace` and `make-base-empty-namespace` are different.

■ `(make-base-empty-namespace)` → namespace?

Like `make-base-empty-namespace` from `racket/base`, but with `scheme/base` attached.

■ `(make-base-namespace)` → namespace?

Like `make-base-namespace` from `racket/base`, but with `scheme/base` attached.

3 `scheme/async-channel`

```
(require scheme/async-channel)
```

The `scheme/async-channel` library re-exports `racket/async-channel`.

4 `scheme/bool`

```
(require scheme/bool)
```

The `scheme/bool` library re-exports `racket/bool`.

5 `scheme/class`

```
(require scheme/class)
```

The `scheme/class` library re-exports `racket/class`, except that `writable<%>` is exported under the name `printable<%>` (and `printable<%>` from `racket/class` is not exported).

```
| printable<%> : interface?
```

An alias for `writable<%>`.

6 `scheme/cmdline`

```
(require scheme/cmdline)
```

The `scheme/cmdline` library re-exports `racket/cmdline`.

7 `scheme/contract`

```
(require scheme/contract)
```

The `scheme/contract` library re-exports `racket/contract`.

8 `scheme/control`

```
(require scheme/control)
```

The `scheme/control` library re-exports `racket/control`.

9 `scheme/date`

```
(require scheme/date)
```

The `scheme/date` library re-exports `racket/date`.

10 `scheme/dict`

```
(require scheme/dict)
```

The `scheme/dict` library re-exports `racket/dict`.

11 `scheme/file`

```
(require scheme/file)
```

The `scheme/file` library re-exports `racket/file`.

12 `scheme/fixnum`

```
(require scheme/fixnum)
```

The `scheme/fixnum` library re-exports `racket/fixnum`.

13 `scheme/flonum`

```
(require scheme/flonum)
```

The `scheme/flonum` library re-exports `racket/flonum`.

14 `scheme/foreign`

```
(require scheme/foreign)
```

The `scheme/foreign` library re-exports `ffi/unsafe`, `ffi/unsafe/cvector`, and `ffi/vector`, except that `unsafe!` must be used to import the unsafe bindings of `ffi/unsafe` and `ffi/unsafe/cvector`.

```
| (unsafe!)
```

Makes unsafe bindings available.

```
| (provide* provide-star-spec ...)  
| provide-star-spec = (unsafe id)  
|                   | (unsafe (rename-out [id external-id]))  
|                   | provide-spec
```

Like `provide`, but `ids` under `unsafe` are not actually provided. Instead, they are collected for introduction into an importing module via a macro created by `define-unsafes`.

```
| (define-unsafes id)
```

Cooperates with `provide*` to define `id` as a `unsafe!`-like form that introduces definitions for each binding provided as `unsafe`. The `define-unsafes` form must occur after all the `provide*` forms to which it refers.

15 `scheme/function`

```
(require scheme/function)
```

The `scheme/function` library re-exports `racket/function`.

16 `scheme/future`

```
(require scheme/future)
```

The `scheme/future` library re-exports `racket/future`.

17 `scheme/generator`

```
(require scheme/generator)
```

The `scheme/generator` library re-exports `racket/generator`.

18 `scheme/gui`

```
(require scheme/gui)
```

The `scheme/gui` library re-exports `racket/gui`, except that it builds on `scheme/gui/base` instead of `racket/gui/base`.

19 `scheme/gui/base`

```
(require scheme/gui/base)
```

The `scheme/gui/base` library re-exports `racket/gui/base`, except that it builds on `scheme` instead of `racket`.

■ `(make-gui-empty-namespace)` → namespace?

Like `make-base-empty-namespace`, but with `scheme/class` and `scheme/gui/base` also attached to the result namespace.

■ `(make-gui-namespace)` → namespace?

Like `make-base-namespace`, but with `scheme/class` and `scheme/gui/base` also required into the top-level environment of the result namespace.

20 `scheme/gui/dynamic`

```
(require scheme/gui/dynamic)
```

The `scheme/gui/dynamic` library re-exports `racket/gui/dynamic`, except that `gui-dynamic-require` extracts bindings from `mred` instead of `scheme/gui/base`.

```
(gui-dynamic-require sym) → any  
  sym : symbol?
```

Like `gui-dynamic-require` from `racket/gui/base`, but to access exports of `scheme/gui/base`.

21 `scheme/help`

```
(require scheme/help)
```

The `scheme/help` library re-exports `racket/help`.

22 `scheme/include`

```
(require scheme/include)
```

The `scheme/include` library re-exports `racket/include`.

23 `scheme/init`

```
(require scheme/init)
```

The `scheme/init` library re-exports `racket/init`, except that it builds on `scheme` instead of `racket`.

24 `scheme/language-info`

```
(require scheme/language-info)
```

The `scheme/language-info` library is like `racket/language-info`, except that it produces `'(#(scheme/runtime-config configure #f))` for the `'configure-runtime` information key.

See also `scheme/runtime-config`.

25 `scheme/list`

```
(require scheme/list)
```

The `scheme/list` library re-exports `racket/list`.

26 `scheme/load`

```
(require scheme/load)
```

The `scheme/load` library re-exports `racket/load`.

27 `scheme/local`

```
(require scheme/local)
```

The `scheme/local` library re-exports `racket/local`.

28 `scheme/match`

```
(require scheme/match)
```

The `scheme/match` library re-exports `racket/match`.

29 `scheme/math`

```
(require scheme/math)
```

The `scheme/math` library re-exports `racket/math`.

30 `scheme/mpair`

```
(require scheme/mpair)
```

The `scheme/mpair` library re-exports `compatibility/mlist`.

31 scheme/nest

```
(require scheme/nest)
| (nest ([datum ...+] ...) body ...+)
```

Combines nested expressions that syntactically drift to the right into a more linear textual format, much in the same way that `let*` linearizes a sequence of nested `let` expressions.

For example,

```
(nest ([let ([x 10]
            [y 6]])
      [with-handlers ([exn:fail? (lambda (x) 15)])]
      [parameterize ([current-output-port (current-error-port)])]
      [let-values ([d r] (quotient/remainder x y))])
      (display (+ d r)))
```

is equivalent to

```
(let ([x 10]
      [y 6])
  (with-handlers ([exn:fail? (lambda (x) 15)])
    (parameterize ([current-output-port (current-error-port)])
      (let-values ([d r] (quotient/remainder x y))
        (display (+ d r))))))
```

The `nest` form is unusual in that it has no semantics apart from its expansion, and its implementation is easier to understand than a precise prose description:

```
(define-syntax nest
  (syntax-rules ()
    [(nest () body0 body ...)
     (let () body0 body ...)]
    [(nest ([form forms ...]) body0 body ...)
     (form forms ... (let () body0 body ...))]
    [(nest ([form forms ...] . more) body0 body ...)
     (form forms ... (nest more body0 body ...))]))
```

32 `scheme/package`

```
(require scheme/package)
```

The `scheme/package` library re-exports `compatibility/package`.

33 `scheme/path`

```
(require scheme/path)
```

The `scheme/path` library re-exports `racket/path`.

34 `scheme/port`

```
(require scheme/port)
```

The `scheme/port` library re-exports `racket/port`.

35 `scheme/pretty`

```
(require scheme/pretty)
```

The `scheme/pretty` library re-exports `racket/pretty`, except that `pretty-write` is exported under the name `pretty-print` (and `pretty-print` from `racket/pretty` is not exported).

```
(pretty-print v [port]) → void?  
  v : any/c  
  port : output-port? = (current-output-port)
```

An alias for `pretty-write`.

36 `scheme/promise`

```
(require scheme/promise)
```

The `scheme/promise` library re-exports `racket/promise`.

37 `scheme/provide`

`(require scheme/provide)`

The `scheme/provide` library re-exports `racket/provide`.

38 `scheme/provide-syntax`

```
(require scheme/provide-syntax)
```

The `scheme/provide-syntax` library re-exports `racket/provide-syntax`.

39 `scheme/provide-transform`

```
(require scheme/provide-transform)
```

The `scheme/provide-transform` library re-exports `racket/provide-transform`.

40 `scheme/require`

```
(require scheme/require)
```

The `scheme/require` library re-exports `racket/require`.

41 `scheme/require-syntax`

```
(require scheme/require-syntax)
```

The `scheme/require-syntax` library re-exports `racket/require-syntax`.

42 `scheme/require-transform`

```
(require scheme/require-transform)
```

The `scheme/require-transform` library re-exports `racket/require-transform`.

43 `scheme/runtime-config`

```
(require scheme/runtime-config)
```

The `scheme/runtime-config` library is like `racket/runtime-config`, except that the result of its `configure` function is a procedure that sets `print-as-expression` to `#f`.

44 `scheme/runtime-path`

```
(require scheme/runtime-path)
```

The `scheme/runtime-path` library re-exports `racket/runtime-path`.

45 scheme/sandbox

```
(require scheme/sandbox)
```

The `scheme/sandbox` library re-exports `racket/sandbox`, except that `sandbox-namespace-specs`, `make-evaluator`, and `make-module-evaluator` are replaced.

```
(sandbox-namespace-specs) → (cons/c (-> namespace?)
                                   (listof module-path?))
(sandbox-namespace-specs spec) → void?
spec : (cons/c (-> namespace?)
            (listof module-path?))
```

Like `sandbox-namespace-specs` from `racket/sandbox`, but the default is `(list make-base-namespace)` if `gui?` is `#f`, `(list make-gui-namespace)` if `gui?` is `#t`.

```
(make-evaluator language
                input-program ...
                #:requires requires
                #:allow-read allow) → (any/c . -> . any)
                                   (or/c module-path?
                                   language : (list/c 'special symbol?)
                                             (cons/c 'begin list?))
                                   input-program : any/c
                                   requires : (listof (or/c module-path? path?))
                                   allow : (listof (or/c module-path? path?))
(make-module-evaluator module-decl
                       #:language lang
                       #:allow-read allow) → (any/c . -> . any)
                                   module-decl : (or/c syntax? pair?)
                                   lang : (or/c #f module-path?)
                                   allow : (listof (or/c module-path? path?))
```

Like `make-evaluator` and `make-module-evaluator` from `racket/sandbox`, but the value of the `sandbox-namespace-specs` parameter is installed as the value of `sandbox-namespace-specs` from `racket/sandbox` before chaining to `make-evaluator` and `make-module-evaluator` from `racket/sandbox`.

46 `scheme/serialize`

```
(require scheme/serialize)
```

The `scheme/serialize` library re-exports `racket/serialize`.

47 `scheme/set`

```
(require scheme/set)
```

The `scheme/set` library re-exports `racket/set`.

48 `scheme/signature`

```
(require scheme/signature)
```

The `scheme/signature` library re-exports `racket/signature`.

49 `scheme/shared`

```
(require scheme/shared)
```

The `scheme/shared` library re-exports `racket/shared`.

50 `scheme/splicing`

```
(require scheme/splicing)
```

The `scheme/splicing` library re-exports `racket/splicing`.

51 `scheme/string`

```
(require scheme/string)
```

The `scheme/string` library re-exports `racket/string`.

52 `scheme/struct-info`

```
(require scheme/struct-info)
```

The `scheme/struct-info` library re-exports `racket/struct-info`.

53 `scheme/stxparam`

```
(require scheme/stxparam)
```

The `scheme/stxparam` library re-exports `racket/stxparam`.

54 `scheme/stxparam-exptime`

```
(require scheme/stxparam-exptime)
```

The `scheme/stxparam-exptime` library re-exports `racket/stxparam-exptime`.

55 `scheme/surrogate`

`(require scheme/surrogate)`

The `scheme/surrogate` library re-exports `racket/surrogate`.

56 `scheme/system`

`(require scheme/system)`

The `scheme/system` library re-exports `racket/system`.

57 `scheme/tcp`

```
(require scheme/tcp)
```

The `scheme/tcp` library re-exports `racket/tcp`.

58 `scheme/trait`

```
(require scheme/trait)
```

The `scheme/trait` library re-exports `racket/trait`.

59 `scheme/udp`

```
(require scheme/udp)
```

The `scheme/udp` library re-exports `racket/udp`.

60 `scheme/unit`

```
(require scheme/unit)
```

The `scheme/unit` library re-exports `racket/unit`, except that `struct` and `struct/ctc` are `struct~s` and `struct~s/ctc` from `mzlib/unit` instead of `struct` from `racket/base` and `struct/ctc` from `racket/unit`.

61 `scheme/unit-exptime`

```
(require scheme/unit-exptime)
```

The `scheme/unit-exptime` library re-exports `racket/unit-exptime`.

62 `scheme/unsafe/ops`

```
(require scheme/unsafe/ops)
```

The `scheme/unsafe/ops` library re-exports `racket/unsafe/ops`.

63 `scheme/vector`

```
(require scheme/vector)
```

The `scheme/vector` library re-exports `racket/vector`.

64 mred

```
(require mred)
```

The `mred` library is like `scheme/gui/base`, except that it provides variants of `make-gui-namespace` and `make-gui-empty-namespace` that attach `mred` instead of `scheme/gui/base`.

Both `scheme/gui/base` and `racket/gui/base` depend on `mred`, so it is attached by all variants of `make-gui-empty-namespace`.

```
(require mred/mred)
```

The `mred` library actually just re-exports `mred/mred`, which is an even older name for the library.

65 Compatibility Executables

The following executables are included in the Racket distribution for compatibility with older versions of Racket:

- `mzscheme` — the same as `racket -I scheme/init`
- `mred` — the same as `gracket -I scheme/gui/init`
- `drscheme` — the same as `drracket`
- `mzc` — an old interface to some of the tools provided by `raco`, including `raco make` and `raco ctool`; use `mzc --help` for more information
- `plt-help` — the same as `raco docs`